


# RS PRO 5100 SC

with motion detector & Bluetooth  
 EAN 4007841 078881  
 Article number 078881



## Function description

Our engineers agreed: The new damp-proof light should be simple and good. Easy to install and maintain, good in energy efficiency, function and quality. The moisture-proof luminaire the world has been waiting for. Robust, highly functional, child's play to install, wireless to network and ultimately convenient to adjust via smartphone. 360° high-frequency sensor, 10 m range. With 4250 lm at 31 W and 4000 K. No unintentional switch-off thanks to presence mode.

## Technical specifications

Dimensions (L x W x H)	1370 x 87 x 58 mm	Luminous flux total product	4250 lm
With lamp	Yes, LED lamp	Total product efficiency	137 lm/W
With motion detector	Yes	Colour temperature	4000 K
Manufacturer's Warranty	5 years	Colour variation LED	SDCM3
Settings via	Bluetooth	Lamp	LED cannot be replaced
Version	with motion detector & Bluetooth	LED cooling system	Passive Thermo Control
PU1, EAN	4007841078881	Twilight setting	2 – 2000 lx
Colour	grey	Time setting	5 s – 60 Min.
Installation site	wall, ceiling	Basic light level function	Yes
Installation	Wall, Ceiling, Surface wiring	Basic light level function time	1-60 min
Impact resistance	IK07	Main light adjustable	10 - 100 %
IP-rating	IP65	Interconnection	Yes
Protection class	II	Interconnection via	Bluetooth
Ambient temperature	-20 – 40 °C	Lebensdauer LED nach IEC-62717 (L70)	100.000 h
Housing material	Plastic	Lebensdauer LED nach IEC-62717 (L80)	68.000 h
Cover material	Plastic, structured	Lebensdauer LED nach IES TM-21 (L70)	>60.000 h
Mains power supply	220 – 240 V / 50 – 60 Hz	Lebensdauer LED nach IES TM-21 (L80)	>60.000 h

# RS PRO 5100 SC

with motion detector & Bluetooth  
EAN 4007841 078881  
Article number 078881



## Technical specifications


Power consumption	0,41 W	Absicherung B10 (ST)	41
Mounting height max.	3,50 m	Absicherung B16 (ST)	65
Detection	also through glass, wood and stud walls	Absicherung C10 (ST)	67
Angle of aperture	160 °	Absicherung C16 (ST)	108
Electronic scalability	Yes	Basic light level function in per cent	0 – 100 %
Mechanical scalability	No	Output	31 W
Reach, radial	Ø 10 m (79 m <sup>2</sup> )	Colour Rendering Index CRI	= 82
Reach, tangential	Ø 10 m (79 m <sup>2</sup> )	Photobiological safety in accordance with EN 62471	RG1
Transmitter power	< 1 mW	Starting current, maximum	14,8 A

# RS PRO 5100 SC

with motion detector & Bluetooth  
EAN 4007841 078881  
Article number 078881




## Detection Zone




Mögliche Montagehöhe: ~ 3,50 m  
Orange: radial und tangential

## Dimension Drawing



## Master circuit diagram



# RS PRO 5100 SC

with motion detector & Bluetooth  
EAN 4007841 078881  
Article number 078881



## Master/slave and master/master interconnection circuit diagram

