

Tool finder for cables

Cable category	Cable image / Cross-section	Cable designation / Symbol	Stripping of cable sheath	Stripping of insulation
Control and electronic lines (flexible lines)		PVC single-conductor cable, single-strand H07V	–	5 6 7 30
		Light rubber hose cable, fine-stranded Ölflex® Classic 100	17 18 20	1 5 6 16
		Heavy rubber hose cable, fine-stranded H07RN-F	24	3 5 7 16 30
		PUR connection and control line, fine-stranded H07BQ-F	20 24 29	5 6 29 30
		Silicone connection and control line, fine-stranded SiHF (Ölflex® Heat 180)	10 20 30	3 16 30
		Twin loudspeaker cable, fine-stranded (N)YFAZ	–	3 5 7
		Solar cable H1Z2Z2	–	4
		Rubber hose cable, fine-stranded NSSHÖU	18 20 21	1 5 6 30
		Medium PVC hose cable, fine-stranded H05VV-F	10 24	5 6 7 16 17
		Signal and energy cable with RADOX®, multi-stranded RADOX® 125	–	1 3
		PVC control line H05VV5-F (Ölflex® 140)	17 18 20 21	5 6 7 30
		Screened control lines Helukabel F-CY-JZ / Ölflex® Classic 115 CY	20 27 30	5 6 7 30
		Fibre optics (glass-fibre cable) A-DQ(ZN)B2Y / (LWL)	21	13 14
		Electronic line, fine-stranded LiYY	10 24	5 6 7 8
		PVC control line with UL/CSA AWM Ölflex® 191	–	5 6 7 30
		PTFE connection and control line, fine-stranded Ölflex® Heat 260 MC	20 24	1 3
		PVC flat cable, fine-stranded YDY	9 25	5 6 7 25
	Installation lines (massive lines)		PVC common round cable NYM	15 27 30
		Halogen-free common round cable (PVC-free) NHXMH	–	
		Ribbon cable NYIF-J	–	
		Installation line (concrete cable) NI2XY	20 29 30	
Data cable		Data cable (twisted pair) UTP/FTP/STP (CAT5, CAT6, CAT7)	26 30	11 12 30
		Coax cable RG 58/59/62/6/7/11	23 24 30	23 24 30
Communication cables and lines		Telephone cable (communication cable), single-strand – J-Y(ST)Y	10 20 24	5 6 30
		Telephone flat cable 4P/6P/8P	9 24 25	–
		Industrial electronic line, seven-strand design JE-LiYCY	10 24 30	2 5 6
		Bell wire, single-strand YR	10 20 24	5 6 30
High-voltage cable		PCV high-voltage cable with copper conductors (earth cable) – NYY-J/-O (/NYCWY)	20 21 22	–

1	11 XX 160		16	13 6X 180	
2	11 82 130		17	13 XX 200	
3	12 12 06 12 12 10		18	16 20 16	
4	12 12 11 12 12 12		19	16 20 28	
5	12 40 200		20	16 20 165	
6	12 42 195		21	16 30 135 16 30 145	
7	12 50 200		22	16 40 150	
8	12 62 180		23	16 60 05	
9	12 64 180		24	16 60 06	
10	12 74 180		25	16 64 125	
11	12 80 040		26	16 65 125	
12	12 80 100		27	16 80 125	
13	12 82 130		28	16 85 125	
14	12 85 100		29	16 90 130	
15	13 4X 165		30	16 95 0X	

L206 00055 EN-00

Recommendation and selection from our comprehensive range of stripping tools

! Please observe the relevant capacity range of the tools !