
Relion® protection and control

Improved network reliability



Relion® protection and control

Improved network reliability

The Relion® product family offers a full range of native IEC 61850 products for the protection, control, measurement and supervision of power systems.

To ensure interoperable and future-proof solutions, the Relion series products have been designed to implement the core values of the IEC 61850 standard. Using these products, you benefit from ABB's leading-edge technology, global application knowledge and experienced support network.

The Relion technology is a forerunner in the field of protection and control in power systems. Our products are continuously improved to meet the market requirements and deeply rooted in our vast experience of developing successful protection and control relays.

The Relion products implement the core values of the IEC 61850 standard and operating with other equipment and systems that conform to this standard, they are capable of running multiple communication tasks, including horizontal GOOSE messaging. Communication also runs smoothly with other manufacturer's products, which comply with the IEC 61850 standard.

The Relion Interactive Selection Guide (ISG) helps you select the protection relay type that is the most suitable for your application. The Relion ISG is available at <http://abb.relionisg.com>



	Type	605 series	611 series	615 series
Applications				
Feeder protection and control	REF			
Motor protection and control	REM			
Transformer protection and control	RET			
Generator protection and control	REG			
Voltage protection and control	REU			
Line differential protection and control	RED			
Line distance protection	REL			
Bay control	REC			
Busbar protection	REB			
Phasor measurement	RES			
Self-powered feeder protection	REJ			
Capacitor bank protection and control	REV			
Breaker protection	REQ			
Railway protection	RER			
Key features				
Auxiliary source		Self-powered or auxiliary source (AC/DC)	Auxiliary source (AC/DC)	Auxiliary source (AC/DC)
Analog input		Conventional or sensor	Conventional	Conventional or sensor
Case type		Fixed	Withdrawable plug-in unit	Withdrawable plug-in unit
Display			4-line display 8 programmable LEDs	4-line display (or option with 10 lines and customizable graphical display) 11 programmable LEDs (2 colors)
Control - Command			Open/close push button	Open/close push button
Programming Interface		Display	Display PCM600 software configuration Web browser	Display PCM600 software configuration Web browser
Communication protocols		Modbus RTU	Modbus TCP/IP serial IEC 61850	Modbus TCP/IP serial IEC 61850 Profibus DPV1 adapter Ethernet redundancy PRP and HSR DNP3 TCP/IP serial IEC 60870-5-103 Process bus (IEC 61850-9-2 LE) Arc fault protection (optional)
Additional functionality				
Additional input /output			Optional I/O card depending on product version RIO600	Optional I/O card depending on product version RIO600

ABB also offers a range of complementary products to facilitate power system automation in substations.

RIO600 is a remote unit to extend the number of input/output ports on the relays (IEC 61850 communication protocol).



COM600 series devices perform the combined role of a user interface, a communication gateway and an automation platform in a single physical unit to facilitate substation operations and data management.



620 series	630 series	650 series	670 series
		RET650	RET670
			RET670
Auxiliary source (AC/DC)	Auxiliary source (AC/DC)	Auxiliary source (AC/DC or DC only)	Auxiliary source (DC)
Conventional or sensor	Conventional	Conventional	Conventional and/or sensor
Withdrawable plug-in unit	Detachable display	3U or 6U depending on version	Different case sizes 6U
10-line display and customizable graphical display	Display 320 x 240 pixels and customizable graphical display	Display 320 x 240 pixels and customizable graphical display	Display 320x 240 pixels and customizable graphical display
11 programmable LEDs (2 colors)	15 programmable LEDs (3 colors)	15 programmable LEDs (3 colors)	15 programmable LEDs (3 colors)
Open/close push button	Open/close push button	Open/close push button	Open/close push button
16 programmable buttons	5 programmable buttons	5 programmable buttons	5 programmable buttons
Display	Display	Display	Display
PCM software configuration	PCM600 software configuration	PCM600 software configuration	PCM600 software configuration
Web browser	Web browser		
Modbus TCP/IP/serial	IEC 61850	IEC 61850	IEC 61850
IEC 61850	DNP3 TCP/IP serial	Ethernet redundancy PRP	Ethernet redundancy PRP
Ethernet redundancy PRP and HSR	IEC 60870-5-103	DNP3 TCP/IP serial	DNP3 TCP/IP serial /SPA/LON
DNP3 TCP/IP serial		IEC 60870-5-103	IEC 60870-5-103
IEC 60870-5-103			IEC 61850-9-2 LE
Arc fault protection (optional)			
Optional I/O card depending on product version	Optional I/O cards depending on product version	Optional I/O card depending on product version	Optional I/O card depending on product version
RIO600	RIO600		

ABB Distribution Solutions
Distribution Automation

P.O. Box 699
FI-65101 Vaasa, Finland
Phone: +358 10 22 11

ABB Distribution Automation

Maneja, Vadodara – 390013, India
Phone: +91 265 260 4386
Fax: +91 265 263 8922

ABB Grid Automation Products

721 59 Västerås, Sweden
Phone: +46 (0) 21 32 50 00

www.abb.com/substationautomation
www.abb.com/reliion

We reserve the right to make technical changes or modify the contents of this document without prior notice. ABB assumes no responsibility for any potential errors or possible lack of information in this document.

We reserve all rights to this document, topics and illustrations contained in this document. Any reproduction, disclosure to third parties or utilization of its contents, in whole or in part is prohibited without the prior written consent of ABB.