











Tool finder for cables

Cable category	Cable image / Cross-section		Cable designation / Symbol	Stripping of cable sheath	Stripping of insulation
Control and electronic lines (flexible lines)			PVC single-conductor cable, single-strand H07V	–	5 6 7 30
			Light rubber hose cable, fine-stranded Ölflex® Classic 100	17 18 20	1 5 6 16
			Heavy rubber hose cable, fine-stranded H07RN-F	24	3 5 7 16 30
			PUR connection and control line, fine-stranded H07BQ-F	20 24 29	5 6 29 30
			Silicone connection and control line, fine-stranded SiHF (Ölflex® Heat 180)	10 20 30	3 16 30
			Twin loudspeaker cable, fine-stranded (N)YFAZ	–	3 5 7
			Solar cable H1Z2Z2	–	4
			Rubber hose cable, fine-stranded NSSHÖU	18 20 21	1 5 6 30
			Medium PVC hose cable, fine-stranded H05VV-F	10 24	5 6 7 16 17
			Signal and energy cable with RADOX®, multi-stranded RADOX® 125	–	1 3
			PVC control line H05VV5-F (Ölflex® 140)	17 18 20 21	5 6 7 30
			Screened control lines Helukabel F-CY-JZ/Ölflex® Classic 115 CY	20 27 30	
			Fibre optics (glass-fibre cable) A-DQ(ZN)B2Y/(LWL)	21	13 14
			Electronic line, fine-stranded LiYY	10 24	5 6 7 8
			PVC control line with UL/CSA AWM Ölflex® 191		5 6 7 30
			PTFE connection and control line, fine-stranded Ölflex® Heat 260 MC	20 24	1 3
			PVC flat cable, fine-stranded YDY	9 25	5 6 7 25
Installation lines (massive lines)			PVC common round cable NYM	15 27 30	5 6 7 16 17
			Halogen-free common round cable (PVC-free) NHXMH		
			Ribbon cable NYIF-J	–	
			Installation line (concrete cable) NI2XY	20 29 30	
Data cable			Data cable (twisted pair) UTP/FTP/STP (CAT5, CAT6, CAT7)	26 30	11 12 30
			Coax cable RG 58/59/62/6/7/11	23 24 30	23 24 30
Communication cables and lines			Telephone cable (communication cable), single-strand – J-Y(ST)Y	10 20 24	5 6 30
			Telephone flat cable 4P/6P/8P	9 24 25	–
			Industrial electronic line, seven-strand design JE-LiYCY	10 24 30	2 5 6
			Bell wire, single-strand YR	10 20 24	5 6 30
High-voltage cable			PCV high-voltage cable with copper conductors (earth cable) – NYY-J/-O (/NYCWY)	20 21 22	–

1 11 XX 160 	16 13 6X 180 
2 11 82 130 	17 13 XX 200 
3 12 12 06 12 12 10 	18 16 20 16 
4 12 12 11 12 12 12 	19 16 20 28 
5 12 40 200 	20 16 20 165 
6 12 42 195 	21 16 30 135 16 30 145 
7 12 50 200 	22 16 40 150 
8 12 62 180 	23 16 60 05 
9 12 64 180 	24 16 60 06 
10 12 74 180 	25 16 64 125 
11 12 80 040 	26 16 65 125 
12 12 80 100 	27 16 80 125 
13 12 82 130 	28 16 85 125 
14 12 85 100 	29 16 90 130 
15 13 4X 165 	30 16 95 0X 

Recommendation and selection from our comprehensive range of stripping tools

! Please observe the relevant capacity range of the tools !