

A man with a beard, wearing a dark plaid shirt, is working in a warehouse. He is holding a long, rectangular LED light fixture up to the ceiling, which has a grid of metal beams. The background shows industrial shelving and various equipment. The lighting is dramatic, with the man's face and the light fixture being the main sources of illumination.

**PHILIPS**

LED lighting

**REAL  
PROs**  
**REAL  
QUALITY**

# Professional Trade Lighting catalogue

Discover our wide portfolio of smart and efficient LED lighting solutions for both indoor and outdoor applications.

2020  
Q3

# Why choose Philips for lighting solutions

An **LED light** for every need,  
from the **world leader** in lighting

## Best products:

Our LED lighting provides you with:

### Unbeatable quality

Industry-leading reliability ensures our lights keep their output and light quality over the full warranted lifetime.

### Easy to install

The efficient design of our CoreLine fixtures enables replacement of existing lights, with no need for expensive rewiring or new ceiling configurations. Our LED lamps are compatible with most dimmers and transformers for easy installation, retaining their full specifications and lifetimes for lowest Total Cost of Ownership.

### Leading the way


With Philips lighting you get much more than high quality and easy to install lighting solutions – you get LED lighting that's setting the standard in the industry. It has never been easier to bring the power of connected lighting to small and medium sized projects, thanks to our Interact Ready range that works seamlessly with the intuitive Interact Pro software.

Some products in this catalogue are made to order.  
Please contact our order desk for more information:  
[professional.trade.lighting@signify.com](mailto:professional.trade.lighting@signify.com)

For the full dimmer and transformer compatibility list, visit:  
[www.lighting.philips.com/main/products/ledlamps](http://www.lighting.philips.com/main/products/ledlamps)

# Product codes explained

| Code     | Explanation                                |
|----------|--------------------------------------------|
| BCS      | Bracket                                    |
| BK       | Black                                      |
| DALI     | Dimmable                                   |
| EL3/ELB3 | Emergency                                  |
| GR       | Grey                                       |
| IA1      | Interact Ready                             |
| MB       | Medium Beam                                |
| MDU      | Motion Detector Unit                       |
| MSE      | Multisensor                                |
| NB       | Narrow Beam                                |
| NOC      | Non Office Compliant                       |
| OC       | Office Compliant                           |
| PSD/PSED | DALI dimmable working on central emergency |
| PSED-E   | Power supply unit with DALI interface      |
| PSR      | Power supply unit regulating               |
| PSU      | Non Dimmable                               |
| RC       | Recessed                                   |
| RS       | Recessed Spot                              |
| SC       | Safety Cable                               |
| SI       | Silver                                     |
| SM       | Surface Mounted                            |
| SMS      | Suspension                                 |
| SP       | Suspended                                  |
| VWB      | Very Wide Beam                             |
| WB       | Wide Beam                                  |
| WH       | White                                      |
| WL       | Wall Mount                                 |
| WT       | Waterproof Batten                          |



# Select the right LED luminaire or lamp

A partner that understands the challenges you face, saves you time.  
Which is why we offer a comprehensive portfolio of LED luminaires and lamps.  
The right product, for every job. For more information and online tools, check:  
[www.lighting.philips.co.uk/home](http://www.lighting.philips.co.uk/home)

| Lamps       |    | CorePro                                                 | MASTER Value                                                    | MASTER                                                    | MasterConnect <small>interact ready.</small>                          |
|-------------|----|---------------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------------------|
| Solution    | ⚙️ | Simple replacement of fluorescent tubes for average use | Strong performance in demanding applications with intense usage | Best in class performance for very demanding applications | For smart lighting applications with personal/automated light control |
| Performance | 💡  | 💡💡💡💡💡                                                   | 💡💡💡💡💡                                                           | 💡💡💡💡💡                                                     | 💡💡💡💡💡                                                                 |
| Price       | 📊  | € € € € € €                                             | € € € € € €                                                     | € € € € € €                                               | € € € € € €                                                           |
| Products    | 📌  | 167 types                                               | 60 types                                                        | 132 types                                                 | 1 type                                                                |
| Life span   | 🕒  | 30,000                                                  | 50,000                                                          | 50,000 - 70,000                                           | 50,000<br>+ insight into remaining life span                          |
| Warranty    | 🕒  | 3 years                                                 | 5 years                                                         | 5 years                                                   | 5 years                                                               |

| Luminaires  |    | Ledinaire                           | CoreLine                                              | CoreLine Interact Ready <small>interact ready.</small>                |
|-------------|----|-------------------------------------|-------------------------------------------------------|-----------------------------------------------------------------------|
| Solution    | ⚙️ | Essential range of trusted products | Suitable for every project where light really matters | For smart lighting applications with personal/automated light control |
| Performance | 💡  | 💡💡💡💡💡                               | 💡💡💡💡💡                                                 | 💡💡💡💡💡                                                                 |
| Price       | 📊  | € € € € € €                         | € € € € € €                                           | € € € € € €                                                           |
| Products    | 📌  | 13 types                            | 17 types                                              | 6 types                                                               |
| Life span   | 🕒  | 50,000 L65/L70                      | 50,000 L70/L80                                        | 50,000<br>+ insight into remaining life span                          |
| Warranty    | 🕒  | 5 years                             | 5 years                                               | 5 years                                                               |

# Contents

## 8 Connected Lighting

- 8 Interact Pro - Gateway
- 8 CoreLine Interact Ready waterproof
- 9 CoreLine Interact Ready recessed luminaire
- 10 CoreLine Interact Ready panel
- 11 CoreLine Interact Ready surface-mounted luminaire
- 12 CoreLine Interact Ready downlight
- 12 CoreLine Interact Ready slim downlight
- 13 CoreLine batten
- 13 Smart wall-switch
- 13 Smart sensor

## 14 CoreLine LED luminaires

- 15 CoreLine panel
- 17 CoreLine recessed luminaire
- 19 CoreLine surface-mounted luminaire
- 21 CoreLine wall-mounted luminaire
- 24 CoreLine waterproof
- 26 CoreLine downlight
- 28 CoreLine slim downlight
- 29 CoreLine recessed spot
- 31 CoreLine projector
- 31 CoreLine bollard
- 32 CoreLine highbay
- 34 CoreLine batten
- 36 CoreLine trunking
- 40 CoreLine tempo
- 43 CoreLine malaga



## 44 Ledinaire LED luminaires

- 45 Ledinaire panel
- 45 Ledinaire recessed and Ledinaire surface-mounted
- 46 Ledinaire wall-mounted
- 47 Ledinaire downlight
- 48 Ledinaire slim downlight
- 48 Ledinaire Zadora
- 49 Ledinaire ClearAccent
- 49 Ledinaire waterproof
- 50 Ledinaire floodlight mini
- 51 Ledinaire floodlight maxi
- 51 Ledinaire batten
- 52 Ledinaire Cove Lighting Batten
- 53 Ledinaire Pentura mini LED
- 53 Ledinaire highbay



## 54 LED lamps and tubes

- 56 LED spot MV GU10
- 58 LED spot LV MR16
- 60 LED spot LV AR111
- 61 LED spot LV MR11
- 62 LED spot MV PAR
- 63 CorePro LEDspot MV Reflectors
- 63 CorePro R7S
- 64 CorePro LEDcapsule LV G4
- 65 CorePro LEDcapsule MV G9
- 66 Standard bulbs
- 68 Filament bulbs
- 69 Classic LEDbulb ST64
- 70 LED Globes
- 71 MASTER LEDcandle
- 72 Classic LEDcandle
- 74 Classic LEDlustre
- 77 LEDtube T8
- 82 LEDtube T5
- 85 LED starter
- 85 LED PL-C
- 86 LED PL-L
- 86 LED PL-S
- 87 LED tube Circular
- 90 TrueForce
- 93 Vintage (spiral) filament lamps
- 93 Vintage cord pendants
- 94 Smoky filament lamps, Eyecatch & Crown Mirror



# The future is connected

The future starts now, are you ready for it?  
Combine Philips Interact Ready lamps and luminaires with Interact Pro software, to create smart lighting systems for your customers.


Philips Interact Ready lighting works with the Interact Pro dashboard and app.



**Want to become a Philips Connected Lighting expert?**

Scan the QR code to sign up for free training:

## Get connected in 5 simple steps



The Interact Pro dashboard and app work with a range of Philips luminaires and lamps and a set of wireless switches and sensors that are Interact Ready.

You can customise the software's settings for specific workspaces. Whether you're connecting 20 light points or 200, Interact Pro helps everyone to work smarter.

# Overview of most popular **Interact Ready** lamps and luminaires

**Philips Interact Ready lighting**  
  
CoreLine Waterproof Interact Ready  
  
MasterConnect LEDtube T8 Ultra Output  
  
CoreLine Panel Interact Ready  
  
CoreLine Downlight Interact Ready

**Interact Pro software**  
  
Interact Pro gateway  
  
Interact Pro app  
  
Interact Pro dashboard

works with

# Overview Interact Ready CoreLine products

Now that more and more products are being connected to the internet, they are becoming smarter. This provides more flexibility, saves extra costs and offers more comfort. This means that there is an opportunity to offer a better experience for the end user. So far, small and medium sized businesses have remained excluded from these developments, but that is now a thing of the past. The luminaires and lamps from the list below are the first Interact Ready LED products and work seamlessly with the intuitive Interact Pro app and dashboard.

## Interact Pro – Gateway



interact Pro

Interact Pro gateway is the heart of the connected lighting system. It connects the system to the cloud via the internet and enables the Interact Ready luminaires, lamps and accessories to communicate sending information to the cloud and the system to be accessed via the Interact Pro apps and dashboard.



1 PACK

| Product Type                   | 12 NC        | EOC code |
|--------------------------------|--------------|----------|
| LCN1840/05 Wireless Gateway EU | 913701037703 | 77579000 |

## CoreLine waterproof



### Features

- Energy efficient and long lifetime: up to 140lm/W and 50,000 hours at L75 lifetime
- Many options available: L1200/1500, up to 6000lm, 4000K
- Smart product architecture with electrical and mechanical design supporting ease and flexibility of installation (longer sliders, faster lock opening, toolless electrical connections)

### Benefits

- Energy savings and longer lifetime to reduce operating costs
- Robust design enabling smarter, simpler and faster installation
- Uniform, wide-beam light distribution, which supports easy and attractive lighting design
- Interact Ready for easy smart lighting controls with no extra cabling

interact ready.



50000h at L75



1 PACK

| Product Type                    | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish | Driver/ power unit/ transformer | IK Rating | IP rating | Input voltage | Input frequency | 12 NC        | EOC code |
|---------------------------------|-----|--------------|------------|-------------|--------|---------------------------------|-----------|-----------|---------------|-----------------|--------------|----------|
|                                 | W   | lm           |            | K           |        |                                 |           |           |               |                 |              |          |
| WT120C LED40S/840 IA1 L1200     | 37  | 4100         | 112        | 4000        | Grey   | PSR                             | IK08      | IP65      | 220 to 240 V  | 50 to 60 Hz     | 910500465266 | 39713500 |
| WT120C LED40S/840 IA1 L1200 EL3 | 40  | 4100         | 104        | 4000        | Grey   | PSR                             | IK08      | IP65      | 220 to 240 V  | 50 to 60 Hz     | 910500465326 | 39980100 |
| WT120C LED60S/840 IA1 L1500     | 50  | 6000         | 121        | 4000        | Grey   | PSR                             | IK08      | IP65      | 220 to 240 V  | 50 to 60 Hz     | 910500465267 | 39714200 |
| WT120C LED60S/840 IA1 L1500 EL3 | 52  | 6000         | 115        | 4000        | Grey   | PSR                             | IK08      | IP65      | 220 to 240 V  | 50 to 60 Hz     | 910500465327 | 39981800 |

## CoreLine recessed luminaire

[lighting.philips.co.uk/products/interact-ready](https://lighting.philips.co.uk/products/interact-ready)



### Features

- Lifetime: 50,000 hours at L70
- Slim design with a height of less than 41 mm
- Surface-mounted version also available (also suitable for suspension)
- Office compliant (OC) and non-office compliant (NOC) version available
- DALI and emergency lighting options available
- Suitable for plaster ceiling installation

### Benefits

- Easy connection (with loop-in)
- Flicker-free thanks to high performance driver
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard

interact ready.



50000h at L75



1 PACK

| Product Type                           | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish | Driver/ power unit/ transformer | IK Rating | IP rating | Input voltage | Input frequency | 12 NC        | EOC code |
|----------------------------------------|-----|--------------|------------|-------------|--------|---------------------------------|-----------|-----------|---------------|-----------------|--------------|----------|
|                                        | W   | lm           |            | K           |        |                                 |           |           |               |                 |              |          |
| RC134B LED37S/830 W60L60 IA1 NOC       | 35  | 3700         | 105        | 3000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865171 | 99650800 |
| RC134B LED37S/830 W30L120 IA1 NOC      |     | 3700         | 105        | 3000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865178 | 99657700 |
| RC134B LED37S/830 W60L60 IA1 OC        |     | 3700         | 105        | 3000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865172 | 99651500 |
| RC134B LED37S/830 W30L120 IA1 OC       |     | 3700         | 105        | 3000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865177 | 99656000 |
| RC134B LED37S/840 W60L60 IA1 NOC       |     | 3700         | 105        | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865170 | 99649200 |
| RC134B LED37S/840 W30L120 IA1 OC       |     | 3700         | 105        | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865175 | 99654600 |
| RC134B LED37S/840 W60L60 IA1 OC        |     | 3700         | 105        | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865169 | 99648500 |
| RC134B LED37S/840 W30L120 IA1 NOC      |     | 3700         | 105        | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865174 | 99653900 |
| RC134B LED37S/840 W30L120 ELB3 IA1 NOC |     | 3700         | 94         | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865182 | 99661400 |
| RC134B LED37S/840 W30L120 ELB3 IA1 OC  |     | 3700         | 94         | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865181 | 99660700 |
| RC134B LED37S/840 W60L60 ELB3 IA1 NOC  | 39  | 3700         | 94         | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865179 | 99658400 |
| RC134B LED37S/840 W60L60 ELB3 IA1 OC   |     | 3700         | 94         | 4000        | White  | PSR-E                           | IK02      | IP20/44   | 220-240 V     | 50 to 60 Hz     | 910925865180 | 99659100 |

# Overview Interact Ready CoreLine products

## CoreLine panel



### Features

- Integrated LED technology
- Slim housing made from aluminium
- Choice of two colour temperatures: 3000 and 4000 K
- Non-Office Compliant (NOC) version and Office Compliant version (OC) available
- Suspension and plaster-ceiling installations are possible with accessories
- Optional emergency lighting

### Benefits

- Enables a simple switch from basic conventional luminaires to LED luminaires
- Energy savings of up to 50% compared to functional TL-D luminaires
- Uniform surface of light
- Easy connection (with loop-in)
- Interact Ready for easy smart lighting controls with no extra cabling

interact  
ready.



50000h  
at L75



1 PACK

| Product Type                           | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish | Driver/<br>power unit/<br>transformer | IK Rating | IP rating | Input voltage | Input<br>frequency | 12 NC        | EOC code |
|----------------------------------------|-----|--------------|------------|-------------|--------|---------------------------------------|-----------|-----------|---------------|--------------------|--------------|----------|
|                                        | W   | lm           |            | K           |        |                                       |           |           |               |                    |              |          |
| RC132V LED34S/830 W60L60 IA1 NOC       | 34  | 3400         | 100        | 3000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483124 | 38517000 |
| RC132V LED36S/840 W30L120 IA1 OC       |     | 3600         | 106        | 4000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483130 | 38523100 |
| RC132V LED34S/830 W60L60 IA1 OC        |     | 3400         | 100        | 3000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483128 | 38521700 |
| RC132V LED36S/840 W30L120 IA1 NOC      |     | 3600         | 106        | 4000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483126 | 38519400 |
| RC132V LED36S/840 W60L60 IA1 OC        |     | 3600         | 106        | 4000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483127 | 38520000 |
| RC132V LED36S/840 W60L60 IA1 NOC       |     | 3600         | 106        | 4000        | White  | PSR                                   | IK03      | IP20/44   | 220-240 V     | 50 to 60 Hz        | 912401483123 | 38516300 |
| RC132V LED36S/840 W30L120 ELB3 IA1 OC  | 36  | 3600         | 100        | 4000        | White  | PSU                                   | IK02      | IP20/44   | 220 to 240 V  | 50 to 60 Hz        | 910500465363 | 40136800 |
| RC132V LED36S/840 W30L120 ELB3 IA1 NOC |     | 3600         | 100        | 4000        | White  | PSU                                   | IK02      | IP20/44   | 220 to 240 V  | 50 to 60 Hz        | 910500465361 | 40134400 |
| RC132V LED36S/840 W60L60 ELB3 IA1 NOC  |     | 3600         | 100        | 4000        | White  | PSU                                   | IK02      | IP20/44   | 220 to 240 V  | 50 to 60 Hz        | 910500465360 | 40133700 |
| RC132V LED36S/840 W60L60 ELB3 IA1 OC   | 40  | 3600         | 90         | 4000        | White  | PSU                                   | IK02      | IP20/44   | 220 to 240 V  | 50 to 60 Hz        | 910500465362 | 40135100 |

## CoreLine surface-mounted luminaire



1



2

### Features

- Integrated LED technology
- Slim housing
- Suspension set available as an accessory
- Recessed version also available for use in grid ceilings

### Benefits

- Enables a simple switch from basic conventional luminaires to LED luminaires
- Energy saving of up to 45% compared to functional TL-D luminaires
- Slim design with a height of less than 40 mm
- Interact Ready for easy smart lighting controls with no extra cabling

interact  
ready.



50000h  
at L75



1 PACK

| Product Type                             | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish | Driver/<br>power unit/<br>transformer | IK Rating | IP rating | Input voltage | Input<br>frequency | 12 NC        | EOC code |
|------------------------------------------|-----|--------------|------------|-------------|--------|---------------------------------------|-----------|-----------|---------------|--------------------|--------------|----------|
|                                          | W   | lm           |            | K           |        |                                       |           |           |               |                    |              |          |
| 2 SM134V LED37S/840 W20L120 IA1 NOC      | 35  | 3700         | 105        | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865183 | 99662100 |
| 1 SM134V LED37S/840 W60L60 IA1 NOC       |     | 3700         | 105        | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865186 | 99665200 |
| 1 SM134V LED37S/840 W60L60 IA1 OC        |     | 3700         | 105        | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865188 | 99667600 |
| 2 SM134V LED37S/830 W20L120 IA1 NOC      |     | 3700         | 105        | 3000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865185 | 99664500 |
| 2 SM134V LED37S/830 W20L120 IA1 OC       |     | 3700         | 105        | 3000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865187 | 99666900 |
| 2 SM134V LED37S/840 W20L120 IA1 OC       |     | 3700         | 105        | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865184 | 99663800 |
| 2 SM134V LED37S/840 W20L120 ELB3 IA1 NOC | 39  | 3700         | 94         | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865192 | 99671300 |
| 1 SM134V LED37S/840 W60L60 ELB3 IA1 NOC  |     | 3700         | 94         | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865193 | 99672000 |
| 1 SM134V LED37S/840 W60L60 ELB3 IA1 OC   |     | 3700         | 94         | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865194 | 99673700 |
| 2 SM134V LED37S/840 W20L120 ELB3 IA1 OC  |     | 3700         | 94         | 4000        | White  | PSR-E                                 | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 910925865191 | 99670600 |

# Overview Interact Ready CoreLine products

## CoreLine downlight



### Features

- Available in 1100 and 2200 lumen versions
- Energy-efficient: up to 115 lm/W
- DALI and emergency lighting versions available
- Choice of colour temperature: 3000 and 4000 K
- Protected glass available as an option (enables IP54 protection)

### Benefits

- Reduced operating costs thanks to energy saving and longer lifetime
- One-to-one replacement, facilitating the switch from conventional to LED luminaires
- Suitable for professional applications thanks to DALI dimming and aluminium reflector
- Interact Ready for easy smart lighting controls with no extra cabling

interact  
ready.



50000h  
at L70



1 PACK

| Product Type                  | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish         | Driver/<br>power unit/<br>transformer | IK Rating | IP rating | Input voltage | Input<br>frequency | 12 NC        | EOC code |
|-------------------------------|-----|--------------|------------|-------------|----------------|---------------------------------------|-----------|-----------|---------------|--------------------|--------------|----------|
|                               | W   | lm           |            | K           |                |                                       |           |           |               |                    |              |          |
| DN140B LED20S/840 WR IA1      | 22  | 2200         | 100        | 4000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401634305 | 32613900 |
| DN140B LED20S/840 C IA1       |     | 2200         | 100        | 4000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401634505 | 32615300 |
| DN140B LED20S/830 WR IA1      |     | 2200         | 100        | 3000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401634205 | 32612200 |
| DN140B LED20S/830 C IA1       |     | 2200         | 100        | 3000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401634405 | 32614600 |
| DN140B LED20S/840 C ELB3 IA1  | 25  | 2200         | 88         | 4000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401640505 | 32842300 |
| DN140B LED20S/830 WR ELB3 IA1 |     | 2200         | 88         | 3000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401640205 | 32839300 |
| DN140B LED20S/840 WR ELB3 IA1 |     | 2200         | 88         | 4000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401640305 | 32840900 |
| DN140B LED20S/830 C ELB3 IA1  |     | 2200         | 88         | 3000        | White RAL 9003 | PSU                                   | IK02      | IP20      | 220-240 V     | 50 to 60 Hz        | 911401640405 | 32841600 |

## CoreLine slim downlight



### Features

- Energy-efficient and a long lifespan: up to 100lm/W and 50,000 hours at L70 lifetime
- Push-in connector with through-wiring option
- Multiple options available: 650/1100/2100lm; 3000K/4000K; Dali
- Total height (including driver): 34mm recessed; 50mm surface mounted

### Benefits

- Energy saving and longer lifetime to reduce overall operating costs
- Product height less than 50mm, fitting more ceiling types
- The natural 'surface of light' effect creates a comfortable, high-end look
- Interact Ready for easy smart lighting controls with no extra cabling

interact  
ready.



50000h  
at L70



1 PACK

| Product Type             | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish        | Driver/<br>power unit/<br>transformer | IK Rating | IP rating | Input voltage | Input<br>frequency | 12 NC        | EOC code  |
|--------------------------|-----|--------------|------------|-------------|---------------|---------------------------------------|-----------|-----------|---------------|--------------------|--------------|-----------|
|                          | W   | lm           |            | K           |               |                                       |           |           |               |                    |              |           |
| DN145B LED20S/830 IA1 WH | 27  | 2000         | 74         | 3000        | White RAL9010 | PSU                                   | IK02      | IP44      | 220 to 240 V  | 50 to 60 Hz        | 910500465898 | 996098899 |
| DN145B LED20S/840 IA1 WH |     | 2000         | 74         | 4000        | White RAL9010 | PSU                                   | IK02      | IP44      | 220 to 240 V  | 50 to 60 Hz        | 912401483216 | 938924699 |

# Interact Ready products

## CoreLine batten



### Features

- Lifetime: 50,000 hours at L70
- Through-wiring standard included
- DALI and emergency lighting options available

### Benefits

- Easy to install and lengths same as TL-D
- Excellent performance and light quality thanks to frosted diffuser
- Interact Ready for easy smart lighting controls with no extra cabling

interact  
ready.



50000h  
at L70



1 PACK

| Product Type                    | LED | Lumen Output | Lumen/Watt | Colour Temp | Finish | Driver/<br>power unit/<br>transformer | IK Rating | IP rating | Input voltage | Input<br>frequency | 12 NC        | EOC code |
|---------------------------------|-----|--------------|------------|-------------|--------|---------------------------------------|-----------|-----------|---------------|--------------------|--------------|----------|
|                                 | W   | lm           |            | K           |        |                                       |           |           |               |                    |              |          |
| BN124C LED41S/840 IA1 TW1 L1200 | 36  | 4100         | 114        | 4000        | White  | PSR                                   | IK02      | IP20      | 220 to 240 V  | 50 to 60 Hz        | 911401800280 | 33733399 |
| BN124C LED53S/840 IA1 TW1 L1500 | 44  | 5300         | 120        | 4000        | White  | PSR                                   | IK02      | IP20      | 220 to 240 V  | 50 to 60 Hz        | 911401800380 | 33734099 |

## Input Devices



interact  
ready.



1 PACK

| Product Type                                                                    | 12 NC        |
|---------------------------------------------------------------------------------|--------------|
| 1 UID8450/10 ZGP Switch Dim 2B                                                  | 913700364303 |
| 2 Wireless IP42 sensor Interact Ready (presence detection)                      | 929001819002 |
| 3 Wireless IP42 multi sensor Interact Ready (presence + daylight detection)     | 929001819102 |
| 2 Wireless IP65 Sensor Interact Ready (presence detection)                      | 913701043903 |
| 3 Wireless IP65 Sensor Interact Ready (presence detection + daylight detection) | 913701044003 |

# Philips CoreLine

The reference for innovative good quality,  
easy-to-use lighting solutions for every  
project where light really matters

Find the **right** solution  
in our range using the **Selector tool**  
[productfinder.lighting.philips.com](https://productfinder.lighting.philips.com)

## CoreLine

Philips CoreLine offers a full range of LED lighting solutions that keeps installation time to a minimum, while saving maximum energy. Whether old or new, optimal lighting can transform a building into something truly special and turn it into a place where people enjoy working and living. Give your customers that “wow” moment with Philips CoreLine: the complete range of high quality LED lighting that's setting the standard in the market. Because when light really matters, you don't want to take a chance.

### CoreLine panel

[lighting.philips.co.uk/products/coreline](https://lighting.philips.co.uk/products/coreline)



#### Features

- Lifetime: 50,000 hours at L80
- Energy efficiency: up to 125lm/W
- Slim and robust housing made from aluminium
- Choice of two colour temperatures: 3000 and 4000K
- Office compliant (OC) and non-office compliant (NOC) version available

- Recessed, surface-mounted and suspended applications possible thanks to a wide range of accessories
- Optional high-quality DALI driver
- New Tp(a)-rated versions available

#### Benefits

- New option: Warm and cool white light, as well as four lumen packages in one luminaire
- New connector for simpler and faster installation
- Higher efficacy and lifetime
- Emergency (ELB3) options available
- Improved optics for the OC version



50000h  
at L80



1 PACK

|     | Product Type                                | LED   | Lumen Output | Colour Temp | Efficacy | Finish  | IP rating | IK rating    | 12NC         | EOC code |
|-----|---------------------------------------------|-------|--------------|-------------|----------|---------|-----------|--------------|--------------|----------|
|     |                                             | W     | lm           | K           | (lm/W)   |         |           |              |              |          |
| NEW | RC132V G4 LED34S/830 PSD W30L120 OC         | 29    | 3400         | 3000        | 110      | White   | IP20/44   | IK02         | 911401879680 | 36052200 |
| NEW | RC132V G4 LED34S/830 PSD W60L60 OC          |       | 3400         | 3000        | 110      | White   | IP20/44   | IK02         | 911401879080 | 36046100 |
| NEW | RC132V G4 LED34S/830 PSD W60L60 OC ELB3     |       | 3400         | 3000        | 110      | White   | IP20/44   | IK03         | 910505100546 | 96724600 |
| NEW | RC132V G4 LED34S/830 PSU W60L60 NOC         |       | 3400         | 3000        | 115      | White   | IP20/44   | IK02         | 911401878080 | 36036200 |
| NEW | RC132V G4 LED34S/830 PSU W60L60 OC          |       | 3400         | 3000        | 115      | White   | IP20/44   | IK02         | 911401878680 | 36042300 |
| NEW | RC132V G4 LED36/840 PSU W60L60 OC TP(a)     |       | 3600         | 4000        | 122      | White   | IP20/44   | IK03         | 911401879780 | 36053900 |
| NEW | RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3 |       | 3600         | 4000        | 122      | White   | IP20/44   | IK03         | 910505100544 | 96722200 |
| NEW | RC132V G4 LED36S/840 PSD W30L120 OC         |       | 3600         | 4000        | 116      | White   | IP20/44   | IK02         | 911401879580 | 36051500 |
| NEW | RC132V G4 LED36S/840 PSD W30L120 OC ELB3    |       | 3600         | 4000        | 116      | White   | IP20/44   | IK03         | 910505100537 | 96715400 |
| NEW | RC132V G4 LED36S/840 PSD W60L60 OC          |       | 3600         | 4000        | 116      | White   | IP20/44   | IK02         | 911401878980 | 36045400 |
| NEW | RC132V G4 LED36S/840 PSD W60L60 OC ELB3     |       | 3600         | 4000        | 116      | White   | IP20/44   | IK03         | 910505100532 | 96710900 |
| NEW | RC132V G4 LED36S/840 PSU W30L120 NOC        |       | 3600         | 4000        | 122      | White   | IP20/44   | IK02         | 911401878480 | 36040900 |
| NEW | RC132V G4 LED36S/840 PSU W30L120 NOC ELB3   |       | 3600         | 4000        | 122      | White   | IP20/44   | IK03         | 910505100547 | 96725300 |
| NEW | RC132V G4 LED36S/840 PSU W30L120 OC         |       | 3600         | 4000        | 122      | White   | IP20/44   | IK02         | 911401878880 | 36044700 |
| NEW | RC132V G4 LED36S/840 PSU W30L120 OC ELB3    |       | 3600         | 4000        | 122      | White   | IP20/44   | IK03         | 910505100536 | 96714700 |
| NEW | RC132V G4 LED36S/840 PSU W60L60 NOC         |       | 3600         | 4000        | 122      | White   | IP20/44   | IK02         | 911401877980 | 36035500 |
| NEW | RC132V G4 LED36S/840 PSU W60L60 NOC ELB3    |       | 3600         | 4000        | 122      | White   | IP20/44   | IK03         | 910505100545 | 96723900 |
| NEW | RC132V G4 LED36S/840 PSU W60L60 OC          | 3600  | 4000         | 122         | White    | IP20/44 | IK02      | 911401878580 | 36041600     |          |
| NEW | RC132V G4 LED36S/840 PSU W60L60 OC ELB3     | 3600  | 4000         | 122         | White    | IP20/44 | IK03      | 910505100533 | 96711600     |          |
| NEW | RC132V G4 LED43S/840 PSD W60L60 NOC ELB3    | 34.5  | 3400         | 4000        | 125      | White   | IP20/44   | IK03         | 910505100550 | 96728400 |
| NEW | RC132V G4 LED43S/840 PSD W60L60 OC          |       | 3400         | 4000        | 125      | White   | IP20/44   | IK02         | 911401879180 | 36047800 |
| NEW | RC132V G4 LED43S/840 PSD W60L60 OC ELB3     |       | 3400         | 4000        | 125      | White   | IP20/44   | IK03         | 910505100541 | 96719200 |
| NEW | RC132V G4 LED43S/840 PSU W60L60 NOC         | 30/35 | 3400         | 4000        | 125      | White   | IP20/44   | IK02         | 911401878180 | 36037900 |
| NEW | RC132V G4 LED34_43S/830_840 PSU W60L60 OC   |       | 3400/4300    | 3000/4000   | 115/123  | White   | IP20/44   | IK02         | 911401879880 | 36054600 |
| NEW | RC132V G4LED34_43S/830_840 PSUW30L120 OC    |       | 3400/4300    | 3000/4000   | 115/123  | White   | IP20/44   | IK02         | 911401880080 | 36056000 |

### CoreLine Tempo X-large



- Plug and play installation with 1m cable and IP66 connector
- Lumen packages from 30,000lm to 44,000lm
- Seaside resistant treatment and swimming pool protection options available

### CoreLine panel



- Metal frame for better robustness
- Easy connection (with loop-in)
- Flicker-free thanks to high-performance driver
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard

### CoreLine waterproof



- New, robust design with improved mechanical and electrical design for a faster and more flexible installation
- Wide-beam light distribution for more effective lighting
- Energy savings (up to 140lm/W) and longer lifetime (50,000 hrs L75) to reduce operating costs



5  
years  
warranty!



Innovative



Easy to install



High Quality


CoreLine

CoreLine panel – Accessories (see page 15)



| Product Type                                      | 12NC         | EOC code |
|---------------------------------------------------|--------------|----------|
|                                                   |              |          |
| NEW RC132Z SC (suspension kit)                    | 911401892080 | 36268799 |
| RC132Z W30L120 SMB (surface mount box)            | 910930031218 | 07332299 |
| RC132Z W60L60 SMB (surface mount box)             | 910930031018 | 07330899 |
| NEW RC132Z SMB-PLC (surface mount box)            | 911401892180 | 36269499 |
| NEW RC132Z WH SME-3 (ceiling rose suspension kit) | 911401892280 | 36270099 |
| NEW RC132Z WH SME-4 (ceiling rose suspension kit) | 911401892380 | 36271799 |

CoreLine recessed luminaire – Accessories (see pages 17 and 18)



Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Recessed range of LED products can be used to replace functional luminaires in general lighting applications. The process of selecting, installing and maintaining is so easy – it's a simple switch. In addition, CoreLine Recessed also provides the option of advanced connectivity and is ready to be connected to IoT based software applications such as Interact Pro.



| Product Type               | 12NC         | EOC code |
|----------------------------|--------------|----------|
|                            |              |          |
| RC134Z CFRM-PLC W30L120 WH | 910925864623 | 98724700 |
| RC134Z CFRM-PLC W60L60 WH  | 910925864621 | 98722300 |

CoreLine recessed luminaire



- Features**
- Lifetime: 50,000 hours at L70
  - Slim design with a height of less than 41 mm
  - Surface-mounted version also available (also suitable for suspension)
  - Office compliant (OC) and non-office compliant (NOC) version available
  - DALI and emergency lighting options available
  - Suitable for plaster ceiling installation

- Benefits**
- Easy connection (with loop-in)
  - Flicker-free thanks to high performance driver
  - Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



| Product Type                           | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                        | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| RC134B LED27S/840 PSD W30L120 OC       | 22   | 2700         | 4000        | 123      | White  | IP44      | IK02      | 910925864770 | 34812000 |
| RC134B LED27S/840 PSD W60L60 OC        |      | 2700         | 4000        | 123      | White  | IP44      | IK02      | 910925864768 | 34810600 |
| RC134B LED27S/830 PSD W30L120 OC       | 23   | 2700         | 3000        | 117      | White  | IP44      | IK02      | 910925864774 | 34816800 |
| RC134B LED27S/830 PSD W60L60 OC        |      | 2700         | 3000        | 117      | White  | IP44      | IK02      | 910925864772 | 34814400 |
| RC134B LED27S/840 PSD W30L120 ELB3 OC  | 25.5 | 2700         | 4000        | 106      | White  | IP44      | IK02      | 910925864795 | 34837300 |
| RC134B LED27S/840 PSD W60L60 ELB3 OC   |      | 2700         | 4000        | 106      | White  | IP44      | IK02      | 910925864780 | 34822900 |
| RC134B LED27S/840 PSD W30L120 NOC      | 26.5 | 2700         | 4000        | 102      | White  | IP44      | IK02      | 910925864784 | 34826700 |
| RC134B LED27S/840 PSD W60L60 NOC       |      | 2700         | 4000        | 102      | White  | IP44      | IK02      | 910925864783 | 34825000 |
| RC134B LED27S/840 PSU W30L120 NOC      | 27   | 2700         | 4000        | 100      | White  | IP44      | IK02      | 910925864782 | 34824300 |
| RC134B LED27S/840 PSU W60L60 NOC       |      | 2700         | 4000        | 100      | White  | IP44      | IK02      | 910925864781 | 34823600 |
| RC134B LED27S/830 PSU W30L120 NOC      | 28.5 | 2700         | 3000        | 95       | White  | IP44      | IK02      | 910925864755 | 34797000 |
| RC134B LED27S/830 PSU W60L60 NOC       |      | 2700         | 3000        | 95       | White  | IP44      | IK02      | 910925864753 | 34795600 |
| RC134B LED27S/830 PSD W30L120 NOC      |      | 2700         | 3000        | 89       | White  | IP44      | IK02      | 910925864761 | 34803800 |
| RC134B LED27S/830 PSD W60L60 NOC       |      | 2700         | 3000        | 89       | White  | IP44      | IK02      | 910925864759 | 34801400 |
| RC134B LED27S/840 PSD W30L120 ELB3 NOC | 30.5 | 2700         | 4000        | 89       | White  | IP44      | IK02      | 910925864793 | 34835900 |
| RC134B LED27S/840 PSD W60L60 ELB3 NOC  |      | 2700         | 4000        | 89       | White  | IP44      | IK02      | 910925864786 | 34828100 |
| RC134B LED27S/840 PSU W30L120 ELB3 NOC |      | 2700         | 4000        | 89       | White  | IP44      | IK02      | 910925864791 | 34833500 |
| RC134B LED27S/840 PSU W60L60 ELB3 NOC  |      | 2700         | 4000        | 89       | White  | IP44      | IK02      | 910925864785 | 34827400 |
| RC134B LED37S/840 PSU W30L120 OC       | 31.5 | 3700         | 4000        | 121      | White  | IP44      | IK02      | 910925864788 | 34830400 |
| RC134B LED37S/840 PSU W60L60 OC        |      | 3700         | 4000        | 121      | White  | IP44      | IK02      | 910925864787 | 34829800 |
| RC134B LED37S/830 PSD W30L120 OC       |      | 3700         | 3000        | 117      | White  | IP44      | IK02      | 910925864773 | 34815100 |
| RC134B LED37S/830 PSD W60L60 OC        |      | 3700         | 3000        | 117      | White  | IP44      | IK02      | 910925864771 | 34813700 |
| RC134B LED37S/840 PSD W30L120 OC       |      | 3700         | 4000        | 117      | White  | IP44      | IK02      | 910925864769 | 34811300 |
| RC134B LED37S/840 PSD W60L60 OC        |      | 3700         | 4000        | 117      | White  | IP44      | IK02      | 910925864762 | 34804500 |
| RC134B LED27S/830 PSU W30L120 ELB3 NOC | 32   | 2700         | 3000        | 84       | White  | IP44      | IK02      | 910925864797 | 34839700 |
| RC134B LED27S/830 PSD W30L120 ELB3 NOC | 34   | 2700         | 3000        | 79       | White  | IP44      | IK02      | 910925864799 | 34841000 |

CoreLine

CoreLine recessed luminaire – Continued



Features

- Lifetime: 50,000 hours at L70
- Slim design with a height of less than 41 mm
- Surface-mounted version also available (also suitable for suspension)
- Office compliant (OC) and non-office compliant (NOC) version available
- DALI and emergency lighting options available
- Suitable for plaster ceiling installation

Benefits

- Easy connection (with loop-in)
- Flicker-free thanks to high performance driver
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                           | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                        | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| RC134B LED37S/830 PSU W30L120 NOC      | 34   | 3700         | 3000        | 109      | White  | IP44      | IK02      | 910925864754 | 34796300 |
| RC134B LED37S/830 PSU W60L60 NOC       |      | 3700         | 3000        | 109      | White  | IP44      | IK02      | 910925864752 | 34794900 |
| RC134B LED37S/840 PSU W30L120 NOC      |      | 3700         | 4000        | 109      | White  | IP44      | IK02      | 910925864776 | 34818200 |
| RC134B LED37S/840 PSU W60L60 NOC       |      | 3700         | 4000        | 109      | White  | IP44      | IK02      | 910925864775 | 34817500 |
| RC134B LED37S/830 PSU W30L120 OC       | 34.5 | 3700         | 3000        | 107      | White  | IP44      | IK02      | 910925864790 | 34832800 |
| RC134B LED37S/830 PSU W60L60 OC        |      | 3700         | 3000        | 107      | White  | IP44      | IK02      | 910925864789 | 34831100 |
| RC134B LED37S/830 PSD W30L120 ELB3 OC  | 35   | 3700         | 3000        | 106      | White  | IP44      | IK02      | 910925864802 | 34843400 |
| RC134B LED37S/840 PSD W30L120 ELB3 OC  |      | 3700         | 4000        | 106      | White  | IP44      | IK02      | 910925864796 | 34838000 |
| RC134B LED37S/840 PSD W60L60 ELB3 OC   | 35.5 | 3700         | 4000        | 106      | White  | IP44      | IK02      | 910925864779 | 34821200 |
| RC134B LED37S/830 PSD W30L120 NOC      |      | 3700         | 3000        | 104      | White  | IP44      | IK02      | 910925864760 | 34802100 |
| RC134B LED37S/830 PSD W60L60 NOC       |      | 3700         | 3000        | 104      | White  | IP44      | IK02      | 910925864758 | 34800700 |
| RC134B LED37S/840 PSD W30L120 ELB3 NOC |      | 3700         | 4000        | 104      | White  | IP44      | IK02      | 910925864794 | 34836600 |
| RC134B LED37S/840 PSD W30L120 NOC      |      | 3700         | 4000        | 104      | White  | IP44      | IK02      | 910925864757 | 34799400 |
| RC134B LED37S/840 PSD W60L60 NOC       |      | 3700         | 4000        | 104      | White  | IP44      | IK02      | 910925864756 | 34798700 |
| RC134B LED37S/830 PSU W30L120 ELB3 NOC | 38   | 3700         | 3000        | 97       | White  | IP44      | IK02      | 910925864798 | 34840300 |
| RC134B LED37S/840 PSU W30L120 ELB3 NOC |      | 3700         | 4000        | 97       | White  | IP44      | IK02      | 910925864792 | 34834200 |
| RC134B LED37S/840 PSU W60L60 ELB3 NOC  | 39   | 3700         | 4000        | 97       | White  | IP44      | IK02      | 910925864777 | 34819900 |
| RC134B LED37S/830 PSD W30L120 ELB3 NOC |      | 3700         | 3000        | 95       | White  | IP44      | IK02      | 910925864801 | 34842700 |
| RC134B LED37S/840 PSD W60L60 ELB3 NOC  |      | 3700         | 4000        | 95       | White  | IP44      | IK02      | 910925864778 | 34820500 |

CoreLine surface-mounted luminaire



1



2

Features

- Lifetime: 50,000 hours at L70
- Suspension set available as an accessory
- Recessed version also available for use in grid ceilings
- DALI and emergency lighting options available
- Slim design and <47 mm height

Benefits

- Easy connection (with loop-in)
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                             | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|------------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                          | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| 2 SM134V LED27S/840 PSD W20L120 OC       | 22   | 2700         | 4000        | 123      | White  | IP20      | IK02      | 910925864823 | 34864900 |
| 1 SM134V LED27S/840 PSD W60L60 OC        |      | 2700         | 4000        | 123      | White  | IP20      | IK02      | 910925864821 | 34862500 |
| 2 SM134V LED27S/830 PSD W20L120 OC       | 23   | 2700         | 3000        | 117      | White  | IP20      | IK02      | 910925864827 | 34868700 |
| 1 SM134V LED27S/830 PSD W60L60 OC        |      | 2700         | 3000        | 117      | White  | IP20      | IK02      | 910925864825 | 34866300 |
| 2 SM134V LED27S/840 PSD W20L120 ELB3 OC  | 25.5 | 2700         | 4000        | 106      | White  | IP20      | IK02      | 910925864848 | 34889200 |
| 1 SM134V LED27S/840 PSD W60L60 ELB3 OC   |      | 2700         | 4000        | 106      | White  | IP20      | IK02      | 910925864833 | 34874800 |
| 2 SM134V LED27S/840 PSD W20L120 NOC      | 26.5 | 2700         | 4000        | 102      | White  | IP20      | IK02      | 910925864837 | 34878600 |
| 1 SM134V LED27S/840 PSD W60L60 NOC       |      | 2700         | 4000        | 102      | White  | IP20      | IK02      | 910925864836 | 34877900 |
| 2 SM134V LED27S/840 PSU W20L120 NOC      | 27   | 2700         | 4000        | 100      | White  | IP20      | IK02      | 910925864835 | 34876200 |
| 1 SM134V LED27S/840 PSU W60L60 NOC       |      | 2700         | 4000        | 100      | White  | IP20      | IK02      | 910925864834 | 34875500 |
| 2 SM134V LED27S/830 PSU W20L120 NOC      | 28.5 | 2700         | 3000        | 95       | White  | IP20      | IK02      | 910925864813 | 34854000 |
| 1 SM134V LED27S/830 PSU W60L60 NOC       |      | 2700         | 3000        | 95       | White  | IP20      | IK02      | 910925864811 | 34852600 |
| 2 SM134V LED27S/830 PSD W20L120 NOC      | 30.5 | 2700         | 3000        | 89       | White  | IP20      | IK02      | 910925864819 | 34860100 |
| 1 SM134V LED27S/830 PSD W60L60 NOC       |      | 2700         | 3000        | 89       | White  | IP20      | IK02      | 910925864817 | 34858800 |
| 2 SM134V LED27S/840 PSD W20L120 ELB3 NOC |      | 2700         | 4000        | 89       | White  | IP20      | IK02      | 910925864846 | 34887800 |
| 1 SM134V LED27S/840 PSD W60L60 ELB3 NOC  |      | 2700         | 4000        | 89       | White  | IP20      | IK02      | 910925864839 | 34880900 |
| 2 SM134V LED27S/840 PSU W20L120 ELB3 NOC |      | 2700         | 4000        | 89       | White  | IP20      | IK02      | 910925864844 | 34885400 |
| 1 SM134V LED27S/840 PSU W60L60 ELB3 NOC  |      | 2700         | 4000        | 89       | White  | IP20      | IK02      | 910925864838 | 34879300 |
| 2 SM134V LED37S/840 PSU W20L120 OC       |      | 3700         | 4000        | 121      | White  | IP20      | IK02      | 910925864841 | 34882300 |
| 1 SM134V LED37S/840 PSU W60L60 OC        |      | 3700         | 4000        | 121      | White  | IP20      | IK02      | 910925864840 | 34881600 |
| 2 SM134V LED37S/830 PSD W20L120 OC       | 31.5 | 3700         | 3000        | 117      | White  | IP20      | IK02      | 910925864826 | 34867000 |
| 1 SM134V LED37S/830 PSD W60L60 OC        |      | 3700         | 3000        | 117      | White  | IP20      | IK02      | 910925864824 | 34865600 |
| 2 SM134V LED37S/840 PSD W20L120 OC       |      | 3700         | 4000        | 117      | White  | IP20      | IK02      | 910925864822 | 34863200 |
| 1 SM134V LED37S/840 PSD W60L60 OC        |      | 3700         | 4000        | 117      | White  | IP20      | IK02      | 910925864820 | 34861800 |
| 2 SM134V LED27S/830 PSU W20L120 ELB3 NOC | 32   | 2700         | 3000        | 84       | White  | IP20      | IK02      | 910925864850 | 34891500 |
| 2 SM134V LED27S/830 PSD W20L120 ELB3 NOC | 34   | 2700         | 3000        | 79       | White  | IP20      | IK02      | 910925864852 | 34893900 |

CoreLine surface-mounted luminaire – Continued



1



2

Features

- Lifetime: 50,000 hours at L70
- Suspension set available as an accessory
- Recessed version also available for use in grid ceilings
- DALI and emergency lighting options available
- Slim design and <47 mm height

Benefits

- Easy connection (with loop-in)
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                           | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                        | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| SM134V LED37S/830 PSU W20L120 NOC      | 34   | 3700         | 3000        | 109      | White  | IP20      | IK02      | 910925864812 | 34853300 |
| SM134V LED37S/830 PSU W60L60 NOC       |      | 3700         | 3000        | 109      | White  | IP20      | IK02      | 910925864810 | 34851900 |
| SM134V LED37S/840 PSU W20L120 NOC      |      | 3700         | 4000        | 109      | White  | IP20      | IK02      | 910925864829 | 34870000 |
| SM134V LED37S/840 PSU W60L60 NOC       |      | 3700         | 4000        | 109      | White  | IP20      | IK02      | 910925864828 | 34869400 |
| SM134V LED37S/830 PSU W20L120 OC       | 34.5 | 3700         | 3000        | 107      | White  | IP20      | IK02      | 910925864843 | 34884700 |
| SM134V LED37S/830 PSU W60L60 OC        |      | 3700         | 3000        | 107      | White  | IP20      | IK02      | 910925864842 | 34883000 |
| SM134V LED37S/840 PSD W20L120 ELB3 OC  | 35   | 3700         | 4000        | 106      | White  | IP20      | IK02      | 910925864849 | 34890800 |
| SM134V LED37S/840 PSD W60L60 ELB3 OC   |      | 3700         | 4000        | 106      | White  | IP20      | IK02      | 910925864832 | 34873100 |
| SM134V LED37S/830 PSD W20L120 NOC      | 35.5 | 3700         | 3000        | 104      | White  | IP20      | IK02      | 910925864818 | 34859500 |
| SM134V LED37S/830 PSD W60L60 NOC       |      | 3700         | 3000        | 104      | White  | IP20      | IK02      | 910925864816 | 34857100 |
| SM134V LED37S/840 PSD W20L120 ELB3 NOC |      | 3700         | 4000        | 104      | White  | IP20      | IK02      | 910925864847 | 34888500 |
| SM134V LED37S/840 PSD W20L120 NOC      |      | 3700         | 4000        | 104      | White  | IP20      | IK02      | 910925864815 | 34856400 |
| SM134V LED37S/840 PSD W60L60 NOC       | 38   | 3700         | 4000        | 104      | White  | IP20      | IK02      | 910925864814 | 34855700 |
| SM134V LED37S/830 PSU W20L120 ELB3 NOC |      | 3700         | 3000        | 97       | White  | IP20      | IK02      | 910925864851 | 34892200 |
| SM134V LED37S/840 PSU W20L120 ELB3 NOC |      | 3700         | 4000        | 97       | White  | IP20      | IK02      | 910925864845 | 34886100 |
| SM134V LED37S/840 PSU W60L60 ELB3 NOC  |      | 3700         | 4000        | 97       | White  | IP20      | IK02      | 910925864830 | 34871700 |
| SM134V LED37S/830 PSD W20L120 ELB3 NOC | 39   | 3700         | 3000        | 95       | White  | IP20      | IK02      | 910925864853 | 34894600 |
| SM134V LED37S/840 PSD W60L60 ELB3 NOC  |      | 3700         | 4000        | 95       | White  | IP20      | IK02      | 910925864831 | 34872400 |

CoreLine surface-mounted luminaire – Accessories



1 PACK

| Product Type                               | 12NC         | EOC code |
|--------------------------------------------|--------------|----------|
| SM134Z SME-3 (ceiling rose suspension kit) | 910925864856 | 34897700 |
| SM134Z SME-5 (ceiling rose suspension kit) | 910925864854 | 34895300 |
| SM134Z SMS (suspension kit)                | 910925864855 | 34896000 |

CoreLine wall-mounted luminaire



Features

- Lifetime: 50,000 hours at L70
- Three lumen packages to cater for diverse applications
- Water- and vandal-proof as standard
- DALI and emergency lighting options available

- Advanced motion detection with dimming mode and grouping function
- Looping wire holes and push-in 6 connector

Benefits

- Easy installation with push-in connectors and looping-wire option
- Slim and unobtrusive design
- Homogeneous light effect to cater for visual comfort



50000h  
at L70



1 PACK

| Product Type                     | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                  | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| WL130V LED12S/830 PSU WH         | 12  | 1200         | 3000        | 100      | White  | IP65      | IK08      | 912401483182 | 38778599 |
| WL130V LED12S/840 PSU WH         |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 912401483183 | 38779299 |
| WL131V LED12S/830 PSED EL3 WH    |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 910500465390 | 40268600 |
| WL131V LED12S/830 PSR EL3 MDU WH |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 910500465405 | 40282200 |
| WL131V LED12S/830 PSU WH         |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 911401807080 | 34000599 |
| WL131V LED12S/840 PSED EL3 WH    |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 910500465391 | 40269300 |
| WL131V LED12S/840 PSR EL3 MDU WH |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 910500465406 | 40283900 |
| WL131V LED12S/840 PSU WH         |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 911401807180 | 34001299 |
| WL131V LED12S/830 PSED WH        | 13  | 1200         | 3000        | 90       | White  | IP65      | IK08      | 912401483196 | 38792199 |
| WL131V LED12S/840 PSED WH        |     | 1200         | 4000        | 90       | White  | IP65      | IK08      | 912401483197 | 38793899 |
| WL131V LED12S/830 PSR MDU WH     | 15  | 1200         | 3000        | 80       | White  | IP65      | IK08      | 912401483190 | 38786099 |
| WL131V LED12S/830 PSU EL3 WH     |     | 1200         | 3000        | 80       | White  | IP65      | IK08      | 910500465894 | 96094000 |
| WL131V LED12S/840 PSR MDU WH     |     | 1200         | 4000        | 80       | White  | IP65      | IK08      | 912401483191 | 38787799 |
| WL131V LED12S/840 PSU EL3 WH     |     | 1200         | 4000        | 80       | White  | IP65      | IK08      | 910500465895 | 96095700 |

CoreLine

CoreLine wall-mounted luminaire



Features

- Lifetime: 50,000 hours at L70
- Three lumen packages to cater for diverse applications
- Water- and vandal-resistant as standard
- DALI and emergency lighting options available

- Advanced motion detection with dimming mode and grouping function
- Looping wire holes and push-in 6 connector

Benefits

- Easy installation with push-in connectors and looping-wire option
- Slim and unobtrusive design
- Homogeneous light effect to cater for visual comfort



50000h  
at L70



1 PACK

| Product Type                     | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                  | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| WL130V LED12S/830 PSU WH         | 12  | 1200         | 3000        | 100      | White  | IP65      | IK08      | 912401483182 | 38778599 |
| WL130V LED12S/840 PSU WH         |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 912401483183 | 38779299 |
| WL131V LED12S/830 PSED EL3 WH    |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 910500465390 | 40268600 |
| WL131V LED12S/830 PSR EL3 MDU WH |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 910500465405 | 40282200 |
| WL131V LED12S/830 PSU WH         |     | 1200         | 3000        | 100      | White  | IP65      | IK08      | 911401807080 | 34000599 |
| WL131V LED12S/840 PSED EL3 WH    |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 910500465391 | 40269300 |
| WL131V LED12S/840 PSR EL3 MDU WH |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 910500465406 | 40283900 |
| WL131V LED12S/840 PSU WH         |     | 1200         | 4000        | 100      | White  | IP65      | IK08      | 911401807180 | 34001299 |
| WL131V LED12S/830 PSED WH        |     | 1200         | 3000        | 90       | White  | IP65      | IK08      | 912401483196 | 38792199 |
| WL131V LED12S/840 PSED WH        |     | 1200         | 4000        | 90       | White  | IP65      | IK08      | 912401483197 | 38793899 |
| WL131V LED12S/830 PSR MDU WH     |     | 1200         | 3000        | 80       | White  | IP65      | IK08      | 912401483190 | 38786099 |
| WL131V LED12S/830 PSU EL3 WH     |     | 1200         | 3000        | 80       | White  | IP65      | IK08      | 910500465894 | 96094000 |
| WL131V LED12S/840 PSR MDU WH     | 15  | 1200         | 4000        | 80       | White  | IP65      | IK08      | 912401483191 | 38787799 |
| WL131V LED12S/840 PSU EL3 WH     |     | 1200         | 4000        | 80       | White  | IP65      | IK08      | 910500465895 | 96095700 |
| WL130V LED20S/830 PSU WH         |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 912401483184 | 38780899 |
| WL130V LED20S/840 PSU WH         | 22  | 2000         | 4000        | 90       | White  | IP65      | IK08      | 912401483185 | 38781599 |
| WL131V LED20S/830 PSED EL3 WH    |     | 2000         | 3000        | 91       | White  | IP65      | IK08      | 910500465392 | 40270900 |
| WL131V LED20S/830 PSR EL3 MDU WH |     | 2000         | 3000        | 91       | White  | IP65      | IK08      | 910500465407 | 40284600 |
| WL131V LED20S/840 PSED EL3 WH    |     | 2000         | 4000        | 91       | White  | IP65      | IK08      | 910500465393 | 40271600 |
| WL131V LED20S/840 PSR EL3 MDU WH |     | 2000         | 4000        | 91       | White  | IP65      | IK08      | 910500465408 | 40285300 |
| WL131V LED20S/840 PSR EL3 MDU WH |     | 2000         | 4000        | 91       | White  | IP65      | IK08      | 910500465408 | 40285300 |

CoreLine wall-mounted luminaire – Continued



Features

- Lifetime: 50,000 hours at L70
- Three lumen packages to cater for diverse applications
- Water- and vandal-resistant as standard
- DALI and emergency lighting options available

- Advanced motion detection with dimming mode and grouping function
- Looping wire holes and push-in 6 connector

Benefits

- Easy installation with push-in connectors and looping-wire option
- Slim and unobtrusive design
- Homogeneous light effect to cater for visual comfort



50000h  
at L70



1 PACK

| Product Type                     | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                  | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| WL130V LED20S/830 PSU MDU WH     | 23  | 2000         | 3000        | 80       | White  | IP65      | IK08      | 912401483186 | 38782299 |
| WL130V LED20S/840 PSU MDU WH     |     | 2000         | 4000        | 80       | White  | IP65      | IK08      | 912401483187 | 38783999 |
| WL131V LED20S/830 PSED WH        |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 912401483198 | 38794599 |
| WL131V LED20S/830 PSU EL3 WH     |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 910500465896 | 96096400 |
| WL131V LED20S/830 PSU WH         |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 911401807280 | 34002999 |
| WL131V LED20S/840 PSED WH        |     | 2000         | 4000        | 90       | White  | IP65      | IK08      | 912401483199 | 38795299 |
| WL131V LED20S/840 PSU EL3 WH     |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 910500465897 | 96097100 |
| WL131V LED20S/840 PSU WH         |     | 2000         | 3000        | 90       | White  | IP65      | IK08      | 911401807380 | 34003699 |
| WL131V LED20S/830 PSR MDU WH     |     | 2000         | 3000        | 80       | White  | IP65      | IK08      | 912401483192 | 38788499 |
| WL131V LED20S/840 PSR MDU WH     |     | 2000         | 4000        | 80       | White  | IP65      | IK08      | 912401483193 | 38789199 |
| WL131V LED34S/830 PSED EL3 WH    |     | 3400         | 3000        | 94       | White  | IP65      | IK08      | 910500465396 | 40274700 |
| WL131V LED34S/830 PSED WH        |     | 3400         | 3000        | 94       | White  | IP65      | IK08      | 910500465394 | 40272300 |
| WL131V LED34S/830 PSR EL3 MDU WH | 36  | 3400         | 3000        | 94       | White  | IP65      | IK08      | 910500465409 | 40286000 |
| WL131V LED34S/830 PSU WH         |     | 3400         | 3000        | 95       | White  | IP65      | IK08      | 912401483188 | 38784699 |
| WL131V LED34S/840 PSED EL3 WH    |     | 3400         | 4000        | 94       | White  | IP65      | IK08      | 910500465397 | 40275400 |
| WL131V LED34S/840 PSED WH        |     | 3400         | 4000        | 94       | White  | IP65      | IK08      | 910500465395 | 40273000 |
| WL131V LED34S/840 PSR EL3 MDU WH |     | 3400         | 4000        | 94       | White  | IP65      | IK08      | 910500465410 | 40287700 |
| WL131V LED34S/840 PSU WH         |     | 3400         | 4000        | 95       | White  | IP65      | IK08      | 912401483189 | 38785399 |
| WL131V LED34S/830 PSR MDU WH     | 38  | 3400         | 3000        | 90       | White  | IP65      | IK08      | 912401483194 | 38790799 |
| WL131V LED34S/840 PSR MDU WH     |     | 3400         | 4000        | 90       | White  | IP65      | IK08      | 912401483195 | 38791499 |

CoreLine

CoreLine waterproof



NEW

Features

- Lifetime: 50,000 hours at L75
- Wide-beam light distribution
- Available in three lengths: 600 mm, 1200 mm and 1500 mm
- Ceiling-mounted bracket and suspension hooks included
- Vandal-resistant by additional screw fixation of mounting brackets
- High performance DALI driver
- IP65 and IK08 rated

Benefits

- Direct replacement of fluorescent lamps ranging from 18W up to 58W
- High luminaire quality: highest efficacy, widest portfolio, best lifetime
- High quality optical performance: Wide Beam, lower glare, visual comfort
- Slim and robust design architecture,
- Ease to install & retrofit: design supports flexible installation (longer sliders, faster locks opening, toolless electrical connections,)
- Innovative: Motion Detection / Interact ready



50000h  
at L75



1 PACK

|     | Product Type                            | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----|-----------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|     |                                         | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| NEW | WT120C G2 LED19S/840 PSU L600           | 15   | 1900         | 4000        | 127      | Grey   | IP65      | IK08      | 911401823480 | 84045900 |
|     | WT120C LED18S/840 PSU L600 EL3          |      | 1800         | 4000        | 120      | Grey   | IP65      | IK08      | 919913997420 | 60643300 |
| NEW | WT120C G2 LED19S/840 PSD L600           | 16   | 1900         | 4000        | 119      | Grey   | IP65      | IK08      | 910505100038 | 88306800 |
| NEW | WT120C G2 LED19S/840 PSU MDU L600       |      | 1900         | 4000        | 119      | Grey   | IP65      | IK08      | 910505100036 | 96244900 |
| NEW | WT120C G2 LED27S/840 PSU L1200          | 20.5 | 2700         | 4000        | 135      | Grey   | IP65      | IK08      | 911401823580 | 84046600 |
| NEW | WT120C G2 LED27S/840 PSD L1200          | 22   | 2700         | 4000        | 123      | Grey   | IP65      | IK08      | 910505100044 | 88307500 |
| NEW | WT120C G2 LED27S/840 PSU MDU L1200      |      | 2700         | 4000        | 123      | Grey   | IP65      | IK08      | 910505100040 | 96248700 |
| NEW | WT120C G2 LED34S/840 PSD L1500          | 25.5 | 3400         | 4000        | 133      | Grey   | IP65      | IK08      | 910505100061 | 88308200 |
| NEW | WT120C G2 LED27S/840 PSU ELB3 L1200     | 26   | 2700         | 4000        | 104      | Grey   | IP65      | IK08      | 910505100042 | 85418000 |
| NEW | WT120C G2 LED34S/840 PSU MDU L1500      | 26.5 | 3400         | 4000        | 131      | Grey   | IP65      | IK08      | 910505100059 | 96267800 |
| NEW | WT120C G2 LED27S/840 PSD ELB3 L1200     | 27   | 2700         | 4000        | 100      | Grey   | IP65      | IK08      | 910505100045 | 88311200 |
| NEW | WT120C G2 LED27S/840 PSU MDU ELB3 L1200 | 28   | 2700         | 4000        | 104      | Grey   | IP65      | IK08      | 910505100043 | 96251700 |
| NEW | WT120C G2 LED40S/840 PSU L1200          | 28.6 | 4000         | 4000        | 143      | Grey   | IP65      | IK08      | 911401823780 | 84048000 |
| NEW | WT120C G2 LED40S/840 PSD L1200          | 30   | 4000         | 4000        | 133      | Grey   | IP65      | IK08      | 910505100053 | 88309900 |
| NEW | WT120C G2 LED34S/840 PSD ELB3 L1500     | 30.5 | 3400         | 4000        | 111      | Grey   | IP65      | IK08      | 910505100064 | 88313600 |
| NEW | WT120C G2 LED34S/840 PSU ELB3 L1500     |      | 3400         | 4000        | 113      | Grey   | IP65      | IK08      | 910505100062 | 85420300 |
| NEW | WT120C G2 LED34S/840 PSU L1500          |      | 3400         | 4000        | 113      | Grey   | IP65      | IK08      | 911401823680 | 84047300 |

CoreLine waterproof – Continued



NEW

Features

- Lifetime: 50,000 hours at L75
- Wide-beam light distribution
- Available in three lengths: 600 mm, 1200 mm and 1500 mm
- Ceiling-mounted bracket and suspension hooks included
- Vandal-resistant by additional screw fixation of mounting brackets
- High performance DALI driver
- IP65 and IK08 rated

Benefits

- Direct replacement of fluorescent lamps ranging from 18W up to 58W
- High luminaire quality: highest efficacy, widest portfolio, best lifetime
- High quality optical performance: Wide Beam, lower glare, visual comfort
- Slim and robust design architecture,
- Ease to install & retrofit: design supports flexible installation (longer sliders, faster locks opening, toolless electrical connections,)
- Innovative: Motion Detection / Interact ready



50000h  
at L75



1 PACK

|     | Product Type                            | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----|-----------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|     |                                         | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| NEW | WT120C G2 LED40S/840 PSU MDU L1200      | 31   | 4000         | 4000        | 129      | Grey   | IP65      | IK08      | 910505100048 | 96256200 |
| NEW | WT120C G2 LED34S/840 PSU MDU ELB3 L1500 | 31.5 | 3400         | 4000        | 110      | Grey   | IP65      | IK08      | 910505100063 | 96271500 |
| NEW | WT120C G2 LED40S/840 PSD ELB3 L1200     | 35   | 4000         | 4000        | 114      | Grey   | IP65      | IK08      | 910505100057 | 88312900 |
| NEW | WT120C G2 LED40S/840 PSU ELB3 L1200     |      | 4000         | 4000        | 114      | Grey   | IP65      | IK08      | 910505100054 | 85419700 |
| NEW | WT120C G2 LED40S/840 PSU MDU ELB3 L1200 | 36   | 4000         | 4000        | 111      | Grey   | IP65      | IK08      | 910505100055 | 96263000 |
| NEW | WT120C G2 LED60S/840 PSU L1500          | 42.9 | 6000         | 4000        | 143      | Grey   | IP65      | IK08      | 911401823880 | 84049700 |
| NEW | WT120C G2 LED60S/840 PSD L1500          | 45   | 6000         | 4000        | 133      | Grey   | IP65      | IK08      | 910505100072 | 88310500 |
| NEW | WT120C G2 LED60S/840 PSU TW3 L1500      |      | 6000         | 4000        | 133      | Grey   | IP65      | IK08      | 910505100066 | 91688900 |
| NEW | WT120C G2 LED60S/840 PSU MDU L1500      | 46   | 6000         | 4000        | 130      | Grey   | IP65      | IK08      | 910505100067 | 96275300 |
| NEW | WT120C G2 LED60S/840 PSU ELB3 L1500     | 50   | 6000         | 4000        | 120      | Grey   | IP65      | IK08      | 910505100073 | 85421000 |
| NEW | WT120C G2 LED60S/840 PSD ELB3 L1500     | 51   | 6000         | 4000        | 118      | Grey   | IP65      | IK08      | 910505100076 | 88314300 |
| NEW | WT120C G2 LED60S/840 PSU MDU ELB3 L1500 |      | 6000         | 4000        | 118      | Grey   | IP65      | IK08      | 910505100074 | 96282100 |
| NEW | WT120C G2 LED80S/840 PSU L1500          | 57.1 | 8000         | 4000        | 140      | Grey   | IP65      | IK08      | 911401823980 | 40928900 |
| NEW | WT120C G2 LED80S/840 PSD L1500          | 61   | 8000         | 4000        | 131      | Grey   | IP65      | IK08      | 910505100079 | 40929600 |
| NEW | WT120C G2 LED80S/840 PSU TW3 L1500      |      | 8000         | 4000        | 131      | Grey   | IP65      | IK08      | 910505100077 | 40930200 |
| NEW | WT120C G2 LED80S/840 PSU MDU L1500      |      | 8000         | 4000        | 131      | Grey   | IP65      | IK08      | 910505100078 | 96286900 |
| NEW | WT120C G2 LED80S/840 PSU L1500 ELB3     | 66   | 8000         | 4000        | 121      | Grey   | IP65      | IK08      | 910505100080 | 40931900 |

CoreLine

CoreLine downlight



Features

- Lifetime: 50,000 hours at L70
- Energy-efficient: up to 115 lm/W
- Available in 1100 and 2200 lumen versions
- DALI option available
- Driver failure <5%
- Choice of colour temperature: 3000 and 4000K
- IP54, DALI and emergency lighting options available

Benefits

- Covers a wide range of professional applications thanks to DALI dimming options and different optics (white and high gloss reflector)
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                                        | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                                     | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| DN140B LED10S/830 PSU High Gloss Reflector IP54 P16 | 9.5  | 1100         | 3000        | 116      | White  | IP20/54   | IK02      | 911401633405 | 32604700 |
| DN140B LED10S/830 PSU High Gloss Reflector P16      |      | 1100         | 3000        | 116      | White  | IP20      | IK02      | 911401631805 | 32588000 |
| DN140B LED10S/830 PSU White IP54 P16                |      | 1100         | 3000        | 116      | White  | IP20/54   | IK02      | 911401632605 | 32596500 |
| DN140B LED10S/830 PSU White P16                     |      | 1100         | 3000        | 116      | White  | IP20      | IK02      | 911401631005 | 32580400 |
| DN140B LED10S/840 PSU High Gloss Reflector IP54 P16 |      | 1100         | 4000        | 116      | White  | IP20/54   | IK02      | 911401633505 | 32605400 |
| DN140B LED10S/840 PSU High Gloss Reflector P16      |      | 1100         | 4000        | 116      | White  | IP20      | IK02      | 911401631905 | 32589700 |
| DN140B LED10S/840 PSU White IP54 P16                |      | 1100         | 4000        | 116      | White  | IP20/54   | IK02      | 911401632705 | 32597200 |
| DN140B LED10S/840 PSU White P16                     |      | 1100         | 4000        | 116      | White  | IP20      | IK02      | 911401631105 | 32581100 |
| DN140B LED10S/830 PSD-E High Gloss Reflector        |      | 1100         | 3000        | 96       | White  | IP20      | IK02      | 911401632005 | 32590399 |
| DN140B LED10S/830 PSD-E High Gloss Reflector IP54   |      | 1100         | 3000        | 96       | White  | IP20/54   | IK02      | 911401633605 | 32606100 |
| DN140B LED10S/830 PSD-E White IP54                  |      | 1100         | 3000        | 96       | White  | IP20/54   | IK02      | 911401632805 | 32598900 |
| DN140B LED10S/830 PSD-E White                       |      | 1100         | 3000        | 96       | White  | IP20      | IK02      | 911401631205 | 32582899 |
| DN140B LED10S/840 PSD-E High Gloss Reflector        | 11.5 | 1100         | 4000        | 96       | White  | IP20      | IK02      | 911401632105 | 32591099 |
| DN140B LED10S/840 PSD-E High Gloss Reflector IP54   |      | 1100         | 4000        | 96       | White  | IP20/54   | IK02      | 911401633705 | 32607800 |
| DN140B LED10S/840 PSD-E White IP54                  |      | 1100         | 4000        | 96       | White  | IP20/54   | IK02      | 911401632905 | 32599600 |
| DN140B LED10S/840 PSD-E White                       |      | 1100         | 4000        | 96       | White  | IP20      | IK02      | 911401631305 | 32583599 |
| DN140B LED10S/830 PSD-E High Gloss Reflector ELB3   | 14.5 | 1100         | 3000        | 76       | White  | IP20      | IK02      | 911401639805 | 32835500 |
| DN140B LED10S/830 PSD-E White ELB3                  |      | 1100         | 3000        | 76       | White  | IP20      | IK02      | 911401639405 | 32831700 |
| DN140B LED10S/840 PSD-E High Gloss Reflector ELB3   |      | 1100         | 4000        | 76       | White  | IP20      | IK02      | 911401639905 | 32836200 |
| DN140B LED10S/840 PSD-E White ELB3                  |      | 1100         | 4000        | 76       | White  | IP20      | IK02      | 911401639505 | 32832400 |
| DN140B LED20S/830 PSU High Gloss Reflector IP54 P16 | 19   | 2200         | 3000        | 116      | White  | IP20/54   | IK02      | 911401633805 | 32608500 |
| DN140B LED20S/830 PSU High Gloss Reflector P16      |      | 2200         | 3000        | 116      | White  | IP20      | IK02      | 911401632205 | 32592700 |
| DN140B LED20S/830 PSU White IP54 P16                |      | 2200         | 3000        | 116      | White  | IP20/54   | IK02      | 911401633005 | 32600900 |
| DN140B LED20S/830 PSU White P16                     |      | 2200         | 3000        | 116      | White  | IP20      | IK02      | 911401631405 | 32584200 |
| DN140B LED20S/840 PSU High Gloss Reflector IP54 P16 |      | 2200         | 4000        | 116      | White  | IP20/54   | IK02      | 911401633905 | 32609200 |
| DN140B LED20S/840 PSU High Gloss Reflector P16      |      | 2200         | 4000        | 116      | White  | IP20      | IK02      | 911401632305 | 32593400 |

CoreLine downlight – Continued



Features

- Lifetime: 50,000 hours at L70
- Energy-efficient: up to 115 lm/W
- Available in 1100 and 2200 lumen versions
- DALI option available
- Driver failure <5%
- Choice of colour temperature: 3000 and 4000K
- IP54, DALI and emergency lighting options available

Benefits

- Covers a wide range of professional applications thanks to DALI dimming options and different optics (white and high gloss reflector)
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                                      | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|---------------------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                                   | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| DN140B LED20S/840 PSU White IP54 P16              | 19   | 2200         | 4000        | 116      | White  | IP20/54   | IK02      | 911401633105 | 32601600 |
| DN140B LED20S/840 PSU White P16                   |      | 2200         | 4000        | 116      | White  | IP20      | IK02      | 911401631505 | 32585900 |
| DN140B LED20S/830 PSD-E High Gloss Reflector      | 20.5 | 2200         | 3000        | 107      | White  | IP20      | IK02      | 911401632405 | 32594199 |
| DN140B LED20S/830 PSD-E High Gloss Reflector IP54 |      | 2200         | 3000        | 107      | White  | IP20/54   | IK02      | 911401634005 | 32610800 |
| DN140B LED20S/830 PSD-E White IP54                |      | 2200         | 3000        | 107      | White  | IP20/54   | IK02      | 911401633205 | 32602300 |
| DN140B LED20S/830 PSD-E White                     |      | 2200         | 3000        | 107      | White  | IP20      | IK02      | 911401631605 | 32586699 |
| DN140B LED20S/840 PSD-E High Gloss Reflector      |      | 2200         | 4000        | 107      | White  | IP20      | IK02      | 911401632505 | 32595899 |
| DN140B LED20S/840 PSD-E High Gloss Reflector IP54 |      | 2200         | 4000        | 107      | White  | IP20/54   | IK02      | 911401634105 | 32611500 |
| DN140B LED20S/840 PSD-E White                     |      | 2200         | 4000        | 107      | White  | IP20      | IK02      | 911401631705 | 32587399 |
| DN140B LED20S/830 PSD-E High Gloss Reflector ELB3 |      | 2200         | 3000        | 94       | White  | IP20      | IK02      | 911401640005 | 32837900 |
| DN140B LED20S/830 PSD-E White ELB3                | 23.5 | 2200         | 3000        | 94       | White  | IP20      | IK02      | 911401639605 | 32833100 |
| DN140B LED20S/840 PSD-E High Gloss Reflector ELB3 |      | 2200         | 4000        | 94       | White  | IP20      | IK02      | 911401640105 | 32838600 |
| DN140B LED20S/840 PSD-E White ELB3                |      | 2200         | 4000        | 94       | White  | IP20      | IK02      | 911401639705 | 32834800 |

CoreLine

CoreLine slim downlight



Features

- Lifetime: 50,000 hours at L70
- Available in 1000 and 2000 lumen versions
- Recessed and surface mounted version
- Choice of colour temperature: 3000 and 4000K
- Recessed and surface-mounted versions enables luminaire to be positioned anywhere

Benefits

- Fits more ceiling types thanks to product height of less than 50 mm
- The natural 'surface of light' effect creates a comfortable, high-end look
- Interact Ready version: integrated wireless antenna for use with Interact Pro app and dashboard



50000h  
at L70



1 PACK

| Product Type                    | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|---------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                 | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| 1 DN145B LED10S/830 PSU II WH   | 11   | 1100         | 3000        | 100      | White  | IP20/44   | IK02      | 911401805980 | 33947499 |
| 1 DN145B LED10S/840 PSU II WH   |      | 1100         | 4000        | 100      | White  | IP20/44   | IK02      | 911401806080 | 33948199 |
| 2 DN145C LED10S/830 PSU II WH   |      | 1100         | 3000        | 100      | White  | IP44      | IK02      | 911401806380 | 33951199 |
| 2 DN145C LED10S/840 PSU II WH   |      | 1100         | 4000        | 100      | White  | IP44      | IK02      | 911401806480 | 33952899 |
| 1 DN145B LED10S/830 PSD-E II WH | 13   | 1100         | 3000        | 85       | White  | IP20/44   | IK02      | 910500465901 | 96100899 |
| 1 DN145B LED10S/840 PSD-E II WH |      | 1100         | 4000        | 85       | White  | IP20/44   | IK02      | 910500465902 | 96101599 |
| 1 DN145B LED20S/830 PSU II WH   | 21   | 2100         | 3000        | 100      | White  | IP20/44   | IK02      | 911401806180 | 33949899 |
| 1 DN145B LED20S/840 PSU II WH   |      | 2100         | 4000        | 100      | White  | IP20/44   | IK02      | 911401806280 | 33950499 |
| 2 DN145C LED20S/830 PSU II WH   |      | 2100         | 3000        | 100      | White  | IP44      | IK02      | 911401806580 | 33953599 |
| 2 DN145C LED20S/840 PSU II WH   |      | 2100         | 4000        | 100      | White  | IP44      | IK02      | 911401806680 | 33954299 |
| 1 DN145B LED20S/830 PSD-E II WH | 22.5 | 2100         | 3000        | 93       | White  | IP20/44   | IK02      | 910500465903 | 96102299 |
| 1 DN145B LED20S/840 PSD-E II WH |      | 2100         | 4000        | 93       | White  | IP20/44   | IK02      | 910500465904 | 96103999 |

CoreLine recessed spot



Features

- Lifetime: 50,000 hours at L70
- Available in fixed and adjustable versions
- Different finishes and frames available
- Multiple rims available in white, aluminium and black
- Available in three light levels; 650 lumen (standard halogen), 900 lumen and 1200 lumen
- Slim design; smaller than 60 mm
- Push-in connector with through-wiring option

Benefits

- High-end materials for decorative applications and special anti-glare optics
- 80% energy saving and 15 x longer lifetime compared to halogen luminaire
- Slim design fits most ceiling types
- Dimming driver works with 99 % of wall-mounted dimmers
- Flicker-free thanks to high performance driver with tested dimming function



50000h  
at L70



1 PACK

| Product Type                      | LED | Lumen Output | Colour Temp | Efficacy | Finish    | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------|-----|--------------|-------------|----------|-----------|-----------|-----------|--------------|----------|
|                                   | W   | lm           | K           | (lm/W)   |           |           |           |              |          |
| RS140B LED6-32-/827 PSR PI6 ALU   | 8   | 650          | 2700        | 82       | Aluminium | IP65      | IK02      | 912401483045 | 38287299 |
| RS140B LED6-32-/827 PSR PI6 WH    |     | 650          | 2700        | 82       | White     | IP65      | IK02      | 912401483031 | 38277399 |
| RS140B LED6-32-/830 PSR PI6 ALU   |     | 650          | 3000        | 82       | Aluminium | IP65      | IK02      | 912401483046 | 38288999 |
| RS140B LED6-32-/830 PSR PI6 WH    |     | 650          | 3000        | 82       | White     | IP65      | IK02      | 912401483032 | 38278099 |
| RS140B LED6-32-/840 PSR PI6 ALU   |     | 650          | 4000        | 82       | Aluminium | IP65      | IK02      | 912401483047 | 38289699 |
| RS140B LED6-32-/840 PSR PI6 WH    |     | 650          | 4000        | 82       | White     | IP65      | IK02      | 912401483033 | 38279799 |
| RS140Z MODULE LED6-32-/827        |     | 650          | 2700        | 82       | White     | IP65      | IK02      | 912401483061 | 38295799 |
| RS140Z MODULE LED6-32-/830        |     | 650          | 3000        | 82       | White     | IP65      | IK02      | 912401483062 | 38296499 |
| RS140Z MODULE LED6-32-/840        |     | 650          | 4000        | 82       | White     | IP65      | IK02      | 912401483063 | 38297199 |
| RS141B LED6-32-/827 PSR PI6 ALU   |     | 650          | 2700        | 82       | Aluminium | IP44      | IK02      | 912401483048 | 38290299 |
| RS141B LED6-32-/827 PSR PI6 WH    |     | 650          | 2700        | 82       | White     | IP44      | IK02      | 912401483034 | 38280399 |
| RS141B LED6-32-/830 PSR PI6 ALU   |     | 650          | 3000        | 82       | Aluminium | IP44      | IK02      | 912401483049 | 38291999 |
| RS141B LED6-32-/830 PSR PI6 WH    |     | 650          | 3000        | 82       | White     | IP44      | IK02      | 912401483035 | 38281099 |
| RS141B LED6-32-/840 PSR PI6 ALU   |     | 650          | 4000        | 82       | Aluminium | IP44      | IK02      | 912401483050 | 38292699 |
| RS141B LED6-32-/840 PSR PI6 WH    |     | 650          | 4000        | 82       | White     | IP44      | IK02      | 912401483036 | 38282799 |
| RS142B LED6-32-/827 PSR PI6 WH FR |     | 650          | 2700        | 82       | White     | IP44      | IK02      | 912401483119 | 38417399 |
| RS142B LED6-32-/830 PSR PI6 WH FR |     | 650          | 3000        | 82       | White     | IP44      | IK02      | 912401483120 | 38418099 |
| RS140B LED9-32-/830 PSR PI6 ALU   |     | 900          | 3000        | 82       | Aluminium | IP65      | IK02      | 912401483051 | 38293399 |
| RS140B LED9-32-/830 PSR PI6 WH    |     | 900          | 3000        | 82       | White     | IP65      | IK02      | 912401483039 | 38285899 |
| RS140B LED9-32-/840 PSR PI6 ALU   |     | 900          | 4000        | 82       | Aluminium | IP65      | IK02      | 912401483052 | 38294099 |
| RS140B LED9-32-/840 PSR PI6 WH    |     | 900          | 4000        | 82       | White     | IP65      | IK02      | 912401483040 | 38286599 |
| RS140Z MODULE LED9-32-/830        |     | 900          | 3000        | 82       | White     | IP65      | IK02      | 912401483064 | 38298899 |
| RS140Z MODULE LED9-32-/840        |     | 900          | 4000        | 82       | White     | IP65      | IK02      | 912401483065 | 38299599 |
| RS141B LED9-32-/830 PSR PI6 WH    |     | 900          | 3000        | 82       | White     | IP44      | IK02      | 912401483037 | 38283499 |
| RS141B LED9-32-/840 PSR PI6 WH    |     | 900          | 4000        | 82       | White     | IP44      | IK02      | 912401483038 | 38284199 |
| RS140B LED12-36-/830 PSR PI6 ALU  | 15  | 1200         | 3000        | 82       | Aluminium | IP65      | IK02      | 912401483053 | 38423499 |

# CoreLine

## CoreLine recessed spot – Continued



### Features

- Lifetime: 50,000 hours at L70
- Available in fixed and adjustable versions
- Different finishes and frames available
- Multiple rims available in white, aluminium and black
- Available in three light levels; 650 lumen (standard halogen), 900 lumen and 1200 lumen
- Slim design; smaller than 60 mm
- Push-in connector with through-wiring option

### Benefits

- High-end materials for decorative applications and special anti-glare optics
- 80% energy saving and 15 X longer lifetime compared to halogen luminaire
- Slim design fits most ceiling types
- Dimming driver works with 99 % of wall-mounted dimmers
- Flicker-free thanks to high performance driver with tested dimming function



50000h  
at L70



1 PACK

| Product Type                     | LED | Lumen Output | Colour Temp | Efficacy | Finish    | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------|-----|--------------|-------------|----------|-----------|-----------|-----------|--------------|----------|
|                                  | W   | lm           | K           | (lm/W)   |           |           |           |              |          |
| RS140B LED12-36-/830 PSR PI6 WH  | 15  | 1200         | 3000        | 82       | White     | IP65      | IK02      | 912401483043 | 38421099 |
| RS140B LED12-36-/840 PSR PI6 ALU |     | 1200         | 4000        | 82       | Aluminium | IP65      | IK02      | 912401483054 | 38424199 |
| RS140B LED12-36-/840 PSR PI6 WH  |     | 1200         | 4000        | 82       | White     | IP65      | IK02      | 912401483044 | 38422799 |
| RS141B LED12-36-/830 PSR PI6 WH  |     | 1200         | 3000        | 82       | White     | IP44      | IK02      | 912401483041 | 38419799 |
| RS141B LED12-36-/840 PSR PI6 WH  |     | 1200         | 4000        | 82       | White     | IP44      | IK02      | 912401483042 | 38420399 |

## CoreLine grid light – Accessories



### Features

- Available in single, double and triple spot
- Connectable to high performance light sources of CoreLine Recessed Spot
- Dimming driver works with most wall-mounted dimmers
- Adjustable light sources, 360 degrees rotational and 20 degree tilting angle

### Benefits

- Slim design fits most ceiling types
- High-end materials for decorative applications
- Easy to install tanks to push-in connectors



1 PACK

| Product Type            | Finish | IP rating | IK rating | 12NC         | EOC code |
|-------------------------|--------|-----------|-----------|--------------|----------|
| RS143Z CFRM GRID 1x1 WH | White  | IP20      | IK03      | 912401483212 | 38832499 |
| RS143Z CFRM GRID 1x2 WH | White  | IP20      | IK03      | 912401483213 | 38833199 |
| RS143Z CFRM GRID 1x3 WH | White  | IP20      | IK03      | 912401483214 | 38834899 |

## CoreLine projector



### Features

- Lifetime: 50,000 hours at L70
- Energy efficient: up to 90 lm/W
- Smooth black finish with matt aluminium swivel
- Medium beam (23D) or wide beam angle (36D) available

### Benefits

- Modern design that blends in to most interiors
- Direct replacement of traditional CDM projectors
- Connectable to standard 3C track systems



50000h  
at L70



1 PACK

| Product Type                 | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                              | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| ST150T LED22S-23-/830 PSU BK | 24  | 2200         | 3000        | 90       | Black  | IP20      | IK02      | 912401483217 | 79067799 |
| ST150T LED22S-23-/830 PSU WH |     | 2200         | 3000        | 90       | Black  | IP20      | IK02      | 912401483219 | 79069199 |
| ST150T LED22S-23-/840 PSU BK |     | 2200         | 4000        | 90       | Black  | IP20      | IK02      | 912401483218 | 79068499 |
| ST150T LED22S-23-/840 PSU WH |     | 2200         | 4000        | 90       | Black  | IP20      | IK02      | 912401483220 | 79070799 |
| ST150T LED22S-36-/830 PSU BK |     | 2200         | 3000        | 90       | Black  | IP20      | IK02      | 912401483221 | 79071499 |
| ST150T LED22S-36-/830 PSU WH |     | 2200         | 3000        | 90       | Black  | IP20      | IK02      | 912401483223 | 79073899 |
| ST150T LED22S-36-/840 PSU BK |     | 2200         | 4000        | 90       | Black  | IP20      | IK02      | 912401483222 | 79072199 |
| ST150T LED22S-36-/840 PSU WH |     | 2200         | 4000        | 90       | Black  | IP20      | IK02      | 912401483224 | 79074599 |
|                              |     |              |             |          |        |           |           |              |          |
|                              |     |              |             |          |        |           |           |              |          |

## CoreLine bollard



### Features

- Lifetime: 50,000 hours at L70
- 1000 lm, available with symmetric and asymmetric optic
- Available in warm white and neutral white
- 1m height
- IP65 and IK08 rated
- Supplied with cable and connector

### Benefits

- Comfortable light
- Easy to install
- Saves energy compared to conventional lamps



50000h  
at L70



1 PACK

| Product Type                         | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|--------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                      | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BCP155 LED100/NW PSU 220-240V S 7043 | 12  | 1000         | 4000        | 85       | Grey   | IP65      | IK10      | 912401483112 | 38378700 |
| BCP155 LED100/WW PSU 220-240V S 7043 |     | 1000         | 3000        | 85       | Grey   | IP65      | IK10      | 912401483111 | 38377000 |
| BCP155 LED100/NW PSU 220-240V A 7043 | 13  | 1000         | 4000        | 80       | Grey   | IP65      | IK10      | 912401483110 | 38376300 |
| BCP155 LED100/WW PSU 220-240V A 7043 |     | 1000         | 3000        | 80       | Grey   | IP65      | IK10      | 912401483109 | 38375600 |

CoreLine

CoreLine bollard – Accessories

|  |        |           |              |          |  |  |  |  |  |
|-----------------------------------------------------------------------------------|--------|-----------|--------------|----------|-------------------------------------------------------------------------------------|--|--|--|--|
| Product Type                                                                      | Finish | IK rating | 12NC         | EOC code |                                                                                     |  |  |  |  |
| ZCP150 ANB L500                                                                   | Grey   | IK10      | 912401483113 | 38379400 |                                                                                     |  |  |  |  |

CoreLine highbay

| <div><div><b>Features</b><ul style="list-style-type: none"><li>Lifetime: 50,000 hours at L80</li><li>Energy efficient: up to 137lm/W</li><li>Consistent colour rendering (CRI = 80) in compliance with EN-12464-1</li><li>DALI and emergency lighting options available</li></ul></div><div><b>Benefits</b><ul style="list-style-type: none"><li>Point-for-point replacement of 250W and 400W conventional HPI highbays</li><li>Minimum dimming level is fixed at 25%</li><li>New integrated sensor version (advanced groups and zones creation, group presence detection, task-tuning) configurable via the Philips Field App with an IR dongle</li></ul></div></div> <div></div> |     |              |             |          |        |           |           |              |          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
| Product Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BY120P G4 LED100S/840 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 69  | 10000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401569851 | 33571100 |
| BY120P G4 LED100S/840 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401569951 | 33570400 |
| BY120P G4 LED100S/865 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401575251 | 33567400 |
| BY120P G4 LED100S/865 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401575351 | 33566700 |
| BY120P G4 LED100S/840 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 73  | 10000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401574451 | 33702900 |
| BY120P G4 LED100S/840 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401574551 | 33703600 |
| BY120P G4 LED100S/865 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401575651 | 33704300 |
| BY120P G4 LED100S/865 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 10000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401575751 | 33705000 |
| NEW BY120P G4 LED100S/840 SRD WB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 138 | 10000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401562461 | 36083600 |
| NEW BY120P G4 LED100S/840 SRD NB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |     | 10000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401579661 | 36084300 |
| BY121P G4 LED200S/840 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 20000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401570051 | 33569800 |
| BY121P G4 LED200S/840 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     | 20000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401570151 | 33568100 |

CoreLine highbay – Continued

| <div><div><b>Features</b><ul style="list-style-type: none"><li>Lifetime: 50,000 hours at L80</li><li>Energy efficient: up to 137lm/W</li><li>Consistent colour rendering (CRI = 80) in compliance with EN-12464-1</li><li>DALI and emergency lighting options available</li></ul></div><div><b>Benefits</b><ul style="list-style-type: none"><li>Point-for-point replacement of 250W and 400W conventional HPI highbays</li><li>Minimum dimming level is fixed at 25%</li><li>New integrated sensor version (advanced groups and zones creation, group presence detection, task-tuning) configurable via the Philips Field App with an IR dongle</li></ul></div></div> <div></div> |     |              |             |          |        |           |           |              |          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
| Product Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BY121P G4 LED200S/865 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 138 | 20000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401575451 | 33565000 |
| BY121P G4 LED200S/865 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 20000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401575551 | 33564300 |
| NEW BY121P G4 LED200S/840 SRD WB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 145 | 20000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401559961 | 36155000 |
| NEW BY121P G4 LED200S/840 SRD NB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |     | 20000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401579561 | 36390500 |
| BY121P G4 LED200S/840 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 146 | 20000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401574651 | 33698500 |
| BY121P G4 LED200S/840 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 20000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401574751 | 33699200 |
| BY121P G4 LED200S/865 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 20000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401575851 | 33700500 |
| BY121P G4 LED200S/865 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 20000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401575951 | 33701200 |
| BY122P G4 LED250S/840 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 172 | 25000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401578351 | 33664000 |
| BY122P G4 LED250S/840 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 4000        | 145      | Grey   | IP65      | IK07      | 911401578451 | 33665700 |
| BY122P G4 LED250S/865 PSU NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401578551 | 33666400 |
| BY122P G4 LED250S/865 PSU WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 6500        | 145      | Grey   | IP65      | IK07      | 911401578651 | 33667100 |
| BY122P G4 LED250S/840 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 183 | 25000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401582051 | 33879800 |
| BY122P G4 LED250S/840 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 4000        | 137      | Grey   | IP65      | IK07      | 911401582151 | 33880400 |
| BY122P G4 LED250S/865 PSD NB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401582251 | 33881100 |
| BY122P G4 LED250S/865 PSD WB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     | 25000        | 6500        | 137      | Grey   | IP65      | IK07      | 911401582351 | 33882800 |
| NEW BY122P G4 LED250S/840 SRD WB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |     | 25000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401559861 | 36391200 |
| NEW BY122P G4 LED250S/840 SRD NB SNHR200                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |     | 25000        | 4000        | 137      | Grey   | IP20      | IK05      | 911401579761 | 36392900 |
| BY121Z G4 BR L300                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |     |              |             |          |        | -         | -         | 911401511561 | 34186600 |
| BY121Z G4 BR L400                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |     |              |             |          |        | -         | -         | 911401511761 | 34187300 |
| NEW IR Dongle v2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |     |              |             |          |        | -         | -         | 929001678906 | 64414700 |

CoreLine

CoreLine batten



Features

- Lifetime: 50,000 hours at L70
- Many options available: L600/1200/1500/1800, up to 10000 lm, 3000K and 4000K
- Through-wiring standard included
- DALI and emergency lighting options available
- New BESA fixing

Benefits

- Direct replacement for conventional battens in terms of light performance, length and installation flexibility
- Smart product architecture for easy, flexible and tool-free installation with openable top compartment and push-in connector
- Homogeneous light distribution in every application through a wide choice of reflectors available as accessories



50000h  
at L70



1 PACK

|     | Product Type                         | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----|--------------------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|     |                                      | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| NEW | BN126C LED20S/830 PSU TW1 L600       | 17   | 2000         | 3000        | 118      | White  | IP20      | IK02      | 911401897080 | 36345599 |
| NEW | BN126C LED22S/840 PSU TW1 L600       |      | 2200         | 4000        | 129      | White  | IP20      | IK02      | 911401896980 | 36344899 |
| NEW | BN126C LED23S/830 PSU TW1 L1200      | 18   | 2300         | 3000        | 128      | White  | IP20      | IK02      | 911401897280 | 36347999 |
| NEW | BN126C LED25S/840 PSU TW1 L1200      |      | 2500         | 4000        | 139      | White  | IP20      | IK02      | 911401897180 | 36346299 |
| NEW | BN126C LED32S/830 PSU TW1 L1500      | 25.5 | 3200         | 3000        | 125      | White  | IP20      | IK02      | 911401897880 | 36353099 |
| NEW | BN126C LED35S/840 PSU TW1 L1500      |      | 3500         | 4000        | 137      | White  | IP20      | IK02      | 911401897780 | 36352399 |
| NEW | BN126C LED38S/830 PSU TW1 L1200      | 31   | 3800         | 3000        | 123      | White  | IP20      | IK02      | 911401897480 | 36349399 |
| NEW | BN126C LED41S/840 PSU TW1 L1200      |      | 4100         | 4000        | 132      | White  | IP20      | IK02      | 911401897380 | 36348699 |
| NEW | BN126C LED41S/840 PSD L1200          | 33   | 4100         | 4000        | 124      | White  | IP20      | IK04      | 911401804681 | 36551099 |
| NEW | BN126C LED41S/840 PSU ELB3 TW1 L1200 | 34   | 4100         | 4000        | 121      | White  | IP20      | IK04      | 910505100628 | 96818299 |
| NEW | BN126C LED46S/830 PSU TW1 L1500      | 40   | 4800         | 3000        | 120      | White  | IP20      | IK02      | 911401898080 | 36355499 |
| NEW | BN126C LED52S/840 PSU TW1 L1500      |      | 5200         | 4000        | 130      | White  | IP20      | IK02      | 911401897980 | 36354799 |
| NEW | BN126C LED52S/840 PSD L1500          | 41   | 5200         | 4000        | 127      | White  | IP20      | IK04      | 911401804781 | 36552799 |
| NEW | BN126C LED52S/840 PSU ELB3 TW1 L1500 | 43   | 5200         | 4000        | 121      | White  | IP20      | IK04      | 910505100629 | 96820599 |
| NEW | BN126C LED57S/830 PSU TW1 L1800      | 49   | 6000         | 3000        | 122      | White  | IP20      | IK02      | 911401898480 | 36359299 |
| NEW | BN126C LED60S/830 PSU TW1 L1200      |      | 6000         | 3000        | 122      | White  | IP20      | IK02      | 911401897680 | 36351699 |
| NEW | BN126C LED64S/840 PSU TW1 L1200      |      | 6400         | 4000        | 131      | White  | IP20      | IK02      | 911401897580 | 36350999 |
| NEW | BN126C LED64S/840 PSU TW1 L1800      |      | 6400         | 4000        | 130      | White  | IP20      | IK02      | 911401898380 | 36358599 |
| NEW | BN126C LED72S/830 PSU TW1 L1500      | 59   | 7400         | 3000        | 125      | White  | IP20      | IK02      | 911401898280 | 36357899 |
| NEW | BN126C LED80S/840 PSU TW1 L1500      |      | 8000         | 4000        | 135      | White  | IP20      | IK02      | 911401898180 | 36356199 |
| NEW | BN126C LED90S/830 PSU TW1 L1800      | 75   | 9400         | 3000        | 125      | White  | IP20      | IK02      | 911401898680 | 36361599 |
| NEW | BN126C LED100S/840 PSU TW1 L1800     |      | 10000        | 4000        | 133      | White  | IP20      | IK02      | 911401898580 | 36360899 |

CoreLine batten - Accessories



|     | Product Type                                                 | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----|--------------------------------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|     |                                                              | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| NEW | BN126Z REF A1 L600 (wall-washer light distribution)          |     |              |             |          |        | IP20      | IK04      | 911401776812 | 36575699 |
| NEW | BN126Z REF A1 L1200 (wall-washer light distribution)         |     |              |             |          |        | IP20      | IK04      | 911401776822 | 36576399 |
| NEW | BN126Z REF A1 L1500 (wall-washer light distribution)         |     |              |             |          |        | IP20      | IK04      | 911401776832 | 36577099 |
| NEW | BN126Z REF A1 L1800 (wall-washer light distribution)         |     |              |             |          |        | IP20      | IK04      | 911401776842 | 36578799 |
| NEW | BN126Z REF A2 L600 (slight asymmetrical light distribution)  |     |              |             |          |        | IP20      | IK04      | 911401776852 | 36579499 |
| NEW | BN126Z REF A2 L1200 (slight asymmetrical light distribution) |     |              |             |          |        | IP20      | IK04      | 911401776862 | 36580099 |
| NEW | BN126Z REF A2 L1500 (slight asymmetrical light distribution) |     |              |             |          |        | IP20      | IK04      | 911401776872 | 36581799 |
| NEW | BN126Z REF A2 L1800 (slight asymmetrical light distribution) |     |              |             |          |        | IP20      | IK04      | 911401776882 | 36582499 |
| NEW | BN126Z Suspension cable                                      |     |              |             |          |        | IP20      | IK04      | 911401776802 | 36574999 |

CoreLine

CoreLine trunking



**Features**

- Lifetime: 50,000 hours at L80
- Highly efficient and reliable LED boards
- Advanced optics enable precise and energy-saving beam shapes

**Benefits**

- Only two 12 NC codes needed to make a light line
- DALI and emergency lighting options available
- Reduced maintenance and best lumens per € solution
- Excellent beam shapes and sparkle for product enhancement



50000h  
at L80

1 PACK

| Product Type                            | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                         | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| LL120X LED45S/840 PSD VWB 9 VLC WH ELD3 | 32  | 4500         | 4000        | 141      | White  | IP20      | IK02      | 919013004258 | 63372900 |
| LL121X LED42S/840 1X PSD O 7 WH         |     | 4200         | 4000        | 131      | White  | IP20      | IK02      | 910925683006 | 90732900 |
| LL121X LED42S/840 1X PSD O 9 EL3 WH     |     | 4200         | 4000        | 131      | White  | IP20      | IK02      | 910770201546 | 34461300 |
| LL121X LED42S/840 1X PSU O 7 EL3 WH     |     | 4200         | 4000        | 131      | White  | IP20      | IK02      | 910770201547 | 34462000 |
| LL121X LED45S/840 1X PSD A 9 WH         |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925683016 | 90741100 |
| LL121X LED45S/840 1x PSD DA20 7 WH      |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682946 | 88203900 |
| LL121X LED45S/840 1X PSD MB 7 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682938 | 88195700 |
| LL121X LED45S/840 1X PSD MB 9 EL3 WH    |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910770201577 | 34492700 |
| LL121X LED45S/840 1X PSD NB 7 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682932 | 88189600 |
| LL121X LED45S/840 1X PSD VWB 9 VLC WH   |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910770211371 | 06919000 |
| LL121X LED45S/840 1x PSD WB 7 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925802903 | 88140700 |
| LL121X LED45S/840 1X PSD WB 9 VLC WH    |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910770211370 | 06918300 |
| LL121X LED45S/840 1X PSD WB 9 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925683015 | 90740400 |
| LL121X LED45S/840 1x PSU DA20 5 WH      |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682926 | 88183400 |
| LL121X LED45S/840 1x PSU MB 5 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682914 | 88171100 |
| LL121X LED45S/840 1x PSU NB 5 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682955 | 88435400 |
| LL121X LED45S/840 1x PSU WB 5 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925682920 | 88177300 |
| LL121X LED45S/840 PSD WB 9 VLC WH ELD3  |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 919013004257 | 03370500 |
| LL121X LED45S/865 1X PSU WB 7 EL3 WH    |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910770200986 | 32468400 |
| LL122X LED45S/840 1X PSD WB 9 WH        |     | 4500         | 4000        | 141      | White  | IP20      | IK02      | 910925683057 | 90782400 |
| LL121X LED45S/840 1X PSD WB 9 EL3 WH    | 34  | 4500         | 4000        | 132      | White  | IP20      | IK02      | 910925683049 | 90774900 |
| LL121X LED45S/840 1X PSU WB 7 EL3 WH    |     | 4500         | 4000        | 132      | White  | IP20      | IK02      | 910925682952 | 88209100 |
| LL121X LED75S/840 1x PSD O 7 WH         | 54  | 7500         | 4000        | 139      | White  | IP20      | IK02      | 910925863981 | 38102100 |
| LL121X LED75S/840 1X PSU O 5 WH         |     | 7500         | 4000        | 139      | White  | IP20      | IK02      | 910925864015 | 38135900 |
| LL121X LED76S/830 1X PSD DA20 7 WH      |     | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925864050 | 38170000 |
| LL121X LED76S/830 1x PSD WB 7 WH        |     | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925863997 | 38118200 |

CoreLine trunking – Continued



**Features**

- Lifetime: 50,000 hours at L80
- Highly efficient and reliable LED boards
- Advanced optics enable precise and energy-saving beam shapes

**Benefits**

- Only two 12 NC codes needed to make a light line
- DALI and emergency lighting options available
- Reduced maintenance and best lumens per € solution
- Excellent beam shapes and sparkle for product enhancement



50000h  
at L80

1 PACK

| Product Type                           | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|----------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                        | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| LL121X LED76S/830 1x PSD WB 9 WH       | 54  | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925864039 | 38159500 |
| LL121X LED76S/830 1x PSU DA20 5 WH     |     | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925864032 | 38152600 |
| LL121X LED76S/830 1x PSU MB 5 WH       |     | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925864012 | 38132800 |
| LL121X LED76S/830 1x PSU WB 5 WH       |     | 7600         | 3000        | 141      | White  | IP20      | IK02      | 910925863980 | 38101400 |
| LL121X LED80S/840 1x PSD DA20 7 WH     |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864017 | 38137300 |
| LL121X LED80S/840 1x PSD MB 7 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864004 | 38124300 |
| LL121X LED80S/840 1x PSD MB 9 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864023 | 38143400 |
| LL121X LED80S/840 1x PSD NB 7 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863999 | 38120500 |
| LL121X LED80S/840 1x PSD NB 9 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864008 | 38128100 |
| LL121X LED80S/840 1x PSD WB 7 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863971 | 38092500 |
| LL121X LED80S/840 1x PSD WB 9 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864005 | 38125000 |
| LL121X LED80S/840 1x PSU DA20 5 WH     |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863993 | 38114400 |
| LL121X LED80S/840 1x PSU MB 5 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863982 | 38103800 |
| LL121X LED80S/840 1x PSU NB 5 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864007 | 38127400 |
| LL121X LED80S/840 1x PSU VWB 5 WH      |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864002 | 38122900 |
| LL121X LED80S/840 1x PSU WB 5 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863973 | 38094900 |
| LL121X LED80S/840 PSU WB SMB WH KIT    |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925863957 | 38078900 |
| LL122X LED80S/840 1x PSD WB 9 WH       |     | 8000         | 4000        | 148      | White  | IP20      | IK02      | 910925864029 | 38149600 |
| LL121X LED76S/830 1X PSD WB 9 EL3 WH   |     | 7600         | 3000        | 136      | White  | IP20      | IK02      | 910925864027 | 38147200 |
| LL121X LED80S/840 1X PSD DA20 9 EL3 WH | 56  | 8000         | 4000        | 143      | White  | IP20      | IK02      | 910925864006 | 38126700 |
| LL121X LED80S/840 1x PSD WB 9 EL3 WH   |     | 8000         | 4000        | 143      | White  | IP20      | IK02      | 910925864013 | 38133500 |
| LL121X LED80S/840 1x PSU DA20 7 EL3 WH |     | 8000         | 4000        | 143      | White  | IP20      | IK02      | 910925864045 | 38165600 |
| LL121X LED80S/840 1x PSU NB 7 EL3 WH   |     | 8000         | 4000        | 143      | White  | IP20      | IK02      | 910925864047 | 38167000 |
| LL121X LED80S/840 1x PSU WB 7 EL3 WH   | 62  | 8000         | 4000        | 143      | White  | IP20      | IK02      | 910925864003 | 38123600 |
| LL122X LED80S/840 1X PSD WB 9 WH       |     | 8000         | 4000        | 129      | White  | IP20      | IK02      | 910925683063 | 90788600 |
| LL120X LED84S/840 2X PSD O 7 VLC WH    | 64  | 8400         | 4000        | 131      | White  | IP20      | IK02      | 910925683008 | 90734300 |

CoreLine

CoreLine trunking – Continued



**Features**

- Lifetime: 50,000 hours at L80
- Highly efficient and reliable LED boards
- Advanced optics enable precise and energy-saving beam shapes

**Benefits**

- Only two 12 NC codes needed to make a light line
- DALI and emergency lighting options available
- Reduced maintenance and best lumens per € solution
- Excellent beam shapes and sparkle for product enhancement

  
50000h  
at L80

  
1 PACK

| Product Type                            | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                         | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| LL120X LED90S/840 2X PSD A 9 VLC WH     | 64  | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925683022 | 90747300 |
| LL120X LED90S/840 2x PSD DA20 7 VLC WH  |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682947 | 88204600 |
| LL120X LED90S/840 2X PSD MB 7 VLC WH    |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682939 | 88196400 |
| LL120X LED90S/840 2x PSD NB 7 VLC WH    |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682933 | 88190200 |
| LL120X LED90S/840 2x PSD VWB 9 VLC WH   |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925683023 | 90748000 |
| LL120X LED90S/840 2x PSD WB 7 VLC WH    |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925772904 | 88141400 |
| LL120X LED90S/840 2x PSD WB 9 VLC WH    |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925683021 | 90746600 |
| LL120X LED90S/840 2x PSU DA20 5 WH      |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682927 | 88184100 |
| LL120X LED90S/840 2x PSU MB 5 WH        |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682915 | 88172800 |
| LL120X LED90S/840 2x PSU NB 5 WH        |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682908 | 88166700 |
| LL120X LED90S/840 2x PSU WB 5 WH        |     | 9000         | 4000        | 141      | White  | IP20      | IK02      | 910925682921 | 88178000 |
| LL120X LED150S/840 2x PSD O 7 VLC WH    |     | 15000        | 4000        | 139      | White  | IP20      | IK02      | 910925863968 | 38089500 |
| LL120X LED150S/840 2x PSU O 5 WH        |     | 15000        | 4000        | 139      | White  | IP20      | IK02      | 910925863979 | 38100700 |
| LL120X LED152S/830 2x PSD DA20 7 VLC WH |     | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925864031 | 38151900 |
| LL120X LED152S/830 2x PSD WB 7 VLC WH   |     | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925863994 | 38115100 |
| LL120X LED152S/830 2X PSD WB 9 VLC WH   |     | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925864001 | 38121200 |
| LL120X LED152S/830 2x PSU DA20 5 WH     | 108 | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925863988 | 38109000 |
| LL120X LED152S/830 2x PSU MB 5 WH       |     | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925863995 | 38116800 |
| LL120X LED152S/830 2x PSU WB 5 WH       |     | 15200        | 3000        | 141      | White  | IP20      | IK02      | 910925863983 | 38104500 |
| LL120X LED160S/840 2X PSD A 9 VLC WH    |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925864044 | 38164900 |
| LL120X LED160S/840 2x PSD DA20 7 VLC WH |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925864016 | 38136600 |
| LL120X LED160S/840 2x PSD MB 7 VLC WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863977 | 38098700 |
| LL120X LED160S/840 2x PSD MB 9 VLC WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925864014 | 38134200 |
| LL120X LED160S/840 2x PSD NB 7 VLC WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863992 | 38113700 |
| LL120X LED160S/840 2x PSD NB 9 VLC WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863989 | 38110600 |
| LL120X LED160S/840 2x PSD WB 7 VLC WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863966 | 38087100 |

CoreLine trunking – Continued



**Features**

- Lifetime: 50,000 hours at L80
- Highly efficient and reliable LED boards
- Advanced optics enable precise and energy-saving beam shapes

**Benefits**

- Only two 12 NC codes needed to make a light line
- DALI and emergency lighting options available
- Reduced maintenance and best lumens per € solution
- Excellent beam shapes and sparkle for product enhancement

  
50000h  
at L80

  
1 PACK

| Product Type                          | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|---------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                       | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| LL120X LED160S/840 2x PSD WB 9 VLC WH | 108 | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863978 | 38099400 |
| LL120X LED160S/840 2x PSU DA20 5 WH   |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863972 | 38093200 |
| LL120X LED160S/840 2x PSU MB 5 WH     |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863970 | 38091800 |
| LL120X LED160S/840 2x PSU NB 5 WH     |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863975 | 38096300 |
| LL120X LED160S/840 2x PSU VWB 5 WH    |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863996 | 38117500 |
| LL120X LED160S/840 2x PSU WB 5 WH     |     | 16000        | 4000        | 148      | White  | IP20      | IK02      | 910925863967 | 38088800 |

CoreLine trunking – Accessories



  
1 PACK

| Product Type             | 12NC         | EOC code |
|--------------------------|--------------|----------|
| LL120X 9 WH BC           | 910770201062 | 32606000 |
| LL120X 9WH CPE SENSOR    | 919913998437 | 61766800 |
| LL120Z CB WH (5PCS)      | 910925255042 | 88161299 |
| LL120Z EC7-M-F (5PCS)    | 910925255041 | 88160599 |
| LL120Z EC9-M-F (4PCS)    | 910925255170 | 91956899 |
| LL120Z EP WH (6PCS)      | 910925255043 | 88162999 |
| LL120Z LCB-7             | 910925255141 | 90799200 |
| LL120Z MB-SW 2xEP CU7 WH | 910925255036 | 88146900 |

CoreLine

CoreLine trunking – Accessories – Continued



| Product Type             | 12NC         | EOC code |
|--------------------------|--------------|----------|
| LL120Z MB-SW 2xEP CU9 WH | 910925255169 | 91260600 |
| LL120Z MB-SW WH (2PCS)   | 910925255035 | 88155199 |
| LL120Z PB WH (5PCS)      | 910925255044 | 88163699 |
| LL120Z SMB WH (5PCS)     | 910925255037 | 88156899 |
| LL120Z SW2-1250          | 910925255038 | 88157599 |
| LL120Z SW2-3000          | 910925255039 | 88158299 |
| LL120Z SW2-5000          | 910925255040 | 88159999 |
| LL121X 7 WH BC           | 910925682907 | 88144500 |
| LL121X 9 WH BC           | 910770200948 | 30764900 |
| LL123X 5C6 7             | 910925683073 | 90798500 |
| LL123X 5C6 9             | 910925683072 | 90797800 |

CoreLine tempo – small



Features

- Lifetime: 75,000 hours at L80
- Energy efficient: up to 130 lm/W
- High-performance asymmetrical and symmetrical optics
- IP65 and IK08 rated
- U-shaped universal mounting bracket and external quick 3-pole
- High surge protection : 6 kV/8kV
- Options: 3000K CCT, DALI control and harsh environment coatings

Benefits

- Point-to-point replacement up to 400W conventional HPI-TP floodlights
- Reliable quality: die-casting aluminium housing guarantees robustness, vibration-proof, wind force protection



| Product Type                 | LED | Lumen Output | Colour Temp | Efficacy | Finish             | IP rating | IK rating | 12NC         | EOC code |
|------------------------------|-----|--------------|-------------|----------|--------------------|-----------|-----------|--------------|----------|
|                              | W   | lm           | K           | (lm/W)   |                    |           |           |              |          |
| BVP110 LED42/NW Asymmetrical | 38  | 4200         | 4000        | 111      | Aluminium and Grey | IP65      | IK08      | 911401555231 | 30635300 |
| BVP110 LED42/NW Symmetrical  |     | 4200         | 4000        | 111      | Aluminium and Grey | IP65      | IK08      | 911401555331 | 30636000 |

CoreLine tempo – medium



Features

- Lifetime: 75,000 hours at L80
- Energy efficient: up to 130 lm/W
- High-performance asymmetrical and symmetrical optics
- IP65 and IK08 rated
- U-shaped universal mounting bracket and external quick 3-pole
- High surge protection : 6 kV/8kV
- Options: 3000K CCT, DALI control and harsh environment coatings

Benefits

- Point-to-point replacement up to 400W conventional HPI-TP floodlights
- Reliable quality: Die-casting aluminium housing guarantees robustness, vibration-proof, wind force protection



| Product Type                      | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                   | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BVP125 LED80-4S/740 Asymmetrical  | 66  | 8200         | 4000        | 124      | Grey   | IP66      | IK08      | 912300024002 | 45588000 |
| BVP125 LED80-4S/740 Symmetrical   |     | 8200         | 4000        | 124      | Grey   | IP66      | IK08      | 912300024004 | 45590300 |
| BVP125 LED120-4S/740 Asymmetrical | 98  | 12300        | 4000        | 126      | Grey   | IP66      | IK08      | 912300024001 | 45587300 |
| BVP125 LED120-4S/740 Symmetrical  |     | 12300        | 4000        | 126      | Grey   | IP66      | IK08      | 912300024003 | 45589700 |

CoreLine tempo – large



Features

- Lifetime: 75,000 hours at L80
- Energy efficient: up to 130 lm/W
- High-performance asymmetrical and symmetrical optics
- IP65 and IK08 rated
- U-shaped universal mounting bracket and external quick 3-pole
- High surge protection : 6 kV/8kV
- Options: 3000K CCT, DALI control and harsh environment coatings

Benefits

- Point-to-point replacement up to 400W conventional HPI-TP floodlights
- Reliable quality: Die-casting aluminium housing guarantees robustness, vibration-proof, wind force protection



| Product Type                      | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|-----------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                   | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BVP130 LED160-4S/740 Asymmetrical | 126 | 16400        | 4000        | 130      | Grey   | IP66      | IK08      | 912300023662 | 9641000  |
| BVP130 LED160-4S/740 Symmetrical  |     | 16400        | 4000        | 130      | Grey   | IP66      | IK08      | 912300023665 | 9644100  |
| BVP130 LED210-4S/740 Asymmetrical | 164 | 21320        | 4000        | 130      | Grey   | IP66      | IK08      | 912300023661 | 9640300  |
| BVP130 LED210-4S/740 Symmetrical  |     | 21320        | 4000        | 130      | Grey   | IP66      | IK08      | 912300023664 | 9643400  |
| BVP130 LED260-4S/740 Asymmetrical | 220 | 26400        | 4000        | 120      | Grey   | IP66      | IK08      | 912300023660 | 9639700  |
| BVP130 LED260-4S/740 Symmetrical  |     | 26400        | 4000        | 120      | Grey   | IP66      | IK08      | 912300023663 | 9642700  |

CoreLine tempo - X-large



NEW

**Features**

- Lifetime: 75,000 hours at L80
- Energy efficient: up to 130 lm/W
- High-performance asymmetrical and symmetrical optics
- IP65 and IK08 rated

**Benefits**

- U-shaped universal mounting bracket and external quick 3-pole
- High surge protection : 6 kV/8kV
- Options: 3000K CCT, DALI control and harsh environment coatings

**Benefits**

- Point-to-point replacement up to 400W conventional HPI-TP floodlights
- Reliable quality: Die-casting aluminium housing guarantees robustness, vibration-proof, wind force protection



75000h  
at L80



1 PACK

| Product Type                               | LED | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|--------------------------------------------|-----|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                                            | W   | lm           | K           | (lm/W)   |        |           |           |              |          |
| BVP140 LED360-4S 30K6/740 PSD Asymmetrical | 225 | 30600        | 4000        | 136      | Grey   | IP66      | IK08      | 912300024344 | 87288500 |
| BVP140 LED360-4S 30K6/740 PSU Asymmetrical |     | 30600        | 4000        | 136      | Grey   | IP66      | IK08      | 912300024336 | 87280900 |
| BVP140 LED360-4S 31K3/740 PSD Symetrical   |     | 31320        | 4000        | 139      | Grey   | IP66      | IK08      | 912300024348 | 87292200 |
| BVP140 LED360-4S 31K3/740 PSU Symetrical   |     | 31320        | 4000        | 139      | Grey   | IP66      | IK08      | 912300024340 | 87284700 |
| BVP140 LED420-4S 35K3/740 PSD Asymmetrical | 250 | 35280        | 4000        | 141      | Grey   | IP66      | IK08      | 912300024343 | 87287800 |
| BVP140 LED420-4S 35K3/740 PSU Asymmetrical |     | 35280        | 4000        | 141      | Grey   | IP66      | IK08      | 912300024335 | 87279300 |
| BVP140 LED420-4S 36K1/740 PSD Symetrical   |     | 36120        | 4000        | 144      | Grey   | IP66      | IK08      | 912300024347 | 87291500 |
| BVP140 LED420-4S 36K1/740 PSU Symetrical   |     | 36120        | 4000        | 144      | Grey   | IP66      | IK08      | 912300024339 | 87283000 |
| BVP140 LED480-4S 40K3/740 PSD Asymmetrical | 295 | 40320        | 4000        | 137      | Grey   | IP66      | IK08      | 912300024342 | 87286100 |
| BVP140 LED480-4S 40K3/740 PSU Asymmetrical |     | 40320        | 4000        | 137      | Grey   | IP66      | IK08      | 912300024334 | 87278600 |
| BVP140 LED480-4S 41K3/740 PSD Symetrical   |     | 41280        | 4000        | 140      | Grey   | IP66      | IK08      | 912300024346 | 87290800 |
| BVP140 LED480-4S 41K3/740 PSU Symetrical   |     | 41280        | 4000        | 140      | Grey   | IP66      | IK08      | 912300024338 | 87282300 |

CoreLine malaga and Accessories



1



2

**Features**

- Lifetime: 70,000 hours at L70
- Highly efficient and reliable LED boards
- Advanced optics enable precise and energy-saving beam shapes

**Benefits**

- Reduced maintenance and best lumens per € solution
- Excellent beam shapes and sparkle for product enhancement



70000h  
at L70



1 PACK

| Product Type             | LED  | Lumen Output | Colour Temp | Efficacy | Finish | IP rating | IK rating | 12NC         | EOC code |
|--------------------------|------|--------------|-------------|----------|--------|-----------|-----------|--------------|----------|
|                          | W    | lm           | K           | (lm/W)   |        |           |           |              |          |
| 1 BRP101 LED37/740 I DM  | 29.6 | 3054         | 4000        | 103      | Grey   | IP65      | IK08      | 911401824180 | 99815100 |
| 1 BRP102 LED55/740 I DM  | 39   | 4600         | 4000        | 118      | Grey   | IP65      | IK08      | 910925865340 | 99817500 |
| 1 BRP102 LED75/740 I DM  | 56.5 | 6133         | 4000        | 109      | Grey   | IP65      | IK08      | 910925865342 | 99819900 |
| 1 BRP102 LED110/740 I DM | 83   | 9006         | 4000        | 111      | Grey   | IP65      | IK08      | 910925865344 | 99821200 |
| 2 ZRP220 AD60/60 A5      |      |              |             |          |        |           |           | 910925227912 | 62134100 |

# Philips Ledinaire

The essential range of trusted products for everyday lighting jobs that need good performance

Find the **right** solution in our range using the **Selector tool**  
[productfinder.lighting.philips.com](http://productfinder.lighting.philips.com)



Trusted



Reliable



Great value

## Ledinaire Floodlight



- Good quality finishing and design
- Reliable driver, less early failures
- Light output to meet standard applications
- Easy to install, supplied with stripped cable

## Ledinaire Panel



- Metal frame for better robustness
- High quality lightguide, no yellowing
- Reliable driver, fewer early failures
- Office compliant available

## Ledinaire Highbay



- Easy to use: light levels tuned to conventional
- Reliable driver, fewer early failures
- High efficacy up to 110 lm/W

## Ledinaire

Choose affordable, reliable and energy-efficient lighting from the leading name in LED.

### Ledinaire panel

[lighting.philips.co.uk/systems/themes/ledinaire](http://lighting.philips.co.uk/systems/themes/ledinaire)



#### Features

- 3400 lm light output, 100lm/W
- Office compliant (OC= $\leq$ 19UGR) & non-office compliant (NOC) versions
- Accessories for plaster, surface-mount and suspension available, safety cable included
- New increased lifetime: 50,000 hours at L70

#### Benefits

- Trusted performance: Philips quality tested driver
- Steel frame for extra robustness
- High quality lightguide to avoid early yellowing
- Easy quick connector for fast installation



50000h  
at L70



4  
PACK

| Product Type                                             | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|----------------------------------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                                          | W   | lm           | K           |           |              |          |
| NEW RC065B LED34S/840 PSU W60L60 NOC UKI                 | 34  | 3400         | 4000        | IP20      | 911401899680 | 36446999 |
| RC065B LED34S/840 PSU W60L60 OC UKI                      |     | 3400         | 4000        | IP20      | 911401899880 | 36450699 |
| NEW RC065B LED34S/865 PSU W60L60 NOC UKI                 |     | 3400         | 6500        | IP20      | 911401899780 | 36447699 |
| NEW RC065B LED34S/865 PSU W60L60 OC                      |     | 3400         | 6500        | IP20      | 911401884680 | 36204599 |
| NEW RC065B LED34S/840 PSU W60L60 NOC UKI ELB3            | 37  | 3400         | 4000        | IP20      | 919013004385 | 63499300 |
| NEW RC065B LED34S/840 PSU W60L60 OC UKI ELB3             |     | 3400         | 4000        | IP20      | 919013004386 | 63500600 |
| NEW RC065B LED34S/865 PSU W60L60 NOC UKI ELB3            |     | 3400         | 6500        | IP20      | 919013004387 | 63501300 |
| RC007Z Plaster ceiling set                               | -   | -            | -           | -         | 911401824180 | 34716599 |
| RC065Z Safety cable                                      | -   | -            | -           | -         | 911401892680 | 36274899 |
| RC065Z Surface-mounting set W60L60                       | -   | -            | -           | -         | 911401892480 | 36272499 |
| RC065Z Suspension set-3 WH (ceiling rose suspension kit) | -   | -            | -           | -         | 911401805681 | 36592399 |

### Ledinaire recessed and Ledinaire surface-mounted



#### Features

- Square and rectangular versions available
- Recessed and surface-mounted versions
- 3000K & 4000K versions
- 3400 lm light output

#### Benefits

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light



50000h  
at L65



1 PACK

| Product Type                      | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-----------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                   | W   | lm           | K           |           |              |          |
| RC060B LED34S/840 PSU W60L60 NOC  | 34  | 3400         | 4000        | IP20      | 911401850780 | 06958500 |
| SM060C LED34S/840 PSU W20L120 NOC |     | 3400         | 4000        | IP20      | 911401850680 | 06962200 |
| SM060C LED34S/840 PSU W20L120 OC  |     | 3400         | 4000        | IP20      | 911401842280 | 35039400 |
| SM060C LED32S/830 PSU W20L120     | 36  | 3200         | 3000        | IP20      | 910503910207 | 06963900 |

# Ledinaire

## Ledinaire recessed and Ledinaire surface-mounted – Continued




### Features

- Square and rectangular versions available
- Recessed and surface-mounted versions
- 3000K & 4000K versions
- 3400 lm light output

### Benefits

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light



50000h  
at L65



1 PACK

| Product Type                                                          | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-----------------------------------------------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                                                       | W   | lm           | K           |           |              |          |
| RC060B LED40S/840 PSU W60L60 NOC                                      | 40  | 4000         | 4000        | IP20      | 911401842380 | 35040000 |
| SM060C LED40S/840 PSU W20L120 NOC                                     |     | 4000         | 4000        | IP20      | 911401842480 | 35041700 |
| RC060B/SM060C LED32S EM PACK ELB3                                     | -   | -            | -           | -         | 919913999632 | 62949400 |
| Emergency pack for Ledinaire Recessed RC060B & Surface Mounted SM060C | -   | -            | -           | -         | 919913999632 | 62949400 |

## Ledinaire wall-mounted



**Features**

- 1100 lm & 1700 lm light output
- 3000K & 4000K versions
- Possibility for through wiring
- Optional motion detection and daylight sensor.

**Benefits**

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light
- Easy to install

  
50000h  
at L65

  
1 PACK

| Product Type                         | LED  | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|--------------------------------------|------|--------------|-------------|-----------|--------------|----------|
|                                      | W    | lm           | K           |           |              |          |
| WL060V LED11S/830 PSU II WH          | 12   | 1100         | 3000        | IP44      | 911401802080 | 33909299 |
| WL060V LED11S/840 PSU II WH          |      | 1100         | 4000        | IP44      | 911401802180 | 33910899 |
| WL060V LED17S/830 PSU II WH          | 18.5 | 1700         | 3000        | IP44      | 911401802280 | 33911599 |
| WL060V LED17S/830 PSU II WH ELB3     |      | 1700         | 3000        | IP44      | 919013004303 | 63417700 |
| WL060V LED17S/840 PSU II WH          |      | 1700         | 4000        | IP44      | 911401802380 | 33912299 |
| WL060V LED17S/840 PSU II WH ELB3     |      | 1700         | 3000        | IP44      | 919013004304 | 63418400 |
| WL060V LED17S/830 PSU MDU II WH      | 19.5 | 1700         | 3000        | IP44      | 911401802480 | 33913999 |
| WL060V LED17S/830 PSU MDU II WH ELB3 |      | 1700         | 4000        | IP44      | 919013004305 | 63419100 |
| WL060V LED17S/840 PSU MDU II WH      |      | 1700         | 4000        | IP44      | 911401802580 | 33914699 |
| WL060V LED17S/840 PSU MDU II WH ELB3 |      | 1700         | 4000        | IP44      | 919013004306 | 63420700 |

## Ledinaire downlight DN060B



**Features**

- 800 lm & 1800 lm light output
- 3000K & 4000K versions
- Modern, unobtrusive design

**Benefits**

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light


  
50000h  
at L65
 
  
1 PACK

| Product Type               | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|----------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                            | W   | lm           | K           |           |              |          |
| DN060B LED8S/830 PSU WH    | 9   | 800          | 3000        | IP20      | 911401532031 | 30662999 |
| DN060B LED8S/840 PSU WH    |     | 800          | 4000        | IP20      | 911401532231 | 30664399 |
| DN060B LED18S/830 PSU WH   | 18  | 1800         | 3000        | IP20      | 911401531931 | 30661299 |
| DN060B LED18S/840 PSU WH   |     | 1800         | 4000        | IP20      | 911401532131 | 30663699 |
| DN060B LED18S EM PACK ELB3 | -   | -            | -           | -         | 919913999631 | 62948700 |
| DN060B LED8S EM PACK ELB3  | -   | -            | -           | -         | 919913999630 | 62947000 |

## Ledinaire downlight DN029B



### Features

- 800lm, 1200lm, 2000lm light output
- Deep CCT switch
- Modern, unobtrusive design

### Benefits

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light



50000h  
at L65



1 PACK

| Product Type                            | LED | Lumen Output | Colour Temp         | IP rating | 12NC         | EOC code |
|-----------------------------------------|-----|--------------|---------------------|-----------|--------------|----------|
|                                         | W   | lm           | K                   |           |              |          |
| 2 DN029B LED8/CCT 8W 220-240V D90 EU    | 8.5 | 800          | 3000, 4300 and 6500 | IP44      | 929002066119 | 66018500 |
| 2 DN029B LED12/CCT 14W 220-240V D150 EU | 14  | 1200         | 3000, 4300 and 6500 | IP44      | 929002066219 | 66020800 |
| 1 DN029B LED20/CCT 24W 220-240V D200 EU | 24  | 2000         | 3000, 4300 and 6500 | IP44      | 929002066319 | 66022200 |

Ledinaire

Ledinaire SlimDownlight



Features

- WH White or ALU Aluminium finish available
- 2700K, 3000K & 4000K versions
- Kits with different LED lamps available

Benefits

- Philips quality and reliability
- Energy saving
- Replaceable LED lamps
- High performance dimming
- Superior light quality with CRI90



50000h  
at L65



1 PACK

| Product Type                            | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-----------------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                         | W   | lm           | K           |           |              |          |
| DN065B G2 LED10/830 11W 220V D150 RD EU | 11  | 950          | 3000        | IP20      | 929002220432 | 67939200 |
| DN065B G2 LED10/840 11W 220V D150 RD EU |     | 1000         | 4000        | IP20      | 929002220532 | 67941500 |
| DN065B G2 LED19/830 22W 220V D200 RD EU | 22  | 1900         | 3000        | IP20      | 929002220632 | 67943900 |
| DN065B G2 LED20/840 22W 220V D200 RD EU |     | 2000         | 4000        | IP20      | 929002220732 | 67945300 |

Ledinaire Zadora



Features

- WH White or ALU Aluminium finish available
- 2700K, 3000K & 4000K versions
- Kits with different LED lamps available

Benefits

- Philips quality and reliability
- Energy saving
- Replaceable LED lamps
- High performance dimming
- Superior light quality with CRI90



50000h  
at L65



1 PACK

| Product Type                          | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|---------------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                       | W   | lm           | K           |           |              |          |
| RS049B LED-MS-40-5W-2700-GU10 ALU 50W | 5   | 355          | 2700        | IP20      | 912401483106 | 07014799 |
| RS049B LED-MS-40-5W-3000-GU10 WH 50W  |     | 365          | 3000        | IP20      | 912401483107 | 07015499 |
| RS049B LED-MS-40-5W-3000-GU10 WH 50W  |     | 375          | 3000        | IP20      | 910503910195 | 07015499 |

Ledinaire ClearAccent



1



2

Features

- Fixed and adjustable versions available
- 3000K & 4000K versions
- 500 lm light output
- Modern, unobtrusive design

Benefits

- Philips quality and reliability
- Energy saving
- Facetted reflector look and feel
- Easy installation with driver on-board



50000h  
at L65



1 PACK

| Product Type                    | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|---------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                 | W   | lm           | K           |           |              |          |
| 1 RS060B LED5-36-/830 PSR II WH | 6   | 500          | 3000        | IP20      | 910503910182 | 07267799 |
| 1 RS060B LED5-36-/840 PSR II WH |     | 500          | 4000        | IP20      | 910503910183 | 07268499 |
| 2 RS061B LED5-36-/830 PSR II WH |     | 500          | 3000        | IP20      | 910503910184 | 07269199 |
| 2 RS061B LED5-36-/840 PSR II WH |     | 500          | 4000        | IP20      | 910503910185 | 07270799 |

Ledinaire waterproof



Features

- Robust and waterproof luminaire, new slim design
- New 6ft version available (8400lm)
- Mounting bracket can be positioned over full length
- Through-wiring versions available
- Increased efficiency to up to 120lm/W

Benefits

- Low height design with less dust accumulation
- New connector for easy installation
- Diff use comfortable light
- Philips quality and reliability



50000h  
at L65



4/9 PACK

| Product Type                         | LED  | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|--------------------------------------|------|--------------|-------------|-----------|--------------|----------|
|                                      | W    | lm           | K           |           |              |          |
| NEW WT065C LED24S/840 PSU L1200      | 20   | 2400         | 4000        | IP65      | 911401825281 | 36951899 |
| NEW WT065C LED24S/840 PSU L1200 ELB3 | 23   | 2400         | 4000        | IP65      | 919013004422 | 56635365 |
| NEW WT065C LED48S/840 PSU L1200      | 43.5 | 4800         | 4000        | IP65      | 911401825381 | 36952599 |
| NEW WT065C LED48S/840 PSU L1200 ELB3 | 46.5 | 4800         | 4000        | IP65      | 919013004423 | 56635372 |
| NEW WT065C LED35S/840 PSU L1500      | 28   | 3500         | 4000        | IP65      | 911401825481 | 36953299 |
| NEW WT065C LED35S/840 PSU L1500 ELB3 | 31   | 3500         | 4000        | IP65      | 919013004424 | 56635389 |
| NEW WT065C LED68S/840 PSU L1500      | 55   | 6800         | 4000        | IP65      | 911401825581 | 36954999 |
| NEW WT065C LED68S/840 PSU L1500 ELB3 | 58   | 6800         | 4000        | IP65      | 919013004425 | 56635396 |
| NEW WT065C LED44S/840 PSU L1800      | 44   | 4400         | 4000        | IP65      | 911401825681 | 36955699 |
| NEW WT065C LED44S/840 PSU L1800 ELB3 | 47   | 4400         | 4000        | IP65      | 919013004426 | 56635402 |
| NEW WT065C LED84S/840 PSU L1800      | 65   | 8400         | 4000        | IP65      | 911401825781 | 36956399 |
| NEW WT065C LED84S/840 PSU L1800 ELB3 | 68   | 8400         | 4000        | IP65      | 919013004427 | 56635419 |

Ledinaire

Ledinaire FloodLight Mini



Features

- Available with or without motion sensor
- 10W/20W/50W
- IP65
- IK07
- Symmetrical beam

- 50,000 hours at L70
- Prewired connection
- Remote control included in the MDU versions

Benefits

- Good quality finishing and design
- Reliable driver, less early failures
- Light output to meet standard applications
- Easy to install, supplied with stripped cable



50000h at L70



1 PACK

| Product Type                                            | LED | Lumen Output | Colour Temp | Motion/Daylight sensor     | IP rating | 12NC         | EOC code |
|---------------------------------------------------------|-----|--------------|-------------|----------------------------|-----------|--------------|----------|
|                                                         | W   | lm           | K           |                            |           |              |          |
| 1 BVP154 LED10/830 PSU 10W VWB CE                       | 10  | 1050         | 3000        | -                          | IP65      | 911401730422 | 32970399 |
| 2 BVP154 LED10/830 PSU 10W VWB Motion Detection Unit CE |     | 1050         | 3000        | motion and daylight sensor | IP65      | 911401733332 | 33131799 |
| 1 BVP154 LED10/840 PSU 10W VWB CE                       |     | 1050         | 4000        | -                          | IP65      | 911401730432 | 32971099 |
| 2 BVP154 LED10/840 PSU 10W VWB Motion Detection Unit CE |     | 1050         | 4000        | motion and daylight sensor | IP65      | 911401733342 | 33132499 |
| 3 BVP154 LED20/830 PSU 20W VWB CE                       | 20  | 2100         | 3000        | -                          | IP65      | 911401730442 | 32972799 |
| 2 BVP154 LED20/830 PSU 20W VWB Motion Detection Unit CE |     | 2100         | 3000        | motion and daylight sensor | IP65      | 911401733352 | 33133199 |
| 3 BVP154 LED21/840 PSU 20W VWB CE                       |     | 2100         | 4000        | -                          | IP65      | 911401730452 | 32973499 |
| 2 BVP154 LED21/840 PSU 20W VWB Motion Detection Unit CE |     | 2100         | 4000        | motion and daylight sensor | IP65      | 911401733362 | 33134899 |
| 3 BVP154 LED50/830 PSU 50W VWB CE                       | 50  | 5250         | 3000        | -                          | IP65      | 911401730462 | 32974199 |
| 4 BVP154 LED50/830 PSU 50W VWB Motion Detection Unit CE |     | 5250         | 3000        | motion and daylight sensor | IP65      | 911401733372 | 33135599 |
| 5 BVP154 LED52/840 PSU 50W VWB CE                       |     | 5250         | 4000        | -                          | IP65      | 911401730472 | 32975899 |
| 4 BVP154 LED52/840 PSU 50W VWB Motion Detection Unit CE |     | 5250         | 4000        | motion and daylight sensor | IP65      | 911401733382 | 33136299 |

Ledinaire FloodLight Maxi



Features

- Available with motion sensor
- 100W/150W/200W
- IP65
- IK08
- Assymetrical and symetrical beam options
- 50,000 hours at L70
- Prewired connection

Benefits

- Good quality finishing and design
- Reliable driver, less early failures
- Light output to meet standard applications
- Easy to install, supplied with stripped cable



50000h at L70



1 PACK

| Product Type                        | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-------------------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                                     | W   | lm           | K           |           |              |          |
| 1 BVP155 LED100/840 PSU 100W AWB CE | 100 | 10000        | 4000        | IP65      | 911401733302 | 33128799 |
| 1 BVP155 LED105/840 PSU 100W VWB CE |     | 10500        | 4000        | IP65      | 911401733272 | 33125699 |
| 2 BVP155 LED150/840 PSU 150W AWB CE | 150 | 15000        | 4000        | IP65      | 911401733312 | 33129499 |
| 2 BVP155 LED157/840 PSU 150W VWB CE |     | 15750        | 4000        | IP65      | 911401733282 | 33126399 |
| 3 BVP155 LED200/840 PSU 200W AWB CE | 200 | 20000        | 4000        | IP65      | 911401733322 | 33130099 |
| 3 BVP155 LED210/840 PSU 200W VWB CE |     | 21000        | 4000        | IP65      | 911401733292 | 33127099 |

Ledinaire batten



Features

- BESA fixing
- Multiple lengths and light levels available (up to 8000lm and 6ft)
- Integral Emergency versions available, Philips quality driver

Benefits

- Easy to install and connect thanks to retainer cables and push-in connectors
- Possible through-wiring for flexibility in the installation thanks to: knock-out holes on both sides and loop-in loop-out terminal



50000h at L65



6/8 PACK

| Product Type                             | LED  | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|------------------------------------------|------|--------------|-------------|-----------|--------------|----------|
|                                          | W    | lm           | K           |           |              |          |
| NEW BN065C LED25S/840 PSU L1200 UKI      | 22.5 | 2500         | 4000        | IP20      | 911401825881 | 36963199 |
| NEW BN065C LED25S/840 PSU L1200 UKI ELB3 | 25.5 | 2500         | 4000        | IP20      | 919013004428 | 56635426 |
| NEW BN065C LED35S/840 PSU L1500 UKI      | 32   | 3500         | 4000        | IP20      | 911401826081 | 36965599 |
| NEW BN065C LED35S/840 PSU L1500 UKI ELB3 | 35   | 3500         | 4000        | IP20      | 919013004430 | 56635440 |
| NEW BN065C LED43S/840 PSU L1800 UKI      | 39   | 4300         | 4000        | IP20      | 911401826281 | 36967999 |
| NEW BN065C LED43S/840 PSU L1800 UKI ELB3 | 42   | 4300         | 4000        | IP20      | 919013004432 | 56635464 |
| NEW BN065C LED52S/840 PSU L1200 UKI      | 47   | 5200         | 4000        | IP20      | 911401825981 | 36964899 |
| NEW BN065C LED52S/840 PSU L1200 UKI ELB3 | 50   | 5200         | 4000        | IP20      | 919013004429 | 56635433 |
| NEW BN065C LED60S/840 PSU L1500 UKI      | 55   | 6000         | 4000        | IP20      | 911401826181 | 36966299 |
| NEW BN065C LED60S/840 PSU L1500 UKI ELB3 | 58   | 6000         | 4000        | IP20      | 919013004431 | 56635457 |
| NEW BN065C LED80S/840 PSU L1800 UKI      | 73   | 8000         | 4000        | IP20      | 911401826381 | 36968699 |
| NEW BN065C LED80S/840 PSU L1800 UKI ELB3 | 76   | 8000         | 4000        | IP20      | 919013004433 | 56635471 |

Ledinaire

Ledinaire Cove Lighting Batten



Features

- LEDtube-based 1600 & 3200 lm
- Light line up to ten battens for LEDtube version
- Mounting accessories included

Benefits

- Trusted performance, low early failures
- LEDtube versions for easy replacement of light sources



50000h  
at L65



1 PACK

| Product Type                | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-----------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                             | W   | lm           | K           |           |              |          |
| 1 BN013C LED5S/830 L300     | 5   | 475          | 3000        | IP20      | 911401835880 | 34953499 |
| 1 BN013C LED5S/840 L300     |     | 500          | 4000        | IP20      | 911401835780 | 34952799 |
| 1 BN013C LED10S/830 L600    | 10  | 940          | 3000        | IP20      | 911401836080 | 34955899 |
| 1 BN013C LED10S/840 L600    |     | 1000         | 4000        | IP20      | 911401835980 | 34954199 |
| 1 BN013C LED14S/830 L900    | 15  | 1410         | 3000        | IP20      | 911401836280 | 34957299 |
| 1 BN013C LED15S/840 L900    |     | 1500         | 4000        | IP20      | 911401836180 | 34956599 |
| 2 BN060C 1xTLED16/840 L1200 | 18  | 1600         | 4000        | IP20      | 910503910118 | 07007999 |
| 1 BN013C LED19S/830 L1200   | 20  | 1880         | 3000        | IP20      | 911401836480 | 34959699 |
| 1 BN013C LED20S/840 L1200   |     | 2000         | 4000        | IP20      | 911401836380 | 34958999 |
| 1 BN013C LED24S/830 L1500   | 24  | 2350         | 3000        | IP20      | 911401836680 | 34961999 |
| 1 BN013C LED25S/840 L1500   |     | 2500         | 4000        | IP20      | 911401836580 | 34960299 |
| 2 BN060C 2xTLED16/840 L1200 | 36  | 3200         | 4000        | IP20      | 910503910119 | 07009399 |

Ledinaire Pentura mini LED



Features

- Ultra-slim LED batten
- Available in 300, 600, 900 and 1200 mm lengths
- 3000K & 4000K versions
- Non-trunkable version with on/off switch available.

Benefits

- Philips quality and reliability
- Energy saving
- Compact design



50000h  
at L65



1 PACK

| Product Type                | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code |
|-----------------------------|-----|--------------|-------------|-----------|--------------|----------|
|                             | W   | lm           | K           |           |              |          |
| BN132C LED3S/830 PSU L300   | 4   | 350          | 3000        | IP40      | 910503910163 | 07250999 |
| BN132C LED3S/840 PSU L300   |     | 350          | 4000        | IP40      | 910503910162 | 07249399 |
| BN132C LED6S/830 PSU L600   | 7   | 650          | 3000        | IP40      | 910503910161 | 07248699 |
| BN132C LED6S/840 PSU L600   |     | 650          | 4000        | IP40      | 910503910160 | 07247999 |
| BN132C LED9S/830 PSU L900   | 10  | 950          | 3000        | IP40      | 910503910159 | 07246299 |
| BN132C LED9S/840 PSU L900   |     | 950          | 4000        | IP40      | 910503910158 | 07245599 |
| BN132C LED12S/830 PSU L1200 | 14  | 1250         | 3000        | IP40      | 910503910157 | 07244899 |
| BN132C LED12S/840 PSU L1200 |     | 1250         | 4000        | IP40      | 910503910156 | 07243199 |

Ledinaire highbay



Features

- Modern, unobtrusive design
- Two lumen packages and sizes; 10,000lm with 24cm diameter, 20,000lm with 34cm diameter
- The IP65 rating is perfect for any application
- Including IP65 connector

- Single suspension with installation hook (included) or pipe mounting(not included)
- Optional reflector accessory for medium beam
- Non-dimming with driver on board

Benefits

- Philips quality and reliability
- Energy savings
- Wide application coverage



50000h  
at L65



1 PACK

| Product Type                 | LED | Lumen Output | Colour Temp | IP rating | 12NC         | EOC code  |
|------------------------------|-----|--------------|-------------|-----------|--------------|-----------|
|                              | W   | lm           | K           |           |              |           |
| BY020P LED100S/840 PSU WB GR | 97  | 10000        | 4000        | IP65      | 911401599651 | 333996299 |
| BY021P LED200S/840 PSU WB GR | 190 | 20000        | 4000        | IP65      | 911401599751 | 333998699 |
| BY020Z AC (reflector)        |     |              |             |           | 911401597351 | 333992499 |
| BY021Z AC (reflector)        |     |              |             |           | 911401597451 | 333994899 |

# Create the perfect ambience for every space

MASTER LEDspot ExpertColour features a light spectrum similar to halogens, for a true colour experience.

## MASTER LEDspot ExpertColour




Customised light spectrum  
similar to halogen



**CRI  
97**

Best-in-class  
colour realisation,  
CRI97



Energy savings  
up to 85%\*



Deep and smooth  
dimming, below 5%



40,000 hours  
lifetime

\* Compared to halogen lamps



## Designed to be seen

Today our work spaces need to fulfil multiple functions. We produce, meet, present, sell and require our lighting to be adaptable to meet every need and mood. There is a growing demand for lighting to be decorative and stylish; it needs to be designed to be seen. The Philips Deco collections are highly stylish giant filament LED lamps, designed to make a statement and accentuate your customer's office or shop interior, or to complement the style in a hotel, bar or restaurant. Complement multiple design preferences with Philips unique filament designs.

### Deco LED Vintage Giant

Accentuates a traditional  
warm & cosy vintage  
atmosphere.

### Deco LED Modern Giant

Modern, a bright and  
sleek, fresh, forward  
design.

## Easy to upgrade, simple to install

Both collections get the most out of classic designs, so you're able to select the perfect shape, from a choice of 'Globe', 'Teardrop' or 'Tubular' shaped lamps. Dimmable and non-dimmable.

LED lamps and tubes

LED lamps save you up to 69% energy and offer the same light quality as conventional lamps. Philips MASTER LED lamps provide you with constant colours, high performance and maximum dimming compatibility. CorePro lamps are good for energy savings of up to 69% and have a lifespan of 30,000 hours. The complete range of Philips LED lamps is designed as a 1-on-1 replacement for currently installed conventional lighting.

LEDspot MV GU10

lighting.philips.co.uk/prof/led-lamps-and-tubes



1  
MASTER LEDspot ExpertColour MV



2  
MASTER LEDspot Value



3  
MASTER LEDspot VLE



4  
CorePro LEDspot GU10 Dimmable



5  
CorePro LEDspot GU10



= Dimmable



= Non-dimmable



= DimTone



GU10



10 PACK

| Product Type                             | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                          | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDspot MV ExpertColor 25D      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LED ExpertColor 3.9-35W GU10 927 25D | 35          | 3.9 | 265          | 68       | 25         |    | 97  | 2700        | 40000    | A+  | 929001346402 | 96707494 |
| MAS LED ExpertColor 3.9-35W GU10 930 25D |             | 3.9 | 280          | 71       | 25         |    | 97  | 3000        | 40000    | A+  | 929001346502 | 96707517 |
| MAS LED ExpertColor 3.9-35W GU10 940 25D |             | 3.9 | 300          | 76       | 25         |    | 97  | 4000        | 40000    | A+  | 929001346602 | 96707531 |
| MAS LED ExpertColor 5.5-50W GU10 927 25D | 50          | 5.5 | 355          | 65       | 25         |    | 97  | 2700        | 40000    | A+  | 929001347002 | 96707616 |
| MAS LED ExpertColor 5.5-50W GU10 930 25D |             | 5.5 | 375          | 68       | 25         |    | 97  | 3000        | 40000    | A+  | 929001347102 | 96707630 |
| MAS LED ExpertColor 5.5-50W GU10 940 25D |             | 5.5 | 400          | 72       | 25         |    | 97  | 4000        | 40000    | A+  | 929001347202 | 96707654 |
| 1 MASTER LEDspot MV ExpertColor 36D      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LED ExpertColor 3.9-35W GU10 927 36D | 35          | 3.9 | 265          | 68       | 36         |    | 97  | 2700        | 40000    | A+  | 929001346702 | 96707555 |
| MAS LED ExpertColor 3.9-35W GU10 930 36D |             | 3.9 | 280          | 71       | 36         |    | 97  | 3000        | 40000    | A+  | 929001346802 | 96707579 |
| MAS LED ExpertColor 3.9-35W GU10 940 36D |             | 3.9 | 300          | 76       | 36         |    | 97  | 4000        | 40000    | A+  | 929001346902 | 96707593 |
| MAS LED ExpertColor 5.5-50W GU10 927 36D | 50          | 5.5 | 355          | 65       | 36         |    | 97  | 2700        | 40000    | A+  | 929001347302 | 96707678 |
| MAS LED ExpertColor 5.5-50W GU10 930 36D |             | 5.5 | 375          | 68       | 36         |    | 97  | 3000        | 40000    | A+  | 929001347402 | 96707692 |
| MAS LED ExpertColor 5.5-50W GU10 940 36D |             | 5.5 | 400          | 72       | 36         |    | 97  | 4000        | 40000    | A+  | 929001347502 | 96707715 |
| 2 MASTER LEDspot MV Value 36D            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE DT 3.7-35W GU10 927 36D  | 35          | 3.7 | 260          | 78       | 36         |  | 90  | 2200-2700   | 25000    | A+  | 929001350002 | 96708095 |
| MAS LEDspot VLE D 3.7-35W GU10 927 36D   |             | 3.7 | 260          | 78       | 36         |  | 90  | 2700        | 25000    | A+  | 929001348202 | 96707739 |
| MAS LEDspot VLE D 3.7-35W GU10 930 36D   |             | 3.7 | 270          | 81       | 36         |  | 90  | 3000        | 25000    | A+  | 929001348302 | 96707753 |
| MAS LEDspot VLE D 3.7-35W GU10 940 36D   | 50          | 3.7 | 285          | 85       | 36         |  | 90  | 4000        | 25000    | A++ | 929001348402 | 96707777 |
| MAS LEDspot VLE DT 4.9-50W GU10 927 36D  |             | 4.9 | 355          | 81       | 36         |  | 90  | 2200-2700   | 25000    | A+  | 929001350302 | 96708118 |
| MAS LEDspot VLE D 4.9-50W GU10 927 36D   |             | 4.9 | 355          | 81       | 36         |  | 90  | 2700        | 25000    | A+  | 929001348802 | 96707852 |
| MAS LEDspot VLE D 4.9-50W GU10 930 36D   |             | 4.9 | 365          | 83       | 36         |  | 90  | 3000        | 25000    | A+  | 929001348902 | 96707876 |
| MAS LEDspot VLE D 4.9-50W GU10 940 36D   |             | 4.9 | 380          | 86       | 36         |  | 90  | 4000        | 25000    | A+  | 929001349002 | 96707890 |
| 2 MASTER LEDspot MV Value 60D            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE D 3.7-35W GU10 927 60D   | 35          | 3.7 | 285          | 78       | 60         |  | 90  | 2700        | 25000    | A+  | 929001348502 | 96707791 |
| MAS LEDspot VLE D 3.7-35W GU10 930 60D   |             | 3.7 | 300          | 81       | 60         |  | 90  | 3000        | 25000    | A+  | 929001348602 | 96707814 |

The current dimmer list for high-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

LEDspot MV GU10 – Continued



1  
MASTER LEDspot ExpertColour MV



2  
MASTER LEDspot Value



3  
MASTER LEDspot VLE



4  
CorePro LEDspot GU10 Dimmable



5  
CorePro LEDspot GU10



= Dimmable



= Non-dimmable



= DimTone



GU10



10 PACK

| Product Type                              | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                           | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 2 MASTER LEDspot MV Value 60D             |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE D 3.7-35W GU10 940 60D    | 35          | 3.7 | 315          | 85       | 60         |    | 90  | 4000        | 25000    | A++ | 929001348702 | 96707838 |
| MAS LEDspot VLE D 4.9-50W GU10 927 60D    | 50          | 4.9 | 392          | 81       | 60         |    | 90  | 2700        | 25000    | A+  | 929001349102 | 96707913 |
| MAS LEDspot VLE D 4.9-50W GU10 930 60D    |             | 4.9 | 402          | 83       | 60         |    | 90  | 3000        | 25000    | A+  | 929001349202 | 96707937 |
| MAS LEDspot VLE D 4.9-50W GU10 940 60D    |             | 4.9 | 417          | 86       | 60         |    | 90  | 4000        | 25000    | A+  | 929001349302 | 96707951 |
| 3 MASTER LEDspot MV Value High Lumen      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE D 6.2-80W GU10 927 36D    | 80          | 6.2 | 650          | 92       | 36         |    | 90  | 2700        | 25000    | A++ | 929002059502 | 99675417 |
| MAS LEDspot VLE D 6.2-80W GU10 930 36D    |             | 6.2 | 650          | 92       | 36         |    | 90  | 3000        | 25000    | A++ | 929002068402 | 96707975 |
| MAS LEDspot VLE D 6.2-80W GU10 940 36D    |             | 6.2 | 680          | 92       | 36         |    | 90  | 4000        | 25000    | A++ | 929002066002 | 96707999 |
| MAS LEDspot VLE D 6.2-80W GU10 965 36D    |             | 6.2 | 680          | 92       | 36         |    | 90  | 6500        | 25000    | A++ | 929002209902 | 96708019 |
| 3 MASTER LEDspot MV Value High Lumen 120D |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE D 650lm GU10 930 120D     | -           | 6.2 | 650          | 104      | 120        |    | 90  | 3000        | 25000    | A+  | 929002210002 | 96724316 |
| MAS LEDspot VLE D 680lm GU10 940 120D     | -           | 6.2 | 680          | 109      | 120        |    | 90  | 4000        | 25000    | A+  | 929002210102 | 96724330 |
| MAS LEDspot VLE D 680lm GU10 965 120D     | -           | 6.2 | 680          | 109      | 120        |    | 90  | 6500        | 25000    | A+  | 929002210202 | 96724354 |
| 4 CorePro LEDspot MV Dimmable             |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LEDspot 4-35W GU10 827 36D DIM    | 35          | 4   | 250          | 62       | 36         |    | 80  | 2700        | 15000    | A+  | 929001218632 | 96721339 |
| CorePro LEDspot 4-35W GU10 830 36D DIM    |             | 4   | 260          | 65       | 36         |    | 80  | 3000        | 15000    | A+  | 929001363902 | 96721353 |
| CorePro LEDspot 4-35W GU10 840 36D DIM    |             | 4   | 270          | 67       | 36         |    | 80  | 4000        | 15000    | A+  | 929001364002 | 96730225 |
| CorePro LEDspot 5-50W GU10 827 36D DIM    | 50          | 5   | 350          | 70       | 36         |   | 80  | 2700        | 15000    | A+  | 929001218832 | 96721377 |
| CorePro LEDspot 5-50W GU10 830 36D DIM    |             | 5   | 365          | 73       | 36         |  | 80  | 3000        | 15000    | A+  | 929001364202 | 96721391 |
| CorePro LEDspot 5-50W GU10 840 36D DIM    |             | 5   | 380          | 76       | 36         |  | 80  | 4000        | 15000    | A+  | 929001364302 | 96730249 |
| 5 CorePro LEDspot MV Non Dimmable         |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LEDspot 3.5-35W GU10 827 36D      | 35          | 3.5 | 255          | 72       | 36         |  | 80  | 2700        | 15000    | A+  | 929001217862 | 96752531 |
| CorePro LEDspot 3.5-35W GU10 830 36D      |             | 3.5 | 265          | 75       | 36         |  | 80  | 3000        | 15000    | A++ | 929001217902 | 96728338 |
| CorePro LEDspot 3.5-35W GU10 840 36D      |             | 3.5 | 275          | 78       | 36         |  | 80  | 4000        | 15000    | A++ | 929001218002 | 96728352 |
| CorePro LEDspot 4.6-50W GU10 827 36D      | 50          | 4.6 | 355          | 77       | 36         |  | 80  | 2700        | 15000    | A+  | 929001215232 | 96752517 |
| CorePro LEDspot 4.6-50W GU10 830 36D      |             | 4.6 | 370          | 80       | 36         |  | 80  | 3000        | 15000    | A+  | 929001218102 | 96728376 |
| CorePro LEDspot 4.6-50W GU10 840 36D      |             | 4.6 | 390          | 84       | 36         |  | 80  | 4000        | 15000    | A++ | 929001218202 | 96728390 |
| CorePro LEDspot 4.6-50W GU10 865 36D      |             | 4.6 | 390          | 84       | 36         |  | 80  | 6500        | 15000    | A++ | 929001218302 | 96728413 |

The current dimmer list for high-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

LED lamps and tubes

LEDspot LV MR16

1

MASTER LEDspot  
ExpertColour

2

MASTER LEDspot  
VLE

3

CorePro LEDspot

= Dimmable

= Non-dimmable

= DimTone

GU5.3

10 PACK

| Product Type                             | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                          | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDspot LV ExpertColor 10D      |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 6.5–35W MR16 927 10D | 35          | 6.5 | 410          | 63       | 10         |          | 97  | 2700        | 40000    | A   | 929001341702 | 96738719 |
| MAS LED ExpertColor 6.5–35W MR16 930 10D |             | 6.5 | 430          | 66       | 10         |          | 97  | 3000        | 40000    | A   | 929001341802 | 96738733 |
| MAS LED ExpertColor 6.5–35W MR16 940 10D |             | 6.5 | 440          | 68       | 10         |          | 97  | 4000        | 40000    | A+  | 929001341902 | 96738757 |
| 1 MASTER LEDspot LV ExpertColor 24D      |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 6.5–35W MR16 927 24D | 35          | 6.5 | 420          | 65       | 24         |          | 97  | 2700        | 40000    | A   | 929001342002 | 96738771 |
| MAS LED ExpertColor 6.5–35W MR16 930 24D |             | 6.5 | 440          | 68       | 24         |          | 97  | 3000        | 40000    | A+  | 929001342102 | 96738795 |
| MAS LED ExpertColor 6.5–35W MR16 940 24D |             | 6.5 | 460          | 71       | 24         |          | 97  | 4000        | 40000    | A+  | 929001342202 | 96738818 |
| MAS LED ExpertColor 7.5–43W MR16 927 24D | 43          | 7.5 | 485          | 65       | 24         |          | 92  | 2700        | 40000    | A   | 929001386002 | 96735381 |
| MAS LED ExpertColor 7.5–43W MR16 930 24D |             | 7.5 | 500          | 67       | 24         |          | 92  | 3000        | 40000    | A   | 929001386102 | 96735404 |
| MAS LED ExpertColor 7.5–43W MR16 940 24D |             | 7.5 | 520          | 69       | 24         |          | 92  | 4000        | 40000    | A   | 929001386202 | 96735428 |
| 1 MASTER LEDspot LV ExpertColor 36D      |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 6.5–35W MR16 927 36D | 35          | 6.5 | 420          | 65       | 36         |          | 97  | 2700        | 40000    | A   | 929001342302 | 96738832 |
| MAS LED ExpertColor 6.5–35W MR16 930 36D |             | 6.5 | 440          | 68       | 36         |          | 97  | 3000        | 40000    | A+  | 929001342402 | 96738856 |
| MAS LED ExpertColor 6.5–35W MR16 940 36D |             | 6.5 | 460          | 71       | 36         |          | 97  | 4000        | 40000    | A+  | 929001342502 | 96738870 |
| MAS LED ExpertColor 7.5–43W MR16 927 36D | 43          | 7.5 | 485          | 65       | 36         |          | 92  | 2700        | 40000    | A   | 929001386302 | 96735442 |
| MAS LED ExpertColor 7.5–43W MR16 930 36D |             | 7.5 | 500          | 67       | 36         |          | 92  | 3000        | 40000    | A   | 929001386402 | 96735466 |
| MAS LED ExpertColor 7.5–43W MR16 940 36D |             | 7.5 | 520          | 69       | 36         |          | 92  | 4000        | 40000    | A   | 929001386502 | 96735480 |
| 1 MASTER LEDspot LV ExpertColor 60D      |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 6.5–35W MR16 927 60D | 35          | 6.5 | 400          | 62       | 60         |          | 97  | 2700        | 40000    | A   | 929001341402 | 96757512 |
| MAS LED ExpertColor 6.5–35W MR16 930 60D |             | 6.5 | 440          | 68       | 60         |          | 97  | 3000        | 40000    | A+  | 929001341502 | 96757536 |
| MAS LED ExpertColor 6.5–35W MR16 940 60D |             | 6.5 | 440          | 68       | 60         |          | 97  | 4000        | 40000    | A+  | 929001341602 | 96757550 |
| 2 MASTER LEDspot LV Value                |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspot VLE D 5.5–35W MR16 827 36D   | 35          | 5.5 | 450          | 82       | 36         |          | 80  | 2700        | 25000    | A+  | 929001325902 | 96708231 |
| MAS LEDspot VLE D 5.5–35W MR16 830 36D   |             | 5.5 | 460          | 84       | 36         |          | 80  | 3000        | 25000    | A+  | 929001326002 | 96708255 |

LEDspot LV MR16 – Continued



1

MASTER LEDspot  
ExpertColour



2

MASTER LEDspot  
VLE



3

CorePro LEDspot

 = Dimmable
   
 = Non-dimmable
   
 = DimTone

 GU5.3
   
 10 PACK

| Product Type                           | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|----------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                        | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 2 MASTER LEDspot LV Value              |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspot VLE D 5.5-35W MR16 840 36D | 35          | 5.5 | 490          | 89       | 36         |    | 80  | 4000        | 25000    | A+  | 929001326102 | 96708279 |
| MAS LEDspot VLE D 7-50W MR16 827 36D   | 50          | 7   | 621          | 88       | 36         |    | 80  | 2700        | 25000    | A+  | 929001903402 | 96815540 |
| MAS LEDspot VLE D 7-50W MR16 830 36D   |             | 7   | 630          | 90       | 36         |    | 80  | 3000        | 25000    | A+  | 929001903502 | 96815564 |
| MAS LEDspot VLE D 7-50W MR16 840 36D   |             | 7   | 660          | 94       | 36         |    | 80  | 4000        | 25000    | A+  | 929001903602 | 96815588 |
| 2 MASTER LEDspot LV DimTone            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDspotLV DimTone 5-35W MR16 36D   | 35          | 5   | 400          | 69       | 36         |    | 80  | 2200-2700   | 25000    | A+  | 929001904702 | 96815380 |
| MAS LEDspotLV DimTone 7-50W MR16 36D   | 50          | 7   | 700          | 88       | 36         |    | 80  | 2200-2700   | 25000    | A+  | 929002058902 | 99658205 |
| 3 CorePro LEDspot LV                   |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LEDspot ND 5-35W MR16 827 36D  | 35          | 5   | 345          | 69       | 36         |    | 80  | 2700        | 15000    | A+  | 929001344302 | 96710630 |
| CorePro LEDspot ND 5-35W MR16 840 36D  |             | 5   | 390          | 78       | 36         |    | 80  | 4000        | 15000    | A+  | 929001344502 | 96710654 |
| CorePro LEDspot ND 7-50W MR16 827 36D  | 50          | 7   | 621          | 88       | 36         |    | 80  | 2700        | 15000    | A+  | 929001904802 | 96814710 |
| CorePro LEDspot ND 7-50W MR16 830 36D  |             | 7   | 621          | 88       | 36         |   | 80  | 3000        | 15000    | A+  | 929001904902 | 96814772 |
| CorePro LEDspot ND 7-50W MR16 840 36D  |             | 7   | 630          | 94       | 36         |  | 80  | 4000        | 15000    | A+  | 929001905002 | 96814796 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

LED lamps and tubes

LEDspot LV AR111



| Product Type                             | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                          | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| MASTER LEDspot LV AR111 8D               |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 11-50W 927 AR111 8D  | 50          | 11  | 680          | 54       | 8          |          | 97  | 2700        | 40000    | A   | 929002238402 | 99687069 |
| MAS LED ExpertColor 11-50W 930 AR111 8D  |             | 11  | 730          | 56       | 8          |          | 97  | 3000        | 40000    | A   | 929002238502 | 99691035 |
| MASTER LEDspot LV AR111 24D              |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 11-50W 927 AR111 24D | 50          | 11  | 650          | 54       | 24         |          | 97  | 2700        | 40000    | A   | 929002238602 | 99686925 |
| MAS LED ExpertColor 11-50W 930 AR111 24D |             | 11  | 680          | 56       | 24         |          | 97  | 3000        | 40000    | A   | 929002238702 | 99691011 |
| MAS LED ExpertColor 15-75W 927 AR111 24D | 75          | 15  | 950          | 55       | 24         |          | 97  | 2700        | 40000    | A   | 929002239002 | 99686987 |
| MAS LED ExpertColor 15-75W 930 AR111 24D |             | 15  | 1000         | 56       | 24         |          | 97  | 3000        | 40000    | A   | 929002239102 | 99687007 |
| MAS LED ExpertColor 15-75W 940 AR111 24D |             | 15  | 1100         | 63       | 24         |          | 97  | 4000        | 40000    | A   | 929002239202 | 99687083 |
| MAS LEDspotLV D 20-100W 927 AR111 24D    | 100         | 20  | 1300         | 58       | 24         |          | 91  | 2700        | 25000    | A   | 929002050302 | 96515044 |
| MAS LEDspotLV D 20-100W 930 AR111 24D    |             | 20  | 1300         | 60       | 24         |          | 91  | 3000        | 25000    | A   | 929002050502 | 96707432 |
| MAS LEDspotLV D 20-100W 940 AR111 24D    |             | 20  | 1400         | 62       | 24         |          | 91  | 4000        | 25000    | A   | 929002050702 | 96725320 |
| MASTER LEDspot LV AR111 40D              |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LED ExpertColor 11-50W 927 AR111 40D | 50          | 11  | 650          | 54       | 40         |          | 97  | 2700        | 40000    | A   | 929002238802 | 99686949 |
| MAS LED ExpertColor 11-50W 930 AR111 40D |             | 11  | 680          | 56       | 40         |          | 97  | 3000        | 40000    | A   | 929002238902 | 99686963 |
| MAS LED ExpertColor 15-75W 927 AR111 40D | 75          | 15  | 950          | 56       | 40         |          | 97  | 2700        | 40000    | A   | 929002239302 | 99687021 |
| MAS LED ExpertColor 15-75W 930 AR111 40D |             | 15  | 1000         | 58       | 40         |          | 97  | 3000        | 40000    | A   | 929002239402 | 99687045 |
| MAS LED ExpertColor 15-75W 940 AR111 40D |             | 15  | 1150         | 65       | 40         |          | 97  | 4000        | 40000    | A   | 929002239502 | 99687106 |
| MAS LEDspotLV D 20-100W 927 AR111 45D    | 100         | 20  | 1300         | 58       | 45         |          | 91  | 2700        | 25000    | A   | 929002050402 | 96707456 |
| MAS LEDspotLV D 20-100W 930 AR111 45D    |             | 20  | 1300         | 60       | 45         |          | 91  | 3000        | 25000    | A   | 929002050602 | 96707470 |
| MAS LEDspotLV D 20-100W 940 AR111 45D    |             | 20  | 1400         | 62       | 45         |          | 91  | 4000        | 25000    | A   | 929002050802 | 96725344 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

LEDspot LV MR11



| Product Type                         | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                      | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 CorePro LEDspot LV MR11            |             |     |              |          |            |          |     |             |          |     |              |          |
| CorePro LEDspot 2.3-20W 827 MR11 36D | 20          | 2.3 | 200          | 80       | 36         |          | 80  | 2700        | 25000    | A++ | 929002066402 | 99659486 |
| 2 MASTER LEDspot LV MR11             |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspotLV 3.5-20W 827 MR11 24D   | 20          | 3.5 | 200          | 60       | 24         |          | 80  | 2700        | 40000    | A+  | 929001123802 | 96410196 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

# LED lamps and tubes

## LEDspot MV PAR



| Product Type                               | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                            | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDspot PAR20 25D                 |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspot CLA D 6-50W 827 PAR20 25D      | 50          | 6   | 500          | 87       | 25         |          | 80  | 2700        | 25000    | A+  | 929001317402 | 96713563 |
| MAS LEDspot CLA D 6-50W 830 PAR20 25D      |             | 6   | 515          | 89       | 25         |          | 80  | 3000        | 25000    | A+  | 929001317502 | 96713662 |
| MAS LEDspot CLA D 6-50W 840 PAR20 25D      |             | 6   | 540          | 93       | 25         |          | 80  | 4000        | 25000    | A+  | 929001317602 | 96713686 |
| MAS LEDspot CLA D 6-50W 827 PAR20 25D ■    |             | 6   | 500          | 83       | 25         |          | 80  | 2700        | 25000    | A+  | 929002338002 | 99768461 |
| MAS LEDspot CLA D 6-50W 830 PAR20 25D ■    |             | 6   | 515          | 86       | 25         |          | 80  | 3000        | 25000    | A+  | 929002338102 | 99768485 |
| MAS LEDspot CLA D 6-50W 840 PAR20 25D ■    |             | 6   | 540          | 90       | 25         |          | 80  | 4000        | 25000    | A++ | 929002338202 | 99768508 |
| 1 MASTER LEDspot PAR20 40D                 |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspot CLA D 6-50W 827 PAR20 40D      | 50          | 6   | 500          | 87       | 40         |          | 80  | 2700        | 25000    | A+  | 929001317702 | 96713709 |
| MAS LEDspot CLA D 6-50W 830 PAR20 40D      |             | 6   | 515          | 89       | 40         |          | 80  | 3000        | 25000    | A+  | 929001317802 | 96713723 |
| MAS LEDspot CLA D 6-50W 840 PAR20 40D      |             | 6   | 540          | 93       | 40         |          | 80  | 4000        | 25000    | A+  | 929001317902 | 96713747 |
| MAS LEDspot CLA D 6-50W 827 PAR20 40D ■    |             | 6   | 500          | 83       | 40         |          | 80  | 2700        | 25000    | A+  | 929002338302 | 99768522 |
| MAS LEDspot CLA D 6-50W 830 PAR20 40D ■    |             | 6   | 515          | 83       | 40         |          | 80  | 3000        | 25000    | A+  | 929002338402 | 99768546 |
| MAS LEDspot CLA D 6-50W 840 PAR20 40D ■    |             | 6   | 540          | 83       | 40         |          | 80  | 4000        | 25000    | A++ | 929002338502 | 99768560 |
| 2 MASTER LEDspot PAR30S                    |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspot CLA D 9.5-75W 827 PAR30S 25D   | 75          | 9.5 | 740          | 83       | 25         |          | 80  | 2700        | 25000    | A+  | 929001322902 | 96713808 |
| MAS LEDspot CLA D 9.5-75W 830 PAR30S 25D   |             | 9.5 | 760          | 85       | 25         |          | 80  | 3000        | 25000    | A+  | 929001342902 | 96713907 |
| MAS LEDspot CLA D 9.5-75W 840 PAR30S 25D   |             | 9.5 | 820          | 93       | 25         |          | 80  | 4000        | 25000    | A+  | 929001323002 | 96713846 |
| MAS LEDspot CLA D 9.5-75W 827 PAR30S 25D ■ |             | 9.5 | 740          | 79       | 25         |          | 80  | 2700        | 25000    | A+  | 929002338602 | 99768607 |
| MAS LEDspot CLA D 9.5-75W 830 PAR30S 25D ■ |             | 9.5 | 760          | 79       | 25         |          | 80  | 3000        | 25000    | A+  | 929002338702 | 99768621 |
| MAS LEDspot CLA D 9.5-75W 840 PAR30S 25D ■ |             | 9.5 | 820          | 79       | 25         |          | 80  | 4000        | 25000    | A+  | 929002338802 | 99768645 |
| 3 MASTER LEDspot PAR38                     |             |     |              |          |            |          |     |             |          |     |              |          |
| MAS LEDspot CLA ND 9-60W 827 PAR38 25D     | 60          | 9   | 750          | 89       | 25         |          | 80  | 2700        | 15000    | A+  | 929001322702 | 96714560 |
| MAS LEDspot CLA D 13-100W 827 PAR38 25D    | 100         | 13  | 875          | 77       | 25         |          | 80  | 2700        | 25000    | A+  | 929001322502 | 96713761 |
| MAS LEDspot CLA D 13-100W 827 PAR38 25D ■  |             | 13  | 1000         | 77       | 25         |          | 80  | 2700        | 25000    | A+  | 929002339002 | 99768706 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

■ Expected September 2020

## CorePro LEDspot MV Reflectors



| Product Type                               | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                            | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 CoreProLEDspot ND1.4-25W R50 E14 827 36D | 25          | 1.4 | 125          | 75       | 36         |          | 80  | 2700        | 15000    | A++ | 929001891002 | 96811733 |
| 2 CoreProLEDspot ND1.8-30W R39 E14 827 36D | 30          | 1.8 | 190          | 83       | 36         |          | 80  | 2700        | 15000    | A++ | 929001890902 | 96811719 |
| 1 CoreProLEDspot ND2.8-40W R50 E14 827 36D | 40          | 2.8 | 255          | 75       | 36         |          | 80  | 2700        | 15000    | A++ | 929001891102 | 96811757 |
| 3 CoreProLEDspot ND 3-40W R63 E27 827 36D  |             | 3   | 255          | 70       | 36         |          | 80  | 2700        | 15000    | A+  | 929001891302 | 96811795 |
| 1 CoreProLEDspot D 4.3-60W R50 E14 827 36D | 60          | 4.3 | 390          | 74       | 36         |          | 80  | 2700        | 15000    | A+  | 929001891202 | 96811771 |
| 3 CoreProLEDspot D 4.5-60W R63 E27 827 36D |             | 4.5 | 410          | 76       | 36         |          | 80  | 2700        | 15000    | A+  | 929001891402 | 96811818 |
| 4 CoreProLEDspot ND 4-60W R80 E27 827 36D  |             | 4   | 410          | 86       | 36         |          | 80  | 2700        | 15000    | A+  | 929001891502 | 96811832 |
| 4 CoreProLEDspot ND 8-100W R80 E27 827 36D | 100         | 8   | 735          | 83       | 36         |          | 80  | 2700        | 15000    | A+  | 929001891602 | 96811856 |

## CorePro R7S



| Product Type                                | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|------|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W    | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 CorePro R7S 78mm 4-40W 830 G              | 40          | 4    | 475          | 119      | 360        |          | 80  | 3000        | 10000    | A++ | 929002327002 | 99735128 |
| 2 CorePro LEDlinear ND 7.5-60W R7S 78mm830  | 60          | 7.5  | 950          | 127      | 360        |          | 80  | 3000        | 15000    | A++ | 929001339002 | 96713945 |
| 2 CorePro LEDlinear ND 7.5-60W R7S 78mm840  |             | 7.5  | 1000         | 133      | 360        |          | 80  | 4000        | 15000    | A++ | 929001339102 | 96713969 |
| 3 CorePro R7S 118mm 8.1-60W 840 G           |             | 8.1  | 970          | 120      | 360        |          | 80  | 4000        | 10000    | A++ | 929002327302 | 99735180 |
| 3 CorePro R7S 118mm 8.1-60W 830 G           | 100         | 8.1  | 900          | 111      | 360        |          | 80  | 3000        | 10000    | A++ | 929002327202 | 99735166 |
| 4 CorePro R7S 118mm 14-100W 830 D           |             | 14   | 1600         | 114      | 360        |          | 80  | 3000        | 15000    | A+  | 929001243702 | 96578797 |
| 4 CorePro R7S 118mm 14-100W 840 D           | 120         | 14   | 1800         | 129      | 360        |          | 80  | 4000        | 15000    | A++ | 929001243802 | 96578810 |
| 4 CorePro LED linear D 14-120W R7S 118 830  |             | 14   | 2000         | 143      | 360        |          | 80  | 3000        | 15000    | A++ | 929001353602 | 96714003 |
| 4 CorePro LED linear D 14-120W R7S 118 840  | 150         | 14   | 2000         | 143      | 360        |          | 80  | 4000        | 15000    | A++ | 929001353702 | 96714065 |
| 5 CoreProLED linear D 17.5-150W R7S 118 830 |             | 17.5 | 2460         | 140      | 360        |          | 80  | 3000        | 15000    | A++ | 929002016602 | 99646738 |
| 5 CoreProLED linear D 17.5-150W R7S 118 840 |             | 17.5 | 2460         | 140      | 360        |          | 80  | 4000        | 15000    | A++ | 929002016702 | 99646752 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

■ Expected September 2020

LED lamps and tubes

CorePro LEDcapsule LV G4

1

CorePro LEDcapsuleLV  
0.9-10W G4 827

2

CorePro LEDcapsuleLV  
1-10W G4 827

3

CorePro LEDcapsuleLV  
1.7-20W G4 827

4

CorePro LEDcapsuleLV  
2-20W G4 827 D

5

CorePro LEDcapsuleLV  
1.7-20W GY6.35 827

6

CorePro LEDcapsuleLV  
1.8-20W G4 827

7

CorePro LEDcapsuleLV  
2.1-20W G4 827 D

8

CorePro LEDcapsuleLV  
1.8-20W GY6.35 827

9

CorePro LEDcapsuleLV  
2.5-28W G4 827

10

CorePro LEDcapsuleLV  
2.7-28W G4 827

= Dimmable

= Non-dimmable

G4

12 PACK

| Product Type                                | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 CorePro LEDcapsuleLV 0.9-10W G4 827       | 10          | 0.9 | 110          | 122      | 360        |          | 80  | 2700        | 15000    | A++ | 929001843902 | 96793121 |
| 2 CorePro LEDcapsuleLV 1-10W G4 827 ■       |             | 1   | 115          | 100      | 360        |          | 80  | 2700        | 15000    | A++ | 929002388802 | 99767617 |
| 3 CorePro LEDcapsuleLV 1.7-20W G4 827       | 20          | 1.7 | 205          | 120      | 360        |          | 80  | 2700        | 15000    | A++ | 929001844102 | 96793107 |
| 4 CorePro LEDcapsuleLV 2-20W G4 827 D       |             | 2   | 200          | 100      | 360        |          | 80  | 2700        | 15000    | A++ | 929001235302 | 96578650 |
| 5 CorePro LEDcapsuleLV 1.7-20W GY6.35 827   |             | 1.7 | 210          | 123      | 360        |          | 80  | 2700        | 15000    | A++ | 929001844302 | 96797679 |
| 6 CorePro LEDcapsuleLV 1.8-20W G4 827 ■     |             | 1.8 | 205          | 105      | 360        |          | 80  | 2700        | 15000    | A++ | 929002389002 | 99767655 |
| 7 CorePro LEDcapsuleLV 2.1-20W G4 827 D ■   |             | 2.1 | 210          | 83       | 360        |          | 80  | 2700        | 15000    | A++ | 929002389402 | 99767532 |
| 8 CorePro LEDcapsuleLV 1.8-20W GY6.35 827 ■ |             | 1.8 | 205          | 105      | 360        |          | 80  | 2700        | 15000    | A++ | 929002389702 | 99767792 |
| 9 CorePro LEDcapsuleLV 2.5-28W G4 827       | 28          | 2.5 | 300          | 120      | 360        |          | 80  | 2700        | 15000    | A++ | 929001896702 | 96826942 |
| 10 CorePro LEDcapsuleLV 2.7-28W G4 827 ■    |             | 2.7 | 315          | 117      | 360        |          | 80  | 2700        | 15000    | A++ | 929002389202 | 99767754 |

The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

■ Expected September 2020

CorePro LEDcapsule MV G9

1

CorePro LEDcapsule  
ND 1.9-25W G9 827

2

CorePro LEDcapsule  
2-25W ND G9 827 G

3

CorePro LEDcapsule  
MV 2.3-25W G9 827 D

4

CorePro LEDcapsule  
MV 2.6-25W G9 827 D

5

CorePro LEDcapsule  
MV 4-40W G9 827 D

6

CorePro LEDcapsule  
ND 3.2-40W G9 827

7

CorePro LEDcapsule  
3.5-40W ND G9 827 G

8

CorePro LEDcapsule  
ND 4.8-60W G9 827

= Dimmable

= Non-dimmable

12 PACK

| Product Type                              | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                           | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| 1 CorePro LEDcapsule ND 1.9-25W G9 827    | 25          | 1.9 | 204          | 107      | 360        |          | 80  | 2700        | 15000    | A++ | 929001323802 | 96713921 |
| 2 CorePro LEDcapsule 2-25W ND G9 827 G    |             | 2   | 200          | 100      | 360        |          | 80  | 2700        | 10000    | A++ | 929002326202 | 99735005 |
| 3 CorePro LEDcapsuleMV 2.3-25W G9 827 D   |             | 2.3 | 215          | 93       | 360        |          | 80  | 2700        | 15000    | A++ | 929001232002 | 96578698 |
| 4 CorePro LEDcapsuleMV 2.6-25W G9 827 D ■ |             | 2.6 | 215          | 83       | 360        |          | 80  | 2700        | 15000    | A++ | 929002389902 | 99766696 |
| 5 CorePro LEDcapsuleMV 4-40W G9 827 D ■   | 40          | 4   | 400          | 100      | 360        |          | 80  | 2700        | 15000    | A++ | 929002390002 | 99766733 |
| 6 CorePro LEDcapsule ND 3.2-40W G9 827    |             | 3.2 | 400          | 125      | 360        |          | 80  | 2700        | 15000    | A++ | 929001902902 | 96815267 |
| 7 CorePro LEDcapsule 3.5-40W ND G9 827 G  |             | 3.5 | 380          | 109      | 360        |          | 80  | 2700        | 10000    | A++ | 929002326502 | 99735067 |
| 8 CorePro LEDcapsule ND 4.8-60W G9 827    | 60          | 4.8 | 570          | 118      | 360        |          | 80  | 2700        | 15000    | A++ | 929002055102 | 99657802 |


The current transformer compatibility list and dimmer list for low-voltage LED lamps can be found on our website under Cases & Tools on: [www.philips.com/ledlamps](http://www.philips.com/ledlamps)

■ Expected September 2020

LED bulbs

Standard bulbs

Standard Bulbs



| Product Type                              | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------------|-------------|------|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                           | W           | W    | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| MASTER LEDbulb DimTone Clear              |             |      |              |          |            |          |     |             |          |     |              |          |
| 1 MAS LEDbulb DT 6~40W B22 A60 CL         | 40          | 6    | 470          | 78       | -          |          | 80  | 2200-2700   | -00      | A+  | 929001150602 | 96481301 |
| 2 MAS LEDbulb DT 6~40W E27 A60 CL         |             | 6    | 470          | 78       | -          |          | 80  | 2200-2700   | -00      | A+  | 929001150802 | 96481288 |
| 2 MAS LEDbulb DT 8.5~60W E27 A60 CL       | 60          | 8.5  | 806          | 94       | -          |          | 80  | 2200-2700   | -00      | A+  | 929001150932 | 96481325 |
| 1 MAS LEDbulb DT 8.5~60W B22 A60 CL       |             | 8.5  | 806          | 94       | -          |          | 80  | 2200-2700   | -00      | A+  | 929001150732 | 96481349 |
| MASTER LEDbulb DimTone Frosted            |             |      |              |          |            |          |     |             |          |     |              |          |
| 6 MAS LEDbulb DT 5.5~40WE27 927-922 A60FR | 40          | 5.5  | 470          | 85       | -          |          | 90  | 2200-2700   | -00      | A+  | 929001351302 | 96707098 |
| 6 MAS LEDbulb DT 9~60W E27 927-922 A60 FR | 60          | 9    | 806          | 89       | -          |          | 90  | 2200-2700   | -00      | A+  | 929001351402 | 96707111 |
| 5 MAS LEDbulb DT 11~75W A67 B22 827 FR    | 75          | 11   | 1055         | 96       | -          |          | 80  | 2200-2700   | -00      | A+  | 929001200402 | 96555538 |
| 3 MAS LEDbulb DT 12~75WE27 927-922 A67 FR |             | 12   | 1055         | 87       | -          |          | 90  | 2200-2700   | -00      | A+  | 929001868602 | 96826188 |
| 5 MAS LEDbulb DT 15~100W A67 B22 827 FR   | 100         | 15   | 1521         | 101      | -          |          | 80  | 2200-2700   | -00      | A+  | 929001200302 | 96555576 |
| 3 MASLEDbulb DT 14~100W E27 927-922 A67FR |             | 14   | 1521         | 108      | -          |          | 90  | 2200-2700   | -00      | A+  | 929002218602 | 99695644 |
| CorePro LEDbulb Dimmable                  |             |      |              |          |            |          |     |             |          |     |              |          |
| 4 CorePro LEDbulb D 5~40W A60 E27 927     | 40          | 5    | 470          | 94       | -          |          | 90  | 2700        | 15000    | A+  | 929002068902 | 99660628 |
| 9 CorePro LEDbulb D 5~40W A60 B22 927     |             | 5    | 470          | 94       | -          |          | 90  | 2700        | 15000    | A+  | 929002069002 | 99660703 |
| 4 CorePro LEDbulb D 8.5~60W A60 E27 927   | 60          | 8.5  | 806          | 94       | -          |          | 90  | 2700        | 15000    | A+  | 929002069102 | 99660642 |
| 9 CorePro LEDbulb D 8.5~60W A60 B22 927   |             | 8.5  | 806          | 94       | -          |          | 90  | 2700        | 15000    | A+  | 929002069202 | 99660727 |
| 4 CorePro LEDbulb D 10.5~75W A60 E27 927  | 75          | 10.5 | 1055         | 100      | -          |          | 90  | 2700        | 15000    | A+  | 929002069302 | 99660666 |
| 9 CorePro LEDbulb D 10.5~75W A60 B22 927  |             | 10.5 | 1055         | 100      | -          |          | 90  | 2700        | 15000    | A+  | 929002069402 | 99660741 |
| 4 CorePro LEDbulb D 13~100W A60 E27 927   | 100         | 13   | 1521         | 117      | -          |          | 90  | 2700        | 15000    | A+  | 929002069502 | 99660680 |
| 9 CorePro LEDbulb D 13~100W A60 B22 927   |             | 13   | 1521         | 117      | -          |          | 90  | 2700        | 15000    | A+  | 929002069602 | 99660765 |
| CorePro LEDbulb Non dimmable              |             |      |              |          |            |          |     |             |          |     |              |          |
| 4 CorePro LEDbulb ND 5.5~40W A60 E27 827  | 40          | 5.5  | 470          | 85       | -          |          | 80  | 2700        | 15000    | A+  | 929001234202 | 96577578 |
| 8 CorePro LEDbulb ND 5.5~40W A60 B22 827  |             | 5.5  | 470          | 85       | -          |          | 80  | 2700        | 15000    | A+  | 929001233802 | 96577653 |
| 4 CorePro LEDbulb ND 5~40W A60 E27 840    |             | 5    | 470          | 94       | -          |          | 80  | 4000        | 15000    | A+  | 929001234602 | 96577790 |

Standard Bulbs – Continued



| Product Type                                | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|------|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W    | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| CorePro LEDbulb Non dimmable                |             |      |              |          |            |          |     |             |          |     |              |          |
| 10 CorePro LEDbulb ND 8~60W A60 E27 827     | 60          | 8    | 806          | 100      | -          |          | 80  | 2700        | 15000    | A+  | 929001234302 | 96577554 |
| 8 CorePro LEDbulb ND 8~60W A60 B22 827      |             | 8    | 806          | 100      | -          |          | 80  | 2700        | 15000    | A+  | 929001233902 | 96577639 |
| 10 CorePro LEDbulb ND 7.5~60W A60 E27 840   |             | 7.5  | 806          | 107      | -          |          | 80  | 4000        | 15000    | A+  | 929001234702 | 96577776 |
| 10 CorePro LEDbulb ND 11~75W A60 E27 827    | 75          | 11   | 1055         | 95       | -          |          | 80  | 2700        | 15000    | A+  | 929001234402 | 96490761 |
| 8 CorePro LEDbulb ND 11~75W A60 B22 827     |             | 11   | 1055         | 95       | -          |          | 80  | 2700        | 15000    | A+  | 929001234002 | 96510049 |
| 10 CorePro LEDbulb ND 10~75W A60 E27 840    |             | 10   | 1055         | 105      | -          |          | 80  | 4000        | 15000    | A+  | 929001234802 | 96510322 |
| 10 CorePro LEDbulb ND 13~100W A60 E27 827   | 100         | 13   | 1521         | 117      | -          |          | 80  | 2700        | 15000    | A+  | 929001234502 | 96490747 |
| 8 CorePro LEDbulb ND 13~100W A60 B22 827    |             | 13   | 1521         | 117      | -          |          | 80  | 2700        | 15000    | A+  | 929001234102 | 96510025 |
| 10 CorePro LEDbulb ND 12.5~100W A60 E27 840 |             | 12.5 | 1521         | 121      | -          |          | 80  | 4000        | 15000    | A+  | 929001312402 | 96510308 |
| 7 CorePro LEDbulb ND 17~120WA67E27 827FR    | 120         | 17   | 2000         | 117      | -          |          | 80  | 2700        | 15000    | A+  | 929002047802 | 99662165 |
| 7 CorePro LEDbulb ND 15.5~120WA67E27 840FR  |             | 15.5 | 2000         | 129      | -          |          | 80  | 4000        | 15000    | A++ | 929002047902 | 99662189 |
| 7 CorePro LEDbulb ND 19~150WA67E27 827FR    | 150         | 19   | 2500         | 131      | -          |          | 80  | 2700        | 15000    | A++ | 929002048102 | 99662202 |
| 7 CorePro LEDbulb ND 17.5~150WA67E27 840FR  |             | 17.5 | 2500         | 142      | -          |          | 80  | 4000        | 15000    | A++ | 929002048202 | 99662226 |

Standard bulbs

## Filament bulbs

■ Expected September 2020

## Filament bulbs

Classic LEDbulb ST64 Clear 1

Classic LEDbulb ST64 GOLD 2

Classic LEDbulb ST64 CL 3

Classic LEDbulb ST64 Clear 4

Legend:

- Dimmable
- Non-dimmable
- DimTone

E27 6/10 PACK

Classic

LED bulbs

Classic LEDbulb ST64 – Continued



1

Classic LEDbulb ST64 Clear



2

Classic LEDbulb ST64 GOLD



3

Classic LEDbulb ST64 CL



4

Classic LEDbulb ST64 Clear



= Dimmable



= Non-dimmable



= DimTone



E27



6/10 PACK

| Product Type                            | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-----------------------------------------|-------------|-----|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                         | W           | W   | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| Classic LEDbulb Dimmable ST64 Gold      |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 2 CLA LEDbulb D 8-50W ST64 E27 822 GOLD | 50          | 8   | 630          | 78       | -          |  | 80  | 2200        | 15000    | A+  | 929001895902 | 96814352 |
| Classic LEDbulb Non Dimmable ST64       |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 1 CLA LEDbulb ND 7-60W E27 WW ST64 CL   | 60          | 7   | 806          | 115      | -          |  | 80  | 2700        | 15000    | A++ | 929001387602 | 96742754 |
| 4 CLA LEDbulb ND 7-60W B22 WW ST64 CL   |             | 7   | 806          | 115      | -          |  | 80  | 2700        | 15000    | A++ | 929001387702 | 96742792 |

LED Globes



1

CLA LEDbulb D  
8-50W G120  
E27 822 GOLD



2

LEDclassic  
G120 CL D



= Dimmable



= Non-dimmable



E27



2/6 PACK

| Product Type                             | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                          | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| Classic LEDglobe Dimmable Gold           |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 1 CLA LEDbulb D 8-50W G120 E27 822 GOLD  | 50          | 8   | 630          | 78       | -          |  | 80  | 2200        | 15000    | A+  | 929001896102 | 96814376 |
| Classic LEDglobe Dimmable                |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 2 CLA LEDbulb D 8-60W G93 E27 827 CL     | 60          | 8   | 806          | 100      | -          |  | 80  | 2700        | 15000    | A+  | 929001895702 | 96814314 |
| 2 CLA LEDbulb D 7.2-60W G95 E27 827 CL ■ |             | 7.2 | 806          | 90       | -          |  | 80  | 2700        | 15000    | A+  | 929002390702 | 99773359 |
| Classic LEDglobe Non Dimmable            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 2 CLA LEDbulb ND 7-60W E27 WW G93 CL     | 60          | 7   | 806          | 115      | -          |  | 80  | 2700        | 15000    | A++ | 929001387902 | 96742716 |

■ Expected September 2020

LED candles & lustres

MASTER LEDcandle



1

MASTER LEDcandle Clear E14



2

MASTER LEDcandle Clear E27



3

MASTER LEDcandle BA38



4

MAS LEDcandle DT B22 B38 CL



5

MAS LEDcandle DT B15 B38 CL



6

MAS LEDcandle DT B22 B38 CL



= Dimmable



= Non-dimmable



= DimTone



E14 | E27



10 PACK

| Product Type                            | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-----------------------------------------|-------------|-----|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                         | W           | W   | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| MASTER LEDcandle DimTone                |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 1 MAS LEDcandle DT 4-25W E14 B38 CL     | 25          | 4   | 250          | 65       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001139802 | 96453681 |
| 3 MAS LEDcandle DT 4-25W E14 BA38 CL    |             | 4   | 250          | 65       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001139902 | 96453766 |
| 4 MAS LEDcandle DT 4-25W B22 B38 CL     |             | 4   | 250          | 62       | -          |  | 80  | 2200-2700   | 15000    | A+  | 929001140202 | 96700655 |
| 1 MAS LEDcandle DT 6-40W E14 B38 CL     | 40          | 6   | 470          | 75       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001140402 | 96453506 |
| 3 MAS LEDcandle DT 6-40W E14 BA38 CL    |             | 6   | 470          | 75       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001140502 | 96453544 |
| 2 MAS LEDcandle DT 6-40W E27 B38 CL     |             | 6   | 470          | 75       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001157902 | 96474792 |
| 5 MAS LEDcandle DT 6-40W B15 B38 CL     |             | 6   | 470          | 78       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001140302 | 96556016 |
| 6 MAS LEDcandle DT 6-40W B22 B38 CL     |             | 6   | 470          | 75       | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001140802 | 96453629 |
| 1 MAS LEDcandle DT 8-60W B40 E14 827 CL | 60          | 8   | 806          | 100      | -          |  | 80  | 2200-2700   | 25000    | A+  | 929001211702 | 96555996 |

LED candles & lustres

LED Candles

Classic LEDcandle



| Product Type                                   | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                                | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| Classic LEDcandle DimTone                      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 1 CLA LEDcandle DT3.5-25W E14 CRI90 B35 CL     | 25          | 3.5 | 250          | 71       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002017902 | 99646226 |
| 1 CLA LEDcandle DT 3.2-25W E14 CRI90 B35 CL ■  |             | 3.2 | 250          | 63       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002393202 | 99770587 |
| 1 CLA LEDcandle DT6-40W E14 CRI90 B35 CL       | 40          | 6   | 470          | 78       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002018002 | 99646288 |
| 9 CLA LEDcandle DT6-40W E14 CRI90 BA35 CL      |             | 6   | 470          | 78       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002018302 | 99646349 |
| CLA LEDlustre DT4.5-40W E27 CRI90 B35 CL ■     |             | 4.5 | 470          | 78       | -          |    | 90  | 2700-2200   | 15000    | A++ | 929002393302 | 99780210 |
| 9 CLA LEDcandle DT 4.5-40W E14 CRI90 BA35 CL ■ |             | 4.5 | 470          | 78       | -          |    | 90  | 2700-2200   | 15000    | A++ | 929002393402 | 99770624 |
| Classic LEDcandle Dimmable                     |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 11 CLA LEDcandle D 2.7-25W B35 E14 827 CL      | 25          | 2.7 | 250          | 93       | -          |    | 80  | 2700        | 15000    | A++ | 929001332002 | 96709801 |
| 11 CLA LEDcandle D 5-40W B35 E14 827 CL        | 40          | 5   | 470          | 94       | -          |    | 80  | 2700        | 15000    | A+  | 929001332102 | 96709825 |
| 11 CLA LEDcandle D 4.5-40W B35 E14 827 CL ■    |             | 4.5 | 470          | 78       | -          |    | 80  | 2700        | 15000    | A++ | 929002391102 | 99773373 |
| 4 CLA LEDcandle D 5-40W BA35 E14 827 CL        |             | 5   | 470          | 94       | -          |    | 80  | 2700        | 15000    | A+  | 929001332802 | 96709962 |
| 14 CLA LEDcandle D 5-40W B35 B22 827 CL        |             | 5   | 470          | 94       | -          |    | 80  | 2700        | 15000    | A+  | 929001332202 | 96709849 |
| Classic LEDcandle Gold Dimmable                |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 7 CLA LEDcandle D 5-32W B35 E14 822 GOLD       | 32          | 5   | 350          | 70       | -          |  | 80  | 2200        | 15000    | A+  | 929001896302 | 96814390 |
| 8 CLA LEDcandle D 5-32W BA35 E14 822 GOLD      |             | 5   | 350          | 70       | -          |  | 80  | 2200        | 15000    | A+  | 929001896502 | 96814437 |
| Classic LEDcandle Non dimmable Clear           |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 2 CLA LEDcandle ND 2-25W B35 E14 827 CL        | 25          | 2   | 250          | 125      | -          |  | 80  | 2700        | 15000    | A++ | 929001238302 | 96574072 |
| 4 CLA LEDcandle ND 2-25W BA35 E14 827 CL       |             | 2   | 250          | 125      | -          |  | 80  | 2700        | 15000    | A++ | 929001238402 | 96574096 |
| 6 CLA LEDcandle ND 2-25W ST35 E14 827 CL       |             | 2   | 250          | 125      | -          |  | 80  | 2700        | 15000    | A++ | 929001238502 | 96574119 |
| 15 CLA LEDcandle ND 2-25W B35 B15 827 CL       |             | 2   | 250          | 125      | -          |  | 80  | 2700        | 15000    | A++ | 929001815502 | 96766880 |
| 16 CLA LEDcandle ND 2-25W B35 B22 827 CL       |             | 2   | 250          | 125      | -          |  | 80  | 2700        | 15000    | A++ | 929001815602 | 96766903 |
| 2 CLA LEDcandle ND 4.3-40W E14 827 B35 CL      | 40          | 4.3 | 470          | 109      | -          |  | 80  | 2700        | 15000    | A++ | 929001889702 | 96808535 |
| 15 CLA LEDcandle ND 4.3-40W B15 827 B35 CL     |             | 4.3 | 470          | 109      | -          |  | 80  | 2700        | 15000    | A++ | 929001889802 | 96808559 |
| 16 CLA LEDcandle ND 4.3-40W B22 827 B35 CL     |             | 4.3 | 470          | 109      | -          |  | 80  | 2700        | 15000    | A++ | 929001889902 | 96808573 |

■ Expected September 2020

Classic LEDcandle – Continued



| Product Type                                | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable     | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|-----|--------------|----------|------------|--------------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W   | lm           | lm/W     | °          |              |     | K           | Hrs.     |     |              |          |
| Classic LEDcandle Non dimmable Clear        |             |     |              |          |            |              |     |             |          |     |              |          |
| 2 CLA LEDcandle ND 6.5-60W B35 E14 827 CL   | 60          | 6.5 | 806          | 124      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929002028002 | 99649128 |
| Classic LEDcandle Non dimmable Frosted      |             |     |              |          |            |              |     |             |          |     |              |          |
| 3 CLA LEDcandle ND 2.2-25W B35 E14 FR       | 25          | 2.2 | 250          | 113      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929001345202 | 96706374 |
| 5 CLA LEDcandle ND 2.2-25W BA35 E14 FR      |             | 2.2 | 250          | 113      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929001345802 | 96706497 |
| 3 CLA LEDcandle ND 4.3-40W E14 827 B35 FR   | 40          | 4.3 | 470          | 109      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929001345302 | 96706398 |
| 5 CLA LEDcandle ND 6.5-60W B35 E14 827 FR   | 60          | 6.5 | 806          | 124      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929002028202 | 99649227 |
| CorePro LEDcandle Non dimmable Clear        |             |     |              |          |            |              |     |             |          |     |              |          |
| 12 Corepro candle ND 4-25W E14 827 B35 CL   | 25          | 4   | 250          | 63       | -          | Non-dimmable | 80  | 2700        | 15000    | A+  | 929001142202 | 96507575 |
| 12 Corepro candle ND 5.5-40W E14 827 B35 CL | 40          | 5.5 | 470          | 85       | -          | Non-dimmable | 80  | 2700        | 15000    | A+  | 929001142502 | 96454794 |
| CorePro LEDcandle Non dimmable Frosted      |             |     |              |          |            |              |     |             |          |     |              |          |
| 15 CorePro candle ND 4-25W E14 827 B35 FR   | 25          | 4   | 250          | 63       | -          | Non-dimmable | 80  | 2700        | 15000    | A+  | 929001157402 | 91787013 |
| 15 CorePro candle ND 5.5-40W E14 827 B35 FR | 40          | 5.5 | 470          | 85       | -          | Non-dimmable | 80  | 2700        | 15000    | A+  | 929001157702 | 91762386 |
| 15 CorePro candle ND 7-60W E14 827 B38 FR   | 60          | 7   | 806          | 115      | -          | Non-dimmable | 80  | 2700        | 15000    | A++ | 929001325102 | 96702994 |

LED Candles

LED candles & lustres


Classic LEDlustre



| Product Type                                   | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                                | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| MASTER LEDlustre DimTone                       |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 7 MAS LEDlustre DT 4-25W E14 P48 CL            | 25          | 4   | 250          | 65       | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001140002 | 96453780 |
| 8 MAS LEDlustre DT 4-25W E27 P48 CL            |             | 4   | 250          | 65       | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001140102 | 96453803 |
| 7 MAS LEDlustre DT 6-40W E14 P48 CL            | 40          | 6   | 470          | 75       | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001140602 | 96453582 |
| 8 MAS LEDlustre DT 6-40W E27 P48 CL            |             | 6   | 470          | 75       | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001140702 | 96453605 |
| 9 MAS LEDlustre DT 6-40W B22 P48 CL            | 60          | 6   | 470          | 75       | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001157302 | 96474778 |
| 7 MAS LEDlustre DT 8-60W P50 E14 827 CL        |             | 8   | 806          | 100      | -          |    | 80  | 2200-2700   | 25000    | A+  | 929001211902 | 96580677 |
| Classic LEDlustre DimTone                      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 10 CLA LEDlustre DT3.5-25W E27 CRI90 P45 CL    | 25          | 3.5 | 250          | 71       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002018402 | 99646363 |
| 11 CLA LEDlustre DT3.5-25W E14 CRI90 P45 CL    |             | 3.5 | 250          | 71       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002018502 | 99646387 |
| 10 CLA LEDlustre DT 3.2-25W E27 CRI90 P45 CL ■ |             | 3.2 | 250          | 63       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002393702 | 99770662 |
| 11 CLA LEDlustre DT3.2-25W E14 CRI90 P45 CL ■  |             | 3.2 | 250          | 63       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002393502 | 99770709 |
| 10 CLA LEDlustre DT6-40W E27 CRI90 P45 CL      | 40          | 6   | 470          | 78       | -          |    | 90  | 2700-2200   | 15000    | A+  | 929002018602 | 99646424 |
| 10 CLA LEDlustre DT 4.5-40W E27 CRI90 P45 CL ■ |             | 4.5 | 470          | 78       | -          |   | 90  | 2700-2200   | 15000    | A++ | 929002393802 | 99770747 |
| 11 CLA LEDlustre DT4.5-40W E14 CRI90 P45 CL ■  |             | 4.5 | 470          | 78       | -          |  | 90  | 2700-2200   | 15000    | A++ | 929002393602 | 99780234 |
| Classic LEDlustre Dimmable                     |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 1 CLA LEDlustre D 2.7-25W P45 E14 827 CL       | 25          | 2.7 | 250          | 93       | -          |  | 80  | 2700        | 15000    | A++ | 929001332302 | 96709863 |
| 3 CLA LEDlustre D 2.7-25W P45 E27 827 CL       |             | 2.7 | 250          | 93       | -          |  | 80  | 2700        | 15000    | A++ | 929001332402 | 96709887 |
| 3 CLA LEDlustre D 4.5-40W P45 E27 827 CL ■     |             | 4.5 | 470          | 63       | -          |  | 80  | 2700        | 15000    | A++ | 929002391402 | 99773434 |
| 1 CLA LEDlustre D 5-40W P45 E14 827 CL         | 40          | 5   | 470          | 94       | -          |  | 80  | 2700        | 15000    | A+  | 929001332502 | 96709900 |
| 1 CLA LEDlustre D 5-40W P45 E27 827 CL         |             | 5   | 470          | 94       | -          |  | 80  | 2700        | 15000    | A+  | 929001332602 | 96709924 |
| 15 CLA LEDlustre D 5-40W P45 B22 827 CL        |             | 5   | 470          | 94       | -          |  | 80  | 2700        | 15000    | A+  | 929001332702 | 96709948 |
| 1 CLA LEDlustre D 4.5-40W P45 E14 827 CL ■     |             | 4.5 | 470          | 78       | -          |  | 80  | 2700        | 15000    | A++ | 929002391302 | 99773410 |

■ Expected September 2020

Classic LEDlustre – Continued



| Product Type                                | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| Classic LEDlustre Gold Dimmable             |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 13 CLA LEDlustre D 5-32W P45 E14 822 GOLD   | 32          | 5   | 350          | 70       | -          |    | 80  | 2200        | 15000    | A+  | 929001896602 | 96815670 |
| 14 CLA LEDlustre D 5-32W P45 E27 822 GOLD   |             | 5   | 350          | 70       | -          |    | 80  | 2200        | 15000    | A+  | 929001896402 | 96814413 |
| Classic LEDlustre Non dimmable Clear        |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 2 CLA LEDlustre ND 2-25W P45 E14 827 CL     | 25          | 2   | 250          | 125      | -          |    | 80  | 2700        | 15000    | A++ | 929001238602 | 96574133 |
| 4 CLA LEDlustre ND 2-25W P45 E27 827 CL     |             | 2   | 250          | 125      | -          |    | 80  | 2700        | 15000    | A++ | 929001238702 | 96574157 |
| 15 CLA LEDlustre ND 2-25W P45 B22 827 CL    |             | 2   | 250          | 125      | -          |    | 80  | 2700        | 15000    | A++ | 929001815902 | 96766965 |
| 2 CLA LEDlustre ND 4.3-40W E14 827 P45 CL   | 40          | 4.3 | 470          | 109      | -          |    | 80  | 2700        | 15000    | A++ | 929001890402 | 96809716 |
| 4 CLA LEDlustre ND 4.3-40W E27 827 P45 CL   |             | 4.3 | 470          | 109      | -          |    | 80  | 2700        | 15000    | A++ | 929001890502 | 96809730 |
| 2 CLA LEDlustre ND 6.5-60W P45 E14 827 CL   | 60          | 6.5 | 806          | 124      | -          |    | 80  | 2700        | 15000    | A++ | 929002028502 | 99649166 |
| 4 CLA LEDlustre ND 6.5-60W P45 E27 827 CL   |             | 6.5 | 806          | 124      | -          |    | 80  | 2700        | 15000    | A++ | 929002029002 | 99649203 |
| Classic LEDlustre Non dimmable Frosted      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 5 CLA LEDlustre ND 2.2-25W P45 E14 FR       | 25          | 2.2 | 250          | 113      | -          |    | 80  | 2700        | 15000    | A++ | 929001345402 | 96706411 |
| 6 CLA LEDlustre ND 2.2-25W P45 E27 FR       |             | 2.2 | 250          | 113      | -          |    | 80  | 2700        | 15000    | A++ | 929001345602 | 96706459 |
| 5 CLA LEDlustre ND 4.3-40W E14 827 P45 FR   | 40          | 4.3 | 470          | 109      | -          |    | 80  | 2700        | 15000    | A++ | 929001345502 | 96706435 |
| 6 CLA LEDlustre ND 4.3-40W E27 827 P45 FR   |             | 4.3 | 470          | 109      | -          |    | 80  | 2700        | 15000    | A++ | 929001345702 | 96706473 |
| 5 CLA LEDlustre ND 6.5-60W P45 E14 827 FR   | 60          | 6.5 | 806          | 124      | -          |    | 80  | 2700        | 15000    | A++ | 929002028702 | 99649289 |
| 6 CLA LEDlustre ND 6.5-60W P45 E27 827 FR   |             | 6.5 | 806          | 124      | -          |   | 80  | 2700        | 15000    | A++ | 929002029202 | 99649340 |
| CorePro LEDlustre Non Dim Clear             |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 16 CorePro Lustre ND 4-25W E14 827 P45 CL   | 25          | 4   | 250          | 63       | -          |  | 80  | 2700        | 15000    | A+  | 929001142302 | 96507599 |
| 16 CorePro Lustre ND 5.5-40W E14 827 P45 CL | 40          | 5.5 | 470          | 91       | -          |  | 80  | 2700        | 15000    | A+  | 929001142602 | 96454831 |
| 17 CorePro Lustre ND 5.5-40W E27 827 P45 CL |             | 5.5 | 470          | 91       | -          |  | 80  | 2700        | 15000    | A+  | 929001175302 | 96507636 |
| CorePro LEDlustre Non Dim Frosted           |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| 18 CorePro Lustre ND 4-25W E14 827 P45 FR   | 25          | 4   | 250          | 63       | -          |  | 80  | 2700        | 15000    | A+  | 929001157502 | 91787037 |
| 19 CorePro Lustre ND 4-25W E27 827 P45 FR   |             | 4   | 250          | 63       | -          |  | 80  | 2700        | 15000    | A+  | 929001157602 | 91787051 |
| 18 CorePro Lustre ND 5.5-40W E14 827 P45 FR | 40          | 5.5 | 470          | 85       | -          |  | 80  | 2700        | 15000    | A+  | 929001157802 | 96474891 |
| 19 CorePro Lustre ND 5.5-40W E27 827 P45 FR |             | 5.5 | 470          | 91       | -          |  | 80  | 2700        | 15000    | A+  | 929001175402 | 96507650 |
| 18 CorePro Lustre ND 7-60W E14 827 P48 FR   | 60          | 7   | 806          | 115      | -          |  | 80  | 2700        | 15000    | A++ | 929001325202 | 96703014 |
| 19 CorePro Lustre ND 7-60W E27 827 P48 FR   |             | 7   | 806          | 115      | -          |  | 80  | 2700        | 15000    | A++ | 929001325302 | 96703038 |

# Philips LED tube

## The right LED tube every time

Industry leading LED range of fluorescent tube replacements

- Best in class lumen performance
- Best compatibility
- Easy installation

For general applications, Universal is the tube of choice.

For more demanding applications: use our Selector tool.

Find the **right** solution in our range using the **Selector tool** [productfinder.lighting.philips.com](https://productfinder.lighting.philips.com)

### MASTER Value LEDtube T8

- Easy and cost effective upgrade for fluorescent tubes (typical payback time within 1 year)
- 50,000 hours lifetime
- Up to 3700 lumen output
- Up to 155 lm/W

### CorePro LEDtube T8 Universal

- Works on every driver technology (EM/HF/Mains)
- Up to 2700 lumen output
- 1 year typical payback time for 24/7 operation\*
- Up to 3x longer lifetime\*

### MASTER LEDtube T5

- 50,000 hours lifetime
- Up to 155 lumen/Watt
- Up to 5600 lumen output

### MASTER LEDtube T8 sensor

- Integrated motion sensor
- Automatic dimming based on movement
- No extra sensors or wiring needed
- Up to 70% energy saving\*

### NEW CorePro LED PL-C, PL-L, PL-S & LED Circular

- Simple retrofit for fluorescent PL-C and PL-L lamps
- 30,000 hours lifetime
- Up to 60% energy saving\*

\*Compared to fluorescent lamps

## LED tubes

### T8 Universal

[www.philips.com/ledtube](https://www.philips.com/ledtube)



| Product Type                                                                                                             | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------------------------------------------------------------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                                                                                                          | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER VALUES LEDtube T8 Ultra Output Universal                                                                        |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube VLE UN 1200mm UO 16W830 T8                                                                                   | 36          | 16  | 2300         | 144      | 240        |    | 83  | 3000        | 50000    | A++ | 929002333002 | 99739171 |
| MAS LEDtube VLE UN 1200mm UO 16W840 T8                                                                                   |             | 16  | 2500         | 156      | 240        |    | 83  | 4000        | 50000    | A++ | 929002333102 | 99739195 |
| MAS LEDtube VLE UN 1200mm UO 16W865 T8                                                                                   |             | 16  | 2500         | 156      | 240        |    | 83  | 6500        | 50000    | A++ | 929002333202 | 99739218 |
| MAS LEDtube VLE UN 1500mm UO 24W830 T8                                                                                   | 58          | 24  | 3400         | 142      | 240        |    | 83  | 3000        | 50000    | A++ | 929002333302 | 99739232 |
| MAS LEDtube VLE UN 1500mm UO 24W840 T8                                                                                   |             | 24  | 3700         | 154      | 240        |    | 83  | 4000        | 50000    | A++ | 929002333402 | 99739256 |
| MAS LEDtube VLE UN 1500mm UO 24W865 T8                                                                                   |             | 24  | 3700         | 154      | 240        |    | 83  | 6500        | 50000    | A++ | 929002333502 | 99739270 |
| 2 CorePro LEDtube T8 High Output Universal                                                                               |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LEDtube UN 600mm HO 8W830 T8  | 18          | 8   | 850          | 106      | 240        |    | 80  | 3000        | 30000    | A+  | 929002419802 | 99782771 |
| CorePro LEDtube UN 600mm HO 8W840 T8  |             | 8   | 900          | 113      | 240        |    | 80  | 4000        | 30000    | A+  | 929002419902 | 99782795 |
| CorePro LEDtube UN 600mm HO 8W865 T8  |             | 8   | 900          | 113      | 240        |    | 80  | 6500        | 30000    | A+  | 929002420002 | 99782818 |
| CorePro LEDtube UN 1200mm HO 18W830 T8                                                                                   | 36          | 18  | 1850         | 103      | 240        |    | 80  | 3000        | 30000    | A+  | 929001869202 | 96801666 |
| CorePro LEDtube UN 1200mm HO 18W840 T8                                                                                   |             | 18  | 2000         | 111      | 240        |  | 80  | 4000        | 30000    | A+  | 929001869302 | 96801680 |
| CorePro LEDtube UN 1200mm HO 18W865 T8                                                                                   |             | 18  | 2000         | 111      | 240        |  | 80  | 6500        | 30000    | A+  | 929001869402 | 96801703 |
| CorePro LEDtube UN 1500mm HO 23W830 T8                                                                                   | 58          | 23  | 2500         | 109      | 240        |  | 80  | 3000        | 30000    | A+  | 929001869502 | 96801727 |
| CorePro LEDtube UN 1500mm HO 23W840 T8                                                                                   |             | 23  | 2700         | 117      | 240        |  | 80  | 4000        | 30000    | A+  | 929001869602 | 96801741 |
| CorePro LEDtube UN 1500mm HO 23W865 T8                                                                                   |             | 23  | 2700         | 117      | 240        |  | 80  | 6500        | 30000    | A+  | 929001869702 | 96801765 |

\*) "UE" stands for Ultra Efficiency. These LED tubes are identical to the Ultra Output range but have a much higher efficiency (172 Lm / W)

■ Expected September 2020

LED tubes

T8 EM/MAIN



1

MASTER LEDtube sensor



2

MASTER LEDtube T8 Food



3

MASTER LEDtube EM



4

MASTER Value LEDtube T8



= Dimmable



= Non-dimmable



FRAGILE



1 = ROTATING END  
(ONLY THE MASTER RANGE)



G13



10 PACK

| Product Type                             | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------------|-------------|------|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                          | W           | W    | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDtube T8 Sensor               |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube Sensor 1200mm HO 16.5W840 T8 | 36          | 16.5 | 2100         | 127      | 240        |    | 83  | 4000        | 50000    | A++ | 929001878502 | 96806029 |
| MAS LEDtube Sensor 1200mm HO 16.5W865 T8 |             | 16.5 | 2100         | 127      | 240        |    | 83  | 6500        | 50000    | A++ | 929001878602 | 96806043 |
| MAS LEDtube Sensor 1500mm HO 24W840 T8   | 58          | 24   | 3100         | 129      | 240        |    | 83  | 4000        | 50000    | A++ | 929001878702 | 96806067 |
| MAS LEDtube Sensor 1500mm HO 24W865 T8   |             | 24   | 3100         | 129      | 240        |    | 83  | 6500        | 50000    | A++ | 929001878802 | 96806081 |
| 2 MASTER LEDtube T8 FOOD                 |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 900mm 8.5W833 T8 Food        | 30          | 8.5  | 750          | 88       | 160        |    | 83  | 3300        | 50000    | A+  | 929001812102 | 96763919 |
| MAS LEDtube 1200mm 12W833 T8 Food        | 36          | 12   | 1000         | 83       | 160        |    | 83  | 3300        | 50000    | A+  | 929001812202 | 96763933 |
| MAS LEDtube 1500mm 20W833 T8 Food        | 58          | 20   | 1680         | 84       | 160        |    | 83  | 3300        | 50000    | A+  | 929001812302 | 96763957 |
| 3 MASTER LEDtube T8 High Output          |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 600mm HO 8W830 T8            | 18          | 8    | 1000         | 125      | 160        |    | 83  | 3000        | 50000    | A++ | 929001307002 | 96697474 |
| MAS LEDtube 600mm HO 8W840 T8            |             | 8    | 1050         | 131      | 160        |    | 83  | 4000        | 50000    | A++ | 929001307102 | 96697498 |
| MAS LEDtube 600mm HO 8W865 T8            |             | 8    | 1050         | 131      | 160        |    | 83  | 6500        | 50000    | A++ | 929001307202 | 96697511 |
| MAS LEDtube 1200mm HO 12.5W 830 T8       | 36          | 12.5 | 2000         | 160      | 160        |    | 83  | 3000        | 60000    | A++ | 929001922602 | 99592356 |
| MAS LEDtube 1200mm HO 12.5W 840 T8       |             | 12.5 | 2100         | 168      | 160        |   | 83  | 4000        | 60000    | A++ | 929001922702 | 99592370 |
| MAS LEDtube 1200mm HO 12.5W 865 T8       |             | 12.5 | 2100         | 168      | 160        |  | 83  | 6500        | 60000    | A++ | 929001922802 | 99592394 |
| MAS LEDtube 1500mm HO 18.2W 830 T8       | 58          | 18.2 | 2900         | 159      | 160        |  | 83  | 3000        | 60000    | A++ | 929001922902 | 99592417 |
| MAS LEDtube 1500mm HO 18.2W 840 T8       |             | 18.2 | 3100         | 170      | 160        |  | 83  | 4000        | 60000    | A++ | 929001923002 | 99592431 |
| MAS LEDtube 1500mm HO 18.2W 865 T8       |             | 18.2 | 3100         | 170      | 160        |  | 83  | 6500        | 60000    | A++ | 929001923102 | 99592455 |
| MASTER LEDtube 1800mm 25W 840 T8 ROT     | /           | 25   | 3700         | 148      | 160        |  | 83  | 4000        | 40000    | A++ | 929001161102 | 96480373 |
| 4 MASTER VALUE LEDtube T8 High Output    |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube VLE 600mm HO 8W 830 T8       | 18          | 8    | 1000         | 125      | 240        |  | 83  | 3000        | 50000    | A++ | 929002021102 | 99646790 |
| MAS LEDtube VLE 600mm HO 8W 840 T8       |             | 8    | 1050         | 131      | 240        |  | 83  | 4000        | 50000    | A++ | 929002021202 | 99646813 |
| MAS LEDtube VLE 600mm HO 8W 865 T8       |             | 8    | 1050         | 131      | 240        |  | 83  | 6500        | 50000    | A++ | 929002021302 | 99646837 |
| MAS LEDtube VLE 1200mm HO 14W 830 T8     | 36          | 14   | 2000         | 143      | 240        |  | 83  | 3000        | 50000    | A++ | 929002021402 | 99646851 |
| MAS LEDtube VLE 1200mm HO 14W 840 T8     |             | 14   | 2100         | 150      | 240        |  | 83  | 4000        | 50000    | A++ | 929002021502 | 99646875 |

Expected September 2020

78

T8 EM/MAIN – Continued



5

MAS LEDtube UO



6

MAS LEDtube UE



= Dimmable



= Non-dimmable



1 = ROTATING END



G13



10 PACK

| Product Type                           | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|----------------------------------------|-------------|------|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                        | W           | W    | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 4 MASTER VALUE LEDtube T8 High Output  |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube VLE 1200mm HO 14W 865 T8   | 36          | 14   | 2100         | 150      | 240        |    | 83  | 6500        | 50000    | A++ | 929002021602 | 99646899 |
| MAS LEDtube VLE 1500mm HO 20.5W 830 T8 | 58          | 20.5 | 2900         | 141      | 240        |    | 83  | 3000        | 50000    | A++ | 929002021702 | 99646912 |
| MAS LEDtube VLE 1500mm HO 20.5W 840 T8 |             | 20.5 | 3100         | 151      | 240        |    | 83  | 4000        | 50000    | A++ | 929002021802 | 99646936 |
| MAS LEDtube VLE 1500mm HO 20.5W 865 T8 |             | 20.5 | 3100         | 151      | 240        |    | 83  | 6500        | 50000    | A++ | 929002021902 | 99646950 |
| 4 MASTER VALUE LEDtube Ultra Output T8 |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube VLE 1200mm UO 16W 830 T8   | 36          | 16   | 2300         | 144      | 240        |    | 83  | 3000        | 50000    | A++ | 929002022002 | 99646974 |
| MAS LEDtube VLE 1200mm UO 16W 840 T8   |             | 16   | 2500         | 156      | 240        |    | 83  | 4000        | 50000    | A++ | 929002022102 | 99646998 |
| MAS LEDtube VLE 1200mm UO 16W 865 T8   |             | 16   | 2500         | 156      | 240        |    | 83  | 6500        | 50000    | A++ | 929002022202 | 99647018 |
| MAS LEDtube VLE 1500mm UO 24W 830 T8   | 58          | 24   | 3400         | 142      | 240        |    | 83  | 3000        | 50000    | A++ | 929002022302 | 99647032 |
| MAS LEDtube VLE 1500mm UO 24W 840 T8   |             | 24   | 3700         | 154      | 240        |    | 83  | 4000        | 50000    | A++ | 929002022402 | 99647056 |
| MAS LEDtube VLE 1500mm UO 24W 865 T8   |             | 24   | 3700         | 154      | 240        |    | 83  | 6500        | 50000    | A++ | 929002022502 | 99647070 |
| 5 MASTER LEDtube Ultra Output T8       |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 1200mm UO 15.5W 830 T8     | 36          | 15.5 | 2300         | 148      | 160        |    | 83  | 3000        | 60000    | A++ | 929002020502 | 99647216 |
| MAS LEDtube 1200mm UO 15.5W 840 T8     |             | 15.5 | 2500         | 161      | 160        |   | 83  | 4000        | 60000    | A++ | 929002020602 | 99647230 |
| MAS LEDtube 1200mm UO 15.5W 865 T8     |             | 15.5 | 2500         | 161      | 160        |  | 83  | 6500        | 60000    | A++ | 929002020702 | 99647254 |
| MAS LEDtube 1500mm UO 23W 830 T8       | 58          | 23   | 3400         | 148      | 160        |  | 83  | 3000        | 60000    | A++ | 929002020802 | 99647278 |
| MAS LEDtube 1500mm UO 23W 840 T8       |             | 23   | 3700         | 161      | 160        |  | 83  | 4000        | 60000    | A++ | 929002020902 | 99647292 |
| MAS LEDtube 1500mm UO 23W 865 T8       |             | 23   | 3700         | 161      | 160        |  | 83  | 6500        | 60000    | A++ | 929002021002 | 99647315 |
| 6 MASTER LEDtube T8 Ultra Efficiency   |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 1200mm UE 14.5W 840 T8     | 36          | 14.5 | 2500         | 172      | 160        |  | 83  | 4000        | 70000    | A++ | 929001376802 | 96731505 |
| MAS LEDtube 1200mm UE 14.5W 865 T8     |             | 14.5 | 2500         | 172      | 160        |  | 83  | 6500        | 70000    | A++ | 929001376902 | 96731529 |
| MAS LEDtube 1500mm UE 21.5W 840 T8     | 58          | 21.5 | 3700         | 172      | 160        |  | 83  | 4000        | 70000    | A++ | 929001377002 | 96731543 |
| MAS LEDtube 1500mm UE 21.5W 865 T8     |             | 21.5 | 3700         | 172      | 160        |  | 83  | 6500        | 70000    | A++ | 929001377102 | 96731567 |

Expected September 2020

79

LED tubes

T8 EM/MAIN – Continued



CorePro LEDtube T8

7

 = Dimmable

 = Non-dimmable

 G13

 10 PACK

| Product Type                    | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------|-------------|------|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                 | W           | W    | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| 7 CorePro LEDtube T8            |             |      |              |          |            |                                                                                     |     |             |          |     |              |          |
| CorePro LEDtube 600mm 8W840     | 18          | 8    | 800          | 100      | 240        |  | 80  | 4000        | 30000    | A+  | 929001338602 | 96711033 |
| CorePro LEDtube 600mm 8W865     |             | 8    | 800          | 100      | 240        |  | 80  | 6500        | 30000    | A+  | 929001338702 | 96711057 |
| CorePro LEDtube 1200mm 14.5W840 | 36          | 14.5 | 1600         | 110      | 240        |  | 80  | 4000        | 30000    | A+  | 929001338802 | 96711071 |
| CorePro LEDtube 1200mm 14.5W865 |             | 14.5 | 1600         | 110      | 240        |  | 80  | 6500        | 30000    | A+  | 929001338902 | 96711095 |
| CorePro LEDtube 1500mm 20W 840  | 58          | 20   | 2200         | 110      | 240        |  | 80  | 4000        | 30000    | A+  | 929001337902 | 96710913 |
| CorePro LEDtube 1500mm 20W 865  |             | 20   | 2200         | 110      | 240        |  | 80  | 6500        | 30000    | A+  | 929001338002 | 96710951 |

HF T8



MAS LEDtube HF HO T8

1



CorePro LEDtube HF

2

 = Dimmable

 = Non-dimmable

 G13

 10 PACK

| Product Type                       | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                    | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDtube HF T8             |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube HF 600mm HO 8W830 T8   | 18          | 8   | 1000         | 125      | 160        |  | 83  | 3000        | 60000    | A+  | 929001393102 | 96743539 |
| MAS LEDtube HF 600mm HO 8W840 T8   |             | 8   | 1050         | 131      | 160        |  | 83  | 4000        | 60000    | A+  | 929001393202 | 96743553 |
| MAS LEDtube HF 600mm HO 8W865 T8   |             | 8   | 1050         | 131      | 160        |  | 83  | 6500        | 60000    | A+  | 929001393302 | 96743676 |
| MAS LEDtube HF 1200mm HO 14W830 T8 | 36          | 14  | 2000         | 143      | 160        |  | 83  | 3000        | 60000    | A+  | 929001284302 | 96687529 |
| MAS LEDtube HF 1200mm HO 14W840 T8 |             | 14  | 2100         | 150      | 160        |  | 83  | 4000        | 60000    | A++ | 929001284102 | 96687482 |
| MAS LEDtube HF 1200mm HO 14W865 T8 |             | 14  | 2100         | 150      | 160        |  | 83  | 6500        | 60000    | A++ | 929001284202 | 96687505 |

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

HF T8 – Continued



MAS LEDtube HF HO T8

1



CorePro LEDtube HF

2

 = Dimmable
  = Non-dimmable

 G13
  10 PACK

| Product Type                        | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------|-------------|-----|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                     | W           | W   | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDtube HF T8              |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| MAS LEDtube HF 1500mm HO 20W830 T8  | 58          | 20  | 2900         | 145      | 160        |  | 83  | 3000        | 60000    | A+  | 929001284602 | 96687581 |
| MAS LEDtube HF 1500mm HO 20W840 T8  |             | 20  | 3100         | 155      | 160        |  | 83  | 4000        | 60000    | A++ | 929001284402 | 96687543 |
| MAS LEDtube HF 1500mm HO 20W865 T8  |             | 20  | 3100         | 155      | 160        |  | 83  | 6500        | 60000    | A++ | 929001284502 | 96687567 |
| 1 MASTER LEDtube HF T8 Ultra Output |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| MAS LEDtube HF 1200mm UO 16W830 T8  | 36          | 16  | 2350         | 147      | 160        |  | 83  | 3000        | 60000    | A+  | 929001300202 | 96688007 |
| MAS LEDtube HF 1200mm UO 16W840 T8  |             | 16  | 2500         | 156      | 160        |  | 83  | 4000        | 60000    | A++ | 929001300002 | 96687963 |
| MAS LEDtube HF 1200mm UO 16W865 T8  |             | 16  | 2500         | 156      | 160        |  | 83  | 6500        | 60000    | A++ | 929001300102 | 96687987 |
| MAS LEDtube HF 1500mm UO 24W830 T8  | 58          | 24  | 3500         | 146      | 160        |  | 83  | 3000        | 60000    | A++ | 929001300502 | 96688069 |
| MAS LEDtube HF 1500mm UO 24W840 T8  |             | 24  | 3700         | 154      | 160        |  | 83  | 4000        | 60000    | A++ | 929001300302 | 96688021 |
| MAS LEDtube HF 1500mm UO 24W865 T8  |             | 24  | 3700         | 154      | 160        |  | 83  | 6500        | 60000    | A++ | 929001300402 | 96688045 |
| 2 CorePro LEDtube HF T8             |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| CorePro LEDtube HF 600mm 9W840 T8 G | 18          | 9   | 800          | 89       | 240        |  | 83  | 4000        | 30000    | A   | 929001249502 | 96652176 |
| CorePro LEDtube HF 600mm 9W865 T8 G |             | 9   | 800          | 89       | 240        |  | 83  | 6500        | 30000    | A   | 929001249602 | 96652190 |

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

LED tubes

HF T5



MAS LEDtube  
HF T5 HE



MAS LEDtube  
HF T5 HO



MAS LEDtube  
HF T5 UO

 = Dimmable

 = Non-dimmable

 G13

 10 PACK

| Product Type                            | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-----------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                         | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDtube HF T5 High Efficiency  |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube HF 600mm HE 8W 830 T5       | 14          | 8   | 1000         | 125      | 160        |    | 83  | 3000        | 50000    | A+  | 929001390702 | 96743232 |
| MAS LEDtube HF 600mm HE 8W 840 T5       |             | 8   | 1050         | 131      | 160        |    | 83  | 4000        | 50000    | A+  | 929001390802 | 96743256 |
| MAS LEDtube HF 600mm HE 8W 865 T5       |             | 8   | 1050         | 131      | 160        |    | 83  | 6500        | 50000    | A+  | 929001390902 | 96743270 |
| MAS LEDtube HF 1200mm HE 16.5W 830 T5   | 28          | 17  | 2300         | 139      | 160        |    | 83  | 3000        | 50000    | A+  | 929001391002 | 96743294 |
| MAS LEDtube HF 1200mm HE 16.5W 840 T5   |             | 17  | 2500         | 152      | 160        |    | 83  | 4000        | 50000    | A++ | 929001391102 | 96743317 |
| MAS LEDtube HF 1200mm HE 16.5W 865 T5   |             | 17  | 2500         | 152      | 160        |    | 83  | 6500        | 50000    | A++ | 929001391202 | 96743331 |
| MAS LEDtube HF 1500mm HE 20W 830 T5     | 35          | 20  | 2800         | 140      | 160        |    | 83  | 3000        | 50000    | A+  | 929001391302 | 96743355 |
| MAS LEDtube HF 1500mm HE 20W 840 T5     |             | 20  | 3000         | 150      | 160        |    | 83  | 4000        | 50000    | A++ | 929001391402 | 96743379 |
| MAS LEDtube HF 1500mm HE 20W 865 T5     |             | 20  | 3000         | 150      | 160        |    | 83  | 6500        | 50000    | A++ | 929001391502 | 96743393 |
| 2 MASTER LEDtube HF T5 High Output      |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube HF 1500mm HO 26W 830 T5     | 49          | 26  | 3700         | 142      | 160        |    | 83  | 3000        | 50000    | A+  | 929001296102 | 96685525 |
| MAS LEDtube HF 1500mm HO 26W 840 T5     |             | 26  | 3900         | 150      | 160        |    | 83  | 4000        | 50000    | A++ | 929001296202 | 96685549 |
| MAS LEDtube HF 1500mm HO 26W 865 T5     |             | 26  | 3900         | 150      | 160        |    | 83  | 6500        | 50000    | A++ | 929001296302 | 96685563 |
| MAS LEDtube HF 1500mm HO 26W 830 T5 G ■ |             | 26  | 3700         | 142      | 160        |   | 83  | 3000        | 50000    | -   | 929002352302 | 99749576 |
| MAS LEDtube HF 1500mm HO 26W 840 T5 G ■ |             | 26  | 3900         | 150      | 160        |  | 83  | 4000        | 50000    | -   | 929002352402 | 99749590 |
| MAS LEDtube HF 1500mm HO 26W 865 T5 G ■ |             | 26  | 3900         | 150      | 160        |  | 83  | 6500        | 50000    | -   | 929002352502 | 99749613 |
| MAS LEDtube HF 1200mm HO 26W 830 T5     | 54          | 26  | 3700         | 142      | 160        |  | 83  | 3000        | 50000    | A+  | 929001338302 | 96705278 |
| MAS LEDtube HF 1200mm HO 26W 840 T5     |             | 26  | 3900         | 150      | 160        |  | 83  | 4000        | 50000    | A++ | 929001338402 | 96705292 |
| MAS LEDtube HF 1200mm HO 26W 865 T5     |             | 26  | 3900         | 150      | 160        |  | 83  | 6500        | 50000    | A++ | 929001338502 | 96705315 |
| MAS LEDtube HF 1200mm HO 26W 830 T5 G ■ |             | 26  | 3700         | 142      | 160        |  | 83  | 3000        | 50000    | -   | 929002352002 | 99749514 |
| MAS LEDtube HF 1200mm HO 26W 840 T5 G ■ |             | 26  | 3900         | 150      | 160        |  | 83  | 4000        | 50000    | -   | 929002352102 | 99749538 |
| MAS LEDtube HF 1200mm HO 26W 865 T5 G ■ |             | 26  | 3900         | 150      | 160        |  | 83  | 6500        | 50000    | -   | 929002352202 | 99749552 |

HF T5 – Continued



MAS LEDtube  
HF T5 HE



MAS LEDtube  
HF T5 HO



MAS LEDtube  
HF T5 UO

 = Dimmable

 = Non-dimmable

 G13

 10 PACK

| Product Type                        | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------|-------------|-----|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                     | W           | W   | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| 3 MASTER LEDtube HF T5 Ultra Output |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| MAS LEDtube HF 1500mm UO 36W 830 T5 | 80          | 36  | 5200         | 144      | 160        |  | 83  | 3000        | 50000    | A++ | 929001346102 | 96705995 |
| MAS LEDtube HF 1500mm UO 36W 840 T5 |             | 36  | 5600         | 156      | 160        |  | 83  | 4000        | 50000    | A++ | 929001346202 | 96706039 |
| MAS LEDtube HF 1500mm UO 36W 865 T5 |             | 36  | 5600         | 156      | 160        |  | 83  | 6500        | 50000    | A++ | 929001346302 | 96706053 |

LED tubes

T5 EM/MAINS



MAS LEDtube  
EM/Mains T5 HO

1

 = Dimmable

 = Non-dimmable

 G13

 10 PACK

| Product Type                               | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------------|-------------|------|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                            | W           | W    | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 MASTER LEDtube EM/Mains T5 High Output   |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 1500mm HO 26W 830 T5           | 49          | 26   | 3600         | 138      | 200        |    | 80  | 3000        | 50000    | A++ | 929001908802 | 96819296 |
| MAS LEDtube 1500mm HO 26W 840 T5           |             | 26   | 3900         | 150      | 200        |    | 80  | 4000        | 50000    | A++ | 929001908902 | 96819319 |
| MAS LEDtube 1500mm HO 26W 865 T5           |             | 26   | 3900         | 150      | 200        |    | 80  | 6500        | 50000    | A++ | 929001909002 | 96819333 |
| MAS LEDtube 1200mm HO 26W 830 T5           | 54          | 26   | 3600         | 138      | 200        |    | 80  | 3000        | 50000    | A++ | 929001908502 | 96819210 |
| MAS LEDtube 1200mm HO 26W 840 T5           |             | 26   | 3900         | 150      | 200        |    | 80  | 4000        | 50000    | A++ | 929001908602 | 96819234 |
| MAS LEDtube 1200mm HO 26W 865 T5           |             | 26   | 3900         | 150      | 200        |    | 80  | 6500        | 50000    | A++ | 929001908702 | 96819258 |
| MASTER LEDtube EM/Mains T5 High Efficiency |             |      |              |          |            |                                                                                       |     |             |          |     |              |          |
| MAS LEDtube 600mm HE 8W 830 T5 ■           | 14          | 8    | 1000         | 125      | TBC        |    | 83  | 3000        | 50000    | -   | 929002420608 | 99783433 |
| MAS LEDtube 600mm HE 8W 840 T5 ■           |             | 8    | 1050         | 131      | TBC        |    | 83  | 4000        | 50000    | -   | 929002420708 | 99783457 |
| MAS LEDtube 600mm HE 8W 865 T5 ■           |             | 8    | 1050         | 131      | TBC        |    | 83  | 6500        | 50000    | -   | 929002420808 | 99783471 |
| MAS LEDtube 1200mm HE 16.5W 830 T5 ■       | 28          | 16.5 | 2300         | 139      | TBC        |    | 83  | 3000        | 50000    | -   | 929002420908 | 99783495 |
| MAS LEDtube 1200mm HE 16.5W 840 T5 ■       |             | 16.5 | 2500         | 152      | TBC        |    | 83  | 4000        | 50000    | -   | 929002421008 | 99783518 |
| MAS LEDtube 1200mm HE 16.5W 865 T5 ■       |             | 16.5 | 2500         | 152      | TBC        |    | 83  | 6500        | 50000    | -   | 929002421108 | 99783532 |
| MAS LEDtube 1500mm HE 20W 830 T5 ■         | 35          | 20   | 2800         | 140      | TBC        |   | 83  | 3000        | 50000    | -   | 929002421208 | 99783556 |
| MAS LEDtube 1500mm HE 20W 840 T5 ■         |             | 20   | 3000         | 150      | TBC        |  | 83  | 4000        | 50000    | -   | 929002421308 | 99783570 |
| MAS LEDtube 1500mm HE 20W 865 T5 ■         |             | 20   | 3000         | 150      | TBC        |  | 83  | 6500        | 50000    | -   | 929002421408 | 99783594 |

■ Expected September 2020

LED tubes and PL-lamps

LED starter



LED Starter

40 PACK

| Product Type                        | 12 NC        | EOC code |
|-------------------------------------|--------------|----------|
| MASTER LEDtube Starter EMP GenII OP | 929001801432 | 96819654 |

LED PL-C



1

CorePro LED PL-C / 2-pins



2

CorePro LED PL-C / 4-pins



= Dimmable



= Non-dimmable



Improved light output



ROTATING END



G24d-1 / G24d-2 / G24d-3



10 PACK

| Product Type                       | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                              | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|------------------------------------|-------------|-----|--------------|----------|------------|---------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                    | W           | W   | lm           | lm/W     | °          |                                                                                       |     | K           | Hrs.     |     |              |          |
| 1 CorePro LED PLC 2 pin            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LED PLC 4.5W 830 2P G24d-1 | 13          | 4.5 | 475          | 106      | -          |    | 83  | 3000        | 30000    | A++ | 929001350702 | 96706596 |
| CorePro LED PLC 4.5W 840 2P G24d-1 |             | 4.5 | 500          | 111      | -          |   | 83  | 4000        | 30000    | A++ | 929001350802 | 96706619 |
| CorePro LED PLC 6.5W 830 2P G24d-2 | 18          | 6.5 | 650          | 100      | -          |  | 83  | 3000        | 30000    | A+  | 929001201402 | 96541272 |
| CorePro LED PLC 6.5W 840 2P G24d-2 |             | 6.5 | 700          | 108      | -          |  | 83  | 4000        | 30000    | A+  | 929001201502 | 96541296 |
| CorePro LED PLC 8.5W 830 2P G24d-3 | 26          | 8.5 | 950          | 112      | -          |  | 83  | 3000        | 30000    | A+  | 929001201202 | 96541234 |
| CorePro LED PLC 8.5W 840 2P G24d-3 |             | 8.5 | 1000         | 118      | -          |  | 83  | 4000        | 30000    | A+  | 929001201302 | 96541258 |
| 2 CorePro LED PLC 4 pin            |             |     |              |          |            |                                                                                       |     |             |          |     |              |          |
| CorePro LED PLC 4.5W 830 4P G24q-1 | 13          | 4.5 | 475          | 106      | -          |  | 83  | 3000        | 30000    | A+  | 929001351002 | 96706633 |
| CorePro LED PLC 4.5W 840 4P G24q-1 |             | 4.5 | 500          | 111      | -          |  | 83  | 4000        | 30000    | A+  | 929001351102 | 96706657 |
| CorePro LED PLC 6.5W 830 4P G24q-2 | 18          | 6.5 | 650          | 100      | -          |  | 83  | 3000        | 30000    | A+  | 929001201002 | 96541197 |
| CorePro LED PLC 6.5W 840 4P G24q-2 |             | 6.5 | 700          | 108      | -          |  | 83  | 4000        | 30000    | A+  | 929001201102 | 96541210 |
| CorePro LED PLC 9W 830 4P G24q-3   | 26          | 9   | 950          | 106      | -          |  | 83  | 3000        | 30000    | A+  | 929001200802 | 96541159 |
| CorePro LED PLC 9W 840 4P G24q-3   |             | 9   | 1000         | 111      | -          |  | 83  | 4000        | 30000    | A+  | 929001200902 | 96541173 |

# LED tubes and PL-lamps

## LED PL-L



CorePro LED PL-L

= Dimmable

= Non-dimmable



ROTATING END



2G11



10 PACK

| Product Type                         | Traditional | LED  | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|--------------------------------------|-------------|------|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                      | W           | W    | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| CorePro LED PLL HF 16.5W 830 4P 2G11 | 36          | 16.5 | 2000         | 121      | -          |          | 83  | 3000        | 30000    | A+  | 929001381502 | 96739662 |
| CorePro LED PLL HF 16.5W 840 4P 2G11 |             | 16.5 | 2100         | 127      | -          |          | 83  | 4000        | 30000    | A+  | 929001381602 | 96739747 |
| CorePro LED PLL HF 16.5W 865 4P 2G11 |             | 16.5 | 2100         | 127      | -          |          | 83  | 6500        | 30000    | A+  | 929001381702 | 96739761 |
| CorePro LED PLL HF 24W 830 4P 2G11   | 55          | 24   | 3200         | 133      | 160        |          | 83  | 3000        | 30000    | A+  | 929001920402 | 96828397 |
| CorePro LED PLL HF 24W 840 4P 2G11   |             | 24   | 3400         | 142      | 160        |          | 83  | 4000        | 30000    | A+  | 929001920502 | 96828410 |
| CorePro LED PLL HF 24W 865 4P 2G11   |             | 24   | 3400         | 142      | 160        |          | 83  | 6500        | 30000    | A+  | 929001920602 | 96828434 |

## LED PL-S



CorePro LED PL-S

= Dimmable

= Non-dimmable



ROTATING END



PL-S



20 PACK

| Product Type                  | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                               | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| CorePro LED PLS 5W 830 2P G23 | 11          | 5   | 520          | 104      | 120        |          | 82  | 3000        | 30000    | A+  | 929001926302 | 99596668 |
| CorePro LED PLS 5W 840 2P G23 |             | 5   | 550          | 110      | 120        |          | 82  | 4000        | 30000    | A+  | 929001926402 | 99596682 |

## CorePro LED Circular



CorePro LED Circular

= Dimmable

= Non-dimmable



G10q



20 PACK

| Product Type                      | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-----------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                   | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| Circular                          |             |     |              |          |            |          |     |             |          |     |              |          |
| CorePro LED Circular 20W 840 G10q | 32          | 20  | 2100         | 105      | 120        |          | 80  | 4000        | 30000    | A+  | 929002068002 | 99660420 |
| CorePro LED Circular 20W 865 G10q |             | 20  | 2100         | 105      | 120        |          | 80  | 6500        | 30000    | A+  | 929002068102 | 99660444 |

# Philips TrueForce LED lamps

Save energy and provide the perfect light for every space

Up to 50% energy savings\*

6 kV surge protection

High efficiency (>170 lm/W)

Plug & play: EM system compatible

TrueForce LED Road

Industry leading LED lamps for HID replacement:

- Powerful light output, optically efficient
- Instant upgrade – no need to replace or modify fixture
- 50,000 hours lifetime, 5 years warranty

More features at a glance



Using existing optics of conventional luminaire



Pleasant white light with CRI 70



Optically efficient, emits light towards direction of use

## TrueForce LED Industrial and Retail

- Plug & play: EM system compatible
- Up to 65% energy savings\*
- Pleasant white light (CRI 80)
- IP 40 rating

\* Compared to conventional systems

## TrueForce LED Urban

- Perfect Fit – compact size
- Energy saving up to 75%\*
- Optically efficient
- IP65 rating
- Pleasant white light with CRI 80
- Overheating protection



**NEW!** Portfolio upgrade and range extension

LED HID

The affordable LED solution for High Intensity Discharge (HID) lamp replacement, Philips TrueForce LED lamps provide an easy LED solution with a fast payback to replace High-Intensity Discharge (HID) lamps.

TrueForce Urban-Post Top HPL & SON Replacement

lighting.philips.co.uk/products/trueforce-led-lamps

| <br>TrueForce Urban 21W | <br>TrueForce Urban 28W | <br>TrueForce Urban 42W | <br>TrueForce Urban 42W E40 | <br>TrueForce Core LED HPL 13W FR | <br>TForce Core LED PT 30-27W E27 FR | <br>TrueForce Core LED HPL 18W FR | <br>TForce Core LED PT 50-42W E27 FR | <br>TrueForce Core LED HPL 26W FR |  = Dimmable |  = Non-dimmable |  E27 |  E40 |  6 PACK |       |       |              |          |
|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------|-------|--------------|----------|
| Product Type                                                                                             |                                                                                                          |                                                                                                          |                                                                                                              | Traditional                                                                                                        |                                                                                                                       | LED                                                                                                                | Lumen Output                                                                                                          | Efficacy                                                                                                            | Beam Angle                                                                                     | Dimmable                                                                                           | CRI                                                                                     | Colour Temp                                                                             | Lifetime                                                                                   | EEL   | 12 NC | EOC code     |          |
|                                                                                                          |                                                                                                          |                                                                                                          |                                                                                                              | W                                                                                                                  |                                                                                                                       | W                                                                                                                  | lm                                                                                                                    | lm/W                                                                                                                | °                                                                                              |                                                                                                    |                                                                                         | K                                                                                       | Hrs.                                                                                       |       |       |              |          |
| TrueForce Urban                                                                                          |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       |                                                                                                                    |                                                                                                                       |                                                                                                                     |                                                                                                |                                                                                                    |                                                                                         |                                                                                         |                                                                                            |       |       |              |          |
| 1 TForce LED HPL ND 30-21W E27 840                                                                       |                                                                                                          |                                                                                                          |                                                                                                              | 80 (HPL 80W, SON 50W)                                                                                              |                                                                                                                       | 21                                                                                                                 | 3000                                                                                                                  | 142                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 4000                                                                                       | 50000 | A++   | 929002006202 | 99638160 |
| 1 TForce LED HPL ND 28-21W E27 830                                                                       |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 21                                                                                                                 | 2850                                                                                                                  | 135                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 50000 | A++   | 929002006102 | 99638146 |
| 2 TForce LED HPL ND 40-28W E27 840                                                                       |                                                                                                          |                                                                                                          |                                                                                                              | 125 (HPL 125W, SON 70W)                                                                                            |                                                                                                                       | 28                                                                                                                 | 4000                                                                                                                  | 142                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 4000                                                                                       | 50000 | A++   | 929002006402 | 99638207 |
| 2 TForce LED HPL ND 38-28W E27 830                                                                       |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 28                                                                                                                 | 3800                                                                                                                  | 135                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 50000 | A++   | 929002006302 | 99638184 |
| 3 TForce LED HPL ND 57-42W E27 830                                                                       |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 42                                                                                                                 | 5700                                                                                                                  | 135                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 50000 | A++   | 929002006502 | 99638221 |
| 3 TForce LED HPL ND 60-42W E27 840                                                                       |                                                                                                          |                                                                                                          |                                                                                                              | 200 (HPL 200W, SON 100W)                                                                                           |                                                                                                                       | 42                                                                                                                 | 6000                                                                                                                  | 142                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 4000                                                                                       | 50000 | A++   | 929002006602 | 99638245 |
| 4 TForce LED HPL ND 57-42W E40 830                                                                       |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 42                                                                                                                 | 5700                                                                                                                  | 135                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 50000 | A++   | 929002006702 | 99638269 |
| 4 TForce LED HPL ND 60-42W E40 840                                                                       |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 42                                                                                                                 | 6000                                                                                                                  | 142                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 4000                                                                                       | 50000 | A++   | 929002006802 | 99638283 |
| TrueForce Urban Core                                                                                     |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       |                                                                                                                    |                                                                                                                       |                                                                                                                     |                                                                                                |                                                                                                    |                                                                                         |                                                                                         |                                                                                            |       |       |              |          |
| 5 TForce Core LED HPL 13W E27 830 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              | 50                                                                                                                 |                                                                                                                       | 13                                                                                                                 | 2000                                                                                                                  | 154                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 25000 | A++   | 929002349702 | 99750251 |
| 5 TForce Core LED HPL 13W E27 840 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 13                                                                                                                 | 2000                                                                                                                  | 154                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 4000                                                                                       | 25000 | A++   | 929002349802 | 99750275 |
| 6 TForce Core LED PT 30-27W E27 830 FR                                                                   |                                                                                                          |                                                                                                          |                                                                                                              | 80                                                                                                                 |                                                                                                                       | 27                                                                                                                 | 3000                                                                                                                  | 111                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 25000 | A+    | 929001925302 | 99594381 |
| 7 TForce Core LED HPL 18W E27 830 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 18                                                                                                                 | 3000                                                                                                                  | 167                                                                                                                 | 360                                                                                            |                                                                                                    |      | 80                                                                                      | 3000                                                                                       | 25000 | A++   | 929002349902 | 99750299 |
| 7 TForce Core LED HPL 18W E27 840 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              | 125                                                                                                                |                                                                                                                       | 18                                                                                                                 | 3000                                                                                                                  | 167                                                                                                                 | 360                                                                                            |                                                                                                    |     | 80                                                                                      | 4000                                                                                       | 25000 | A++   | 929002350002 | 99750312 |
| 8 TForce Core LED PT 50-42W E27 830 FR                                                                   |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 42                                                                                                                 | 5000                                                                                                                  | 119                                                                                                                 | 360                                                                                            |                                                                                                    |    | 80                                                                                      | 3000                                                                                       | 25000 | A+    | 929001925002 | 99594428 |
| 9 TForce Core LED HPL 26W E27 830 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 26                                                                                                                 | 4000                                                                                                                  | 154                                                                                                                 | 360                                                                                            |                                                                                                    |    | 80                                                                                      | 3000                                                                                       | 25000 | A++   | 929002350102 | 99750336 |
| 9 TForce Core LED HPL 26W E27 840 FR                                                                     |                                                                                                          |                                                                                                          |                                                                                                              |                                                                                                                    |                                                                                                                       | 26                                                                                                                 | 4000                                                                                                                  | 154                                                                                                                 | 360                                                                                            |                                                                                                    |    | 80                                                                                      | 4000                                                                                       | 25000 | A++   | 929002350202 | 99750350 |

TrueForce Highbay HPIT, HPI, SON-T, SON & HPL Replacement



TrueForce LED HPI



TrueForce LED HB MV

 = Dimmable
  = Non-dimmable

 E27
  E40
  4 PACK

| Product Type                            | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                             | CRI | Colour Temp | Lifetime | EEL         | 12 NC        | EOC code |
|-----------------------------------------|-------------|-----|--------------|----------|------------|--------------------------------------------------------------------------------------|-----|-------------|----------|-------------|--------------|----------|
|                                         | W           | W   | lm           | lm/W     | °          |                                                                                      |     | K           | Hrs.     |             |              |          |
| Trueforce Highbay Universal             |             |     |              |          |            |                                                                                      |     |             |          |             |              |          |
| TForce LED HPI UN 88W E40 840 NB ■      | 250         | 95  | 13000        | 128      | -          |   | 80  | 4000        | 50000    | A+ (Mains)  | 929002350702 | 99753672 |
| TForce LED HPI UN 88W E40 840 WB ■      |             | 95  | 13000        | 140      | -          |   | 80  | 4000        | 50000    | A++ (Mains) | 929002350802 | 99753696 |
| TForce LED HPI UN 145W E40 840 NB ■     | 400         | 140 | 20000        | 133      | -          |   | 80  | 4000        | 50000    | A+ (Mains)  | 929002350902 | 99753719 |
| TForce LED HPI UN 145W E40 840 WB ■     |             | 140 | 20000        | 140      | -          |   | 80  | 4000        | 50000    | A++ (Mains) | 929002351002 | 99753733 |
| 1 Trueforce Highbay Instantfit          |             |     |              |          |            |                                                                                      |     |             |          |             |              |          |
| TForce LED HPI ND 110-88W E40 840 60D   | 250         | 88  | 11000        | 125      | 60         |   | 80  | 4000        | 50000    | A+          | 929001356802 | 96713785 |
| TForce LED HPI ND 110-88W E40 840 120D  |             | 88  | 11000        | 125      | 120        |   | 80  | 4000        | 50000    | A+          | 929001356902 | 96713822 |
| TForce LED HPI ND 200-145W E40 840 60D  | 400         | 145 | 20000        | 137      | 60         |   | 80  | 4000        | 50000    | A+          | 929001357002 | 96713860 |
| TForce LED HPI ND 200-145W E40 840 120D |             | 145 | 20000        | 137      | 120        |   | 80  | 4000        | 50000    | A+          | 929001357102 | 96713884 |
| 2 Trueforce Highbay Direct Mains        |             |     |              |          |            |                                                                                      |     |             |          |             |              |          |
| TForce LED HB MV ND 120-100W E40 840 NB | 250         | 100 | 12000        | 120      | 60         |   | 80  | 4000        | 50000    | A+          | 929001929702 | 99596767 |
| TForce LED HB MV ND 120-100W E40 840 WB |             | 100 | 12000        | 120      | 120        |   | 80  | 4000        | 50000    | A+          | 929001929802 | 99596781 |
| TForce LED HB MV ND 200-160W E40 840 NB | 400         | 160 | 20000        | 125      | 60         |   | 80  | 4000        | 50000    | A+          | 929001812402 | 99596705 |
| TForce LED HB MV ND 200-160W E40 840 WB |             | 160 | 20000        | 125      | 120        |  | 80  | 4000        | 50000    | A+          | 929001812502 | 99596729 |

■ Expected September 2020

## LED HID

## TrueForce Road SONT



 = Dimmable

 = Non-dimmable



| Product Type                      | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL   | 12 NC | EOC code                |
|-----------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-------|-------|-------------------------|
|                                   | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |       |       |                         |
| TrueForce Road SONT HF Instantfit |             |     |              |          |            |          |     |             |          |       |       |                         |
| ① TForce LED Road 40-25W E27 730  | 50          | 25  | 4000         | 160      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929001999402   99632519 |
| ① TForce LED Road 42-25W E27 740  |             | 25  | 4200         | 168      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929001999502   99632533 |
| ② TForce LED Road 55-35W E27 730  | 70          | 35  | 5500         | 157      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929001898402   96811153 |
| ② TForce LED Road 60-35W E27 740  |             | 35  | 6000         | 171      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929001898502   96811177 |
| ③ TForce LED Road 84-55W E40 730  | 100         | 55  | 8400         | 152      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929002007402   99639044 |
| ③ TForce LED Road 90-55W E40 740  |             | 55  | 9000         | 163      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929002007502   99639068 |
| ④ TForce LED Road 112-68W E40 730 | 100-150     | 68  | 11200        | 164      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929002007602   99639082 |
| ④ TForce LED Road 120-68W E40 740 |             | 68  | 12000        | 176      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929002007702   99639105 |
| TrueForce Road SONT Direct Mains  |             |     |              |          |            |          |     |             |          |       |       |                         |
| ② TForce LED Road 35W E27 730 MV  | 70          | 35  | 5500         | 157      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929002221708   99674830 |
| ② TForce LED Road 35W E27 740 MV  |             | 35  | 6000         | 171      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929002068508   99674854 |
| ③ TForce LED Road 55W E40 730 MV  | 100         | 55  | 8400         | 153      | 360        |          | ✖   | 70          | 3000     | 50000 | A++   | 929002221608   99674779 |
| ③ TForce LED Road 55W E40 740 MV  |             | 55  | 9000         | 164      | 360        |          | ✖   | 70          | 4000     | 50000 | A++   | 929002068708   99674793 |

## Decorative Range

### Vintage (spiral) filament lamps




 = Dimmable

 = Non-dimmable



| Product Type                              | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable                                                                            | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|-------------------------------------------|-------------|-----|--------------|----------|------------|-------------------------------------------------------------------------------------|-----|-------------|----------|-----|--------------|----------|
|                                           | W           | W   | lm           | lm/W     | °          |                                                                                     |     | K           | Hrs.     |     |              |          |
| Vintage: spiral filament bulbs            |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 1 LED classic 25W A60 E27 GOLD SP D SRT4  | 25          | 5.5 | 250          | 45       | -          |  | 80  | 2000        | 15000    | A   | 929002223801 | 99676032 |
| Vintage: spiral filament candle B35       |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 2 LED classic 15W B35 E14 GOLD SP D SRT4  | 15          | 3.5 | 136          | 39       | -          |  | 80  | 2000        | 15000    | A   | 929002224301 | 99676131 |
| Vintage: spiral filament candle P45       |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 3 LED classic 15W P45 E27 GOLD SP D SRT4  | 15          | 3.5 | 136          | 38       | -          |  | 80  | 2000        | 15000    | A   | 929002224201 | 99676117 |
| 4 LED classic 15W P45 E14 GOLD SP D SRT4  |             | 3.5 | 136          | 39       | -          |  | 80  | 2000        | 15000    | A   | 929002224401 | 99676155 |
| Vintage: spiral filament ST64             |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 5 LED classic 25W ST64 E27 GOLD SP D SRT4 | 25          | 5.5 | 250          | 45       | -          |  | 80  | 2000        | 15000    | A   | 929002223901 | 99676056 |
| Vintage: spiral filament globe            |             |     |              |          |            |                                                                                     |     |             |          |     |              |          |
| 6 LED classic 25W G93 E27 GOLD SP D SRT4  | 25          | 5.5 | 250          | 45       | -          |  | 80  | 2000        | 15000    | A   | 929002224001 | 99676070 |

### Vintage cord pendants



 = Dimmab

 = Non-dimmable



4 PACK

[illegible]

Decorative Range

Smoky filament lamps, Eyecatch & Crown Mirror



1  
LEDgiant G200  
smoky dimmable



2  
LEDgiant A160  
smoky dimmable



3  
LEDgiant T65  
smoky dimmable



4  
Classic LED  
mushroom



5  
Classic LED  
diamond



6  
LED classic-giant  
E27 G200



7  
LED classic-giant  
E27 A160



8  
LED classic-giant  
E27 T65



9  
LED classic CM A60  
E27 WW CL D SRT4



10  
LEDclassic  
G120 CM D

☾ = Dimmable


☒ = Non-dimmable

4 PACK

| Product Type                                | Traditional | LED | Lumen Output | Efficacy | Beam Angle | Dimmable | CRI | Colour Temp | Lifetime | EEL | 12 NC        | EOC code |
|---------------------------------------------|-------------|-----|--------------|----------|------------|----------|-----|-------------|----------|-----|--------------|----------|
|                                             | W           | W   | lm           | lm/W     | °          |          |     | K           | Hrs.     |     |              |          |
| Giant filament lamps                        |             |     |              |          |            |          |     |             |          |     |              |          |
| 6 LED classic-giant 40W E27 G200 GOLD DIM   | 40          | 6.5 | 470          | 72       | -          | ☾        | 80  | 2000        | 15000    | A+  | 929001873401 | 96803479 |
| 7 LED classic-giant 40W E27 A160 GOLD DIM   |             | 6.5 | 470          | 72       | -          | ☾        | 80  | 2000        | 15000    | A+  | 929001873501 | 96803493 |
| 8 LED classic-giant 40W E27 T65 GOLD DIM    |             | 6.5 | 470          | 72       | -          | ☾        | 80  | 2000        | 15000    | A+  | 929001873601 | 96803516 |
| Smoky filament lamps                        |             |     |              |          |            |          |     |             |          |     |              |          |
| 1 LED giant 25W E27 G200 4000K smoky D      | 25          | 6.5 | 270          | 41       | -          | ☾        | 80  | 4000        | 15000    | A   | 929001903101 | 96815069 |
| 2 LED giant 25W E27 A160 4000K smoky D      |             | 6.5 | 270          | 41       | -          | ☾        | 80  | 4000        | 15000    | A   | 929001903201 | 96815106 |
| 3 LED giant 25W E27 T65 4000K smoky D       |             | 6.5 | 270          | 41       | -          | ☾        | 80  | 4000        | 15000    | A   | 929001903301 | 96815120 |
| Eyecatch                                    |             |     |              |          |            |          |     |             |          |     |              |          |
| 4 LED classic 30W Mushroom E27 2000K GOLD D | 30          | 5   | 350          | 70       | -          | ☾        | 80  | 2000        | 15000    | A+  | 929001935601 | 99593513 |
| 5 LED classic 40W Diamond E27 2700K CL D    | 40          | 5   | 500          | 100      | -          | ☾        | 80  | 2700        | 15000    | A+  | 929001935701 | 99593537 |
| Crown Mirror                                |             |     |              |          |            |          |     |             |          |     |              |          |
| 9 LED classic CM 48W A60 E27 WW CL D SRT4   | 48          | 7.5 | 610          | 81       | -          | ☾        | 80  | 2700        | 15000    | A+  | 929001333501 | 96709269 |
| 10 LED classic 50W G120 E27 2700K CM D      | 50          | 8   | 700          | 87       | -          | ☾        | 80  | 2700        | 15000    | A+  | 929001935401 | 99593414 |

PHILIPS

Lighting



Philips Conversion Tool for conventional lamps

Tired of sourcing lamps from multiple suppliers?  
Are some of your popular conventional lamp stock items now discontinued?

With our Lamps and **Drivers Conversion Tool**, you can find the Philips equivalent of **any conventional lamp and driver**!



3 simple steps:



1 Register or sign in



2 Enter the name, part code or description of the product you need (can be a non-Philips product)



3 Click the relevant lamp in the search results ...

... the Conversion Tool will then display the Philips version of the same product!

Great features:

- Use the comprehensive product filter to assist in the search
- Compare the products side-by-side for any differences (dimensions, wattage, temperature range, etc).
- Export your search results with all associated specification
- Search multiple items at the same time

Try it now: [www.philips.com/conversiontool](http://www.philips.com/conversiontool)





© 2020 Signify Holding. All rights reserved. Signify reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

[philips.co.uk/lighting](https://philips.co.uk/lighting)  
[professional.trade.lighting@signify.com](mailto:professional.trade.lighting@signify.com)