

# UNICRIMP

## Q-FIRE RANGE

**NEW!**

# DON'T GET CAUGHT OUT BY THE LATEST REGS

Prevent cables from premature collapse during a fire and keep emergency services and the public safe

BS7671 IET Wiring Regulations 18th Edition, Chapter 52: Selection and erection of wiring systems, provides requirements for the methods of support of wiring systems in escape routes.

**Regulation 521.10.202** requires cables to be adequately supported against their premature collapse in the event of a fire. This applies throughout the installation and not just in escape routes.

**Section 527.1** Precautions within a fire-segregated compartment, regulation 527.1.3 notes that where the compartment provides a means of evacuation in an emergency the cables also need to satisfy the requirements of the CPR in respect of their reaction to fire.

## Saddle Clips & P Clips

- Assist installation of fire cable to meet the requirement of BS 5839-1: 2017
- Tested & approved to BS 476 Pt.6 and BS 476 Pt.7




| Part Number | Description               | Colour | Ref. | 1mm    | 1.5mm           | 2.5mm           | 4mm    | Fixing Dia. | Pack Qty |
|-------------|---------------------------|--------|------|--------|-----------------|-----------------|--------|-------------|----------|
| QSC302LSFR  | Red 302 Saddle Clip LSF   | Red    | 302  | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QSC302LSFB  | Black 302 Saddle Clip LSF | Black  | 302  | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QSC302LSFW  | White 302 Saddle Clip LSF | White  | 302  | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QSC342LSFR  | Red 342 Saddle Clip LSF   | Red    | 342  | 4L/1.0 | 3L/1.5 - 4L/1.5 | 2L/2.5 - 3L/2.5 |        | 5mm         | 50       |
| QSC342LSFB  | Black 342 Saddle Clip LSF | Black  | 342  | 4L/1.0 | 3L/1.5 - 4L/1.5 | 2L/2.5 - 3L/2.5 |        | 5mm         | 50       |
| QSC342LSFW  | White 342 Saddle Clip LSF | White  | 342  | 4L/1.0 | 3L/1.5 - 4L/1.5 | 2L/2.5 - 3L/2.5 |        | 5mm         | 50       |
| QSC382LSFR  | Red 382 Saddle Clip LSF   | Red    | 382  |        |                 |                 | 2L/4.0 | 5mm         | 50       |
| QSC382LSFB  | Black 382 Saddle Clip LSF | Black  | 382  |        |                 |                 | 2L/4.0 | 5mm         | 50       |
| QSC382LSFW  | White 382 Saddle Clip LSF | White  | 382  |        |                 |                 | 2L/4.0 | 5mm         | 50       |
| QPC28LSFR   | Red 28 P Clip LSF         | Red    | 28   | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QPC28LSFB   | Black 28 P Clip LSF       | Black  | 28   | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QPC28LSFW   | White 28 P Clip LSF       | White  | 28   | 3L/1.0 | 2L/1.5          |                 |        | 5mm         | 50       |
| QPC30LSFR   | Red 30 P Clip LSF         | Red    | 30   | 4L/1.0 | 3L/1.5          |                 |        | 5mm         | 50       |
| QPC30LSFB   | Black 30 P Clip LSF       | Black  | 30   | 4L/1.0 | 3L/1.5          |                 |        | 5mm         | 50       |
| QPC30LSFW   | White 30 P Clip LSF       | White  | 30   | 4L/1.0 | 3L/1.5          |                 |        | 5mm         | 50       |
| QPC32LSFR   | Red 32 P Clip LSF         | Red    | 32   |        |                 | 2L/2.5          |        | 5mm         | 50       |
| QPC32LSFB   | Black 32 P Clip LSF       | Black  | 32   |        |                 | 2L/2.5          |        | 5mm         | 50       |
| QPC32LSFW   | White 32 P Clip LSF       | White  | 32   |        |                 | 2L/2.5          |        | 5mm         | 50       |
| QPC34LSFR   | Red 34 P Clip LSF         | Red    | 34   |        | 4L/1.5          | 3L/2.5          |        | 5mm         | 50       |
| QPC34LSFB   | Black 34 P Clip LSF       | Black  | 34   |        | 4L/1.5          | 3L/2.5          |        | 5mm         | 50       |
| QPC34LSFW   | White 34 P Clip LSF       | White  | 34   |        | 4L/1.5          | 3L/2.5          |        | 5mm         | 50       |
| QPC37LSFR   | Red 37 P Clip LSF         | Red    | 37   |        |                 | 4L/2.5          | 2L/4.0 | 5mm         | 50       |
| QPC37LSFB   | Black 37 P Clip LSF       | Black  | 37   |        |                 | 4L/2.5          | 2L/4.0 | 5mm         | 50       |
| QPC37LSFW   | White 37 P Clip LSF       | White  | 37   |        |                 | 4L/2.5          | 2L/4.0 | 5mm         | 50       |

## Stainless Steel Roller Ball Cable Ties



- Minimum loop tensile strength 4.6mm wide = 44kg
- Made from 316 grade steel
- Minimum loop tensile strength 7.9mm wide = 110kg

Dimensions A, D & E: Nominal    Dimensions B & C: +-0.4mm




| Part Number | A     | B     | C      | D      | E     | Bundle Dia. Max. | Pack Qty |
|-------------|-------|-------|--------|--------|-------|------------------|----------|
| QSST150S    | 150mm | 4.6mm | 0.25mm | 6.4mm  | 4mm   | 35mm             | 100      |
| QSST200S    | 200mm | 4.6mm | 0.25mm | 6.4mm  | 4mm   | 50mm             | 100      |
| QSST300S    | 300mm | 4.6mm | 0.25mm | 6.4mm  | 4mm   | 83mm             | 100      |
| QSST360S    | 360mm | 4.6mm | 0.25mm | 6.4mm  | 4mm   | 100mm            | 100      |
| QSST520S    | 520mm | 4.6mm | 0.25mm | 6.4mm  | 4mm   | 150mm            | 100      |
| QSST300LH   | 300mm | 7.9mm | 0.25mm | 10.6mm | 5.4mm | 83mm             | 100      |
| QSST360LH   | 360mm | 7.9mm | 0.25mm | 10.6mm | 5.4mm | 100mm            | 100      |
| QSST520LH   | 520mm | 7.9mm | 0.25mm | 10.6mm | 5.4mm | 150mm            | 50       |
| QSST840LH   | 840mm | 7.9mm | 0.25mm | 10.6mm | 5.4mm | 250mm            | 50       |

## Stainless Steel Mounts



| Part Number | Description                        | Dimensions       | Fixing Dia. | Max. Tie Width | Pack Qty |
|-------------|------------------------------------|------------------|-------------|----------------|----------|
| QSSTM-4     | Stainless Steel Cable Tie Mount M4 | 15 x 29.20 x 5mm | 4.2mm       | 10mm           | 50       |
| QSSTM-6     | Stainless Steel Cable Tie Mount M6 | 15 x 29.20 x 5mm | 6.2mm       | 10mm           | 50       |

## Fire-Safe Cable Clips



| Part Number | Description                         | Suitable Trunking Size | Pack Qty |
|-------------|-------------------------------------|------------------------|----------|
| QFGFC25     | Fire-Safe Cable Clips 25mm (120Min) | 25mm                   | 10       |
| QFGFC40     | Fire-Safe Cable Clips 40mm          | 40mm                   | 10       |
| QFGFC50     | Fire-Safe Cable Clips 50mm          | 50mm                   | 10       |